

More Possibilities. The Scaffolding System.

LAYHER ACCESS SOLUTIONS CATALOGUE 2023/2024





LADDERS FROM PAGE 8



Single ladders
Double ladders
Multifunction ladders
Alu telescopic stage
Working plattform
Aluminium steps
Wooden steps
Accessories
Spare parts
Roof ladders

ACCESSES FROM PAGE 32



Accesses	32
Start-stairway	35
Stairways	36
Stairways with platform	38
Maintenance platforms	40
Bridging stairways	42
Accessories	44

ROLLING TOWERS FROM PAGE 46



Rolling tower configurator	48
Amendment of standard DIN EN 1004	50
Safety structure P2	52
SoloTower	54
Zifa	60
Uni light	66
Uni compact	76
Uni standard	84
Uni wide	94
Uni Comfort	102
Staro rolling tower	106
Extension and spare parts	114



ALU BRIDGING BEAM FROM PAGE 106

NOTICE



Telescopic Stages Alu bridging beam 21 or 106 106 All dimensions and weights are guideline values.

Component weights are subject to fluctuations due to tolerances and may therefore diverge from what is specified. Subject to technical modification.

Our deliveries shall be made exclusively in accordance with our currently valid General Terms of Sale. These include the following provisions:

The place of performance is Gueglingen-Eibensbach.

Title to the delivered goods shall be retained until full payment has been made.

The fully GTC you can find here: gtc.layher.com

Steel components are hot-dip galvanized according to EN ISO 1461 and DASt guideline 022. Connection parts or other small pieces can be galvanized according to EN ISO 4042.

Please request the specific instructions for assembly and use when ordering. Protected by copyright. Not to be reproduced, either in whole or in part. Misprints and errors excepted.





Further Information, you can find in the Layher Info. Just scan the QR Code.





Further information, you can find in the software. Just scan the QR Code.

MADE IN GERMANY – MADE BY LAYHER



QUALITY MADE IN GERMANY.

Quality made by Layher comes from Gueglingen-Eibensbach. Our company has set down deep local roots since it was established. Right up until today, development, production, logistics and management are all in one place. Proximity to development, logistics and administration creates benefits to our customers around the world: short ways, short response times, controlled quality and manufacturing. The production can be adapted to the requirements at short notice and to the needs of the customers.

SIMPLY SAFE. THE ACCESS SOLUTIONS.

This brand promise made by Layher is the expression of a brand philosophy that we've been living by for over 75 years. Quality assurance, future-proofing, delivery-securing, operational safety and long-lasting partnership are advantages that can be used to extend or increase your business opportunities and success in the long term. With comprehensive services, a permanent range of training courses and an ethos of customer focus, more than 1,900 dedicated Layher employees are creating more possibilities for our customers every single day. In 45 countries all over the world.

SUSTAINABILITY AT LAYHER.

We've long been acting with a clear focus, with a view to both economic and ecological sustainability in all our process steps. Social responsibility towards employees, clients and society as a whole are at the very centre of this. We're a dependable employer, active in protecting our resources. The sparing use of work materials as a feature of our sustainable approach is fundamental to how we see ourselves: we already take care to ensure sustainable building methods when planning a new production facility, for example by greening the roofs or using photovoltaic systems. We also value locations that are close by, avoiding unnecessary CO_2 emissions due to long traffic routes. The topic of sustainability is firmly embedded in Layher's organisational structure thanks to its energy management team. Their work has paid off in particular in the form of DIN EN ISO 50001 certification.



Discover the world of Layher in its company film at: yt-image-en.layher.com













MORE SPEED

High level of material availability, effective delivery service and quick assembly and dismantling of the scaffolding systems thanks to 100% fitting accuracy.

MORE SAFETY

Outstanding quality and precision coupled with a long service life – confirmed internationally through independent certifications, inspections and approvals. Continuity and long-term partnership.

MORE PROXIMITY

Comprehensive personal consultation and close-knit delivery network. Global presence through our own subsidiaries. Family-owned company that works closely with its customers.

MORE SIMPLICITY

Economical scaffolding systems that have been proven in practice, available with an extensive product range. Cross-system combinations for versatile use. Rapid decision making thanks to efficient structures and processes.

MORE FUTURE

Thanks to permanent product innovations and the improvement of existing parts. By opening up new areas of business. With an integrated system to ensure high profitability and retention of investment value. Through an extensive range of training opportunities and seminars to ensure that customers are always right up-to-date with the latest technical and commercial developments.

Layher Lightweight: Through the use of high-tensile steel, a new production process, and an improved design, we have succeeded in minimising the weight of the core components of our systems – while maintaining or raising load-bearing capacity.

REQUIREMENTS OF THE DIN EN 131

DIN EN 131-1

With effect from 1 January 2018, extensive amendments to the standard will come into force for ladders used in the commercial field as simple ladders and will require a cross-piece for simple ladders with a length of 3 metres and above. This also includes multi-function ladders usable as simple ladders. The width of the cross-piece is proportionate to the ladder length and to the external width of the ladder, widening as the ladder length increases.

What does that mean for dealers? As a general principle your warehouse stocks are protected. You can still sell the ladders you purchased prior to 1 January 2018 without cross-pieces.

- Layher recommends however that simple ladders be immediately modified to comply with the current standard in accordance with DIN EN 131-1.
- Even multifunctional ladders such as the Layher telescopic ladder TOPIC 1058 must have a base widening in the lean-to position.

What does that mean for end users? Commercial users can use their simple ladders without cross-pieces until the next scheduled ladder inspection. After that, the ladders must be upgraded to conform to the new standard (i.e. with cross-pieces).

• Layher ladders are, thanks to the Combigrip ladder foot, simple to equip with cross-pieces so that they conform to the valid standard.

DIN EN 131-2

All ladders will be categorised as commercial-use or private-use-only ladders. This categorisation is based on a differing basic load during individual tests on the ladders (2250 N to 2700 N). Furthermore, 'durability test for double ladders', 'slip resistance test on floors for simple ladders', 'stability test of simple ladders' have been added. The purpose of these additional tests is to improve the stability and safety of the products when in use. Ladders approved for commercial use may be used in private households too.

What does that mean for dealers? When selling the ladders, the intended use (private or commercial purposes) must be borne in mind. The approved application is identified by the following pictograms.



 All Layher ladders meet, without exception, the requirements for commercial use and hence also for private use.

LADDER EXAMINATION

- Every Layher ladder will be examined before leaving the plant.
- Please note the date the next examination on the ladder label (depending on the quantity of uses).

What does that mean for end users? In the commercial field, only ladders approved for that purpose and identified by appropriate pictograms may be used.

All Layher ladders meet, without exception, the requirements for commercial use and hence also for private use.

DIN EN 131-3

Since September 1, 2018 user information (instructions for assembly and use) must be supplied in printed form with every ladder. The label must now show the precisely specified DIN pictograms.

What does that mean for dealers? Since September 1, 2018 instructions for assembly and use must be supplied with every ladder sold. This must be forwarded by the dealer to the customer.

Layher will implement this requirement starting on the date specified to do so. Instructions for assembly and use will then be enclosed ex works in the ladder packaging. Alternatively, they can be downloaded for printout in the 'Mediathek' at downloads.layher.com free of charge.

What does that mean for end users? The instructions for assembly and use must be kept to hand during use of the ladder.

DIN EN 131-4

Since September 2020 the amendments to standard DIN EN 131-4 apply. This means that multi-purpose ladders like the Layher car boot ladder *TOPIC* 1057.112 with 4x3 rungs, which can be used as a work platform, must be delivered by the manufacturer including matching platforms.

- Layher Steigtechnik is offering with immediate effect a simple, high-quality and economical solution: the car boot ladder 4x3 including platform with reference number 1057.043 as a KIT – consisting of car boot ladder *TOPIC* 1057 and platform.
- The telescopic ladder TOPIC 1058 with base widening, Ref. no. 1016.175 corresponds to latest version of the DIN EN 131-4.

What does that mean for customers and end users?

- After the new DIN EN 131-4 has come into effect, dealers may continue to sell ladders in stock that were produced in accordance with the previous standard.
- After the new DIN EN 131-4 has come into effect, customers may also continue to use already purchased ladders that were produced in accordance with the previous standard until the next scheduled ladder inspection.
- Layher recommends an annual examination.
- The examination must be documented and archived and must be performed by a qualified person.

SAFER WORKING IN ACCORDANCE WITH TRBS 2121-2 FOR MORE SAFETY AT THE WORKPLACE

TRBS 2121-2 are technical rules for operating safety that govern the commercial use of ladders. They are not separate legal regulations. They specify, within the scope of their application, the requirements of the German Ordinance on Industrial Safety and Health. By compliance with these Technical Rules, contractors / commercial users can work on the assumption that the appropriate requirements of the Ordinance are met and that they are thus acting in conformity with the law.



- The commercial user may use ladders as workplaces when standing with both feet on a step (min. 80 mm depth) or platform.
- The use of step ladders or platform ladders as high-level workplaces is permitted without restriction up to a platform height of 2 metres.
- For a platform height between 2 metres and 5 metres, ladders may be used for work in limited periods (up to 2 hours per work shift).
- Layher offers in its simple ladder and double ladder range various ladder models with steps and / or platform.
- Layher also offers a suspended platform (Ref. No. 1016.003) as a retrofit set, which can to used to upgrade existing rung ladders from Layher and allow them to remain in use as workplaces.

Use of rung ladders as workplaces in exceptional cases:

- In specifically justified exceptional cases (e.g. for work in narrow shafts, ergonomic reasons), working on portable ladders with rungs is permissible.
- The specific reasons must be documented by the contractor / commercial user in the risk assessment to be conducted for every activity / every site.

Ladders as accesses

- Up to a height of 5 metres, rung ladders and step ladders may remain in use as accesses (entry / exit) to high-level workplaces.
- Above 5 metres, ladders may only be used as accesses when this is only a very infrequent occurrence.
- Layher recommends, for alternative access to high-level workplaces above 5 metres, scaffolding stair towers made using Layher Allround Scaffolding.



LAYHER LADDERS

THE QUALITY IS IN THE DETAILS



Plastic-sheathed steel joints

Play-free screw connection for long life.



Stile section

Torsion stiff stile section for high loads at low weight.
 Beading along the outer stile face prevents damage to the rung flanges, for example when they are slid over the edges of the truck loading area.



Quadruple folding

- Increased contact area by rung folding on the inner stile face.
- Higher forces can be transmitted.
- Optimal stile-rung-connection.



Triangular profile and grooving

- Sure footing by heavily grooved rungs and steps. R12 slip resistance in step direction.
- Increased turning protection within the stiles thanks to triangular rung shape.



Combigrip ladder foot

- Optimal hold in the stile with good slipping prevention.
- Easy and fast retrofitting of ladder cross-pieces for single ladders.

The load-bearing capacity of Layher Ladders is always 150 kg – if nothing different is mentioned.

With Layher ladders you don't just get the statutory warranty, but benefit from a 5-year Layher warranty. It covers material and workmanship flaws in all aluminium and steel parts. It starts from the purchase date of the product, as printed on your receipt.

The claims arising from this warranty will be processed at the location of one of our many branches or delivery warehouses in Germany or at our headquarters.

Documented safety: Layher products can be measured by these quality and safety standards:



Single ladder wide TOPIC 1054

The wide single ladder for even more comfortable standing – increased stability and improved lateral stability. Slip-resistant plastic shoes for sure footing.

Clear width:	390 mm
Outer width to 16 rungs:	448 mm
Outer width from 18 rungs:	450 mm
Rung spacing:	280 mm
Cross-piece width (from 12 rungs):	1130 mm



TIP:

comply with the new requirements of DIN EN 131-1, which will specify a cross-piece for simple ladders of 3 metres and more length. The Layher Combigrip ladder foot can be quickly and easily retrofitted in *TOPIC* ladders of earlier generations.

Retrofit kits see page 2



Single ladder wide TOPIC 1054

Length [m]	Number of rungs	Standing height [m]	Stile height [mm]	Weight approx. [kg]	Ref. No.	
1.75	6	0.70	64	4.0	1054.006	
2.30	8	1.25	64	5.0	1054.008	
2.85	10	1.80	64	6.0	1054.010	
3.50	12	2.40	64	9.5	1054.012	(j)
4.05	14	2.90	64	11.0	1054.014	(j)
4.65	16	3.45	64	12.5	1054.016	1
5.20	18	3.95	76	13.5	1054.018	(j)
5.75	20	4.50	76	15.5	1054.020	(j)
6.30	22	5.00	76	16.5	1054.022	()
6.85	24	5.55	100	18.0	1054.024	1



Ladders, highlighted with ① will be delivered ex works with cross-piece.



Suitable accessories





Suspended platform

hook

Other accessories can be found on page 26.

Single step ladder TOPIC 1042

Single ladder with steps for a wider standing area. Easy to use, maximum safety thanks to slip-resistant plastic shoes.





Clear width:	390 mm
Outer width:	450 mm
Step spacing:	250 mm
Step length:	80 mm
Stile height:	76 mm
Cross-piece width (from 12 rungs):	1130 mm

, 1,000

TIP: With the Layher Combigrip ladder foot, you automatically comply with the new requirements of DIN EN 131-1, which will specify a cross-piece for simple ladders of 3 metres and more length. The Layher Combigrip ladder foot can be quickly and easily retrofitted in *TOPIC* ladders of earlier generations.



Single step ladder TOPIC 1042

Length [m]	Number of rungs	Standing height [m]	Max. load [kg]	Weight approx. [kg]	Ref. No.	
1.65	6	0.65	250	5.0	1042.006 🖴	
1.90	7	0.90	250	5.6	1042.007 🖴	
2.15	8	1.10	250	6.2	1042.008 🛎	
2.40	9	1.35	250	7.0	1042.009 😐	
2.65	10	1.60	250	7.6	1042.010 🖴	
2.99	12	2.15	250	12.4	1042.012 🖴	1
3.24	13	2.40	250	12.9	1042.013 🕒	()
3.49	14	2.60	250	13.4	1042.014 😐	(
3.74	15	2.85	250	13.9	1042.015 😐	()
3.99	16	3.10	225	14.3	1042.016 😐	1
4.24	17	3.35	225	14.8	1042.017 😐	()
4.49	18	3.60	225	15.3	1042.018 😐	()



Ladders, highlighted with 0 will be delivered ex works with cross-piece.



Wooden single ladder 1023 with rungs

The wooden single ladder has 80 mm wide and grooved steps for high slip resistance. Stiles are made of sturdy pine wood and the steps are made of solid beech. For more safety, the steps are inserted through a grooved joint in the stile, glued and screwed. The 1023.012 is delivered with a crossbar.

Clear width: Outer width: Step spacing: Stile height: 365 mm 409 mm 250 mm 70 mm





Wooden single ladder 1052

The wooden single ladder is a simple, sturdy yet high-quality ladder. The stiles are made of solid red pine. The rungs are made from sturdy beechwood. Thanks to the special square-section studs and a special gluing process, a durable and permanent connection between stile and rung is achieved.

350 mm

400 mm

280 mm

65 mm

Clear width:
Outer width:
Rung spacing:
Stile height:





Wooden single ladder 1023

Length [m]	Number of rungs	Standing height [m]	Weight approx. [kg]	Ref. No.	
1.80	6	0.71	5.5	1023.006	
2.30	8	1.18	7.0	1023.008	
2.80	10	1.65	9.0	1023.010	
3.39	12	2.15	11.5	1023.012	(



Suitable accessories

Ladder wall

mounting

Wooden single ladder 1052

Length [m]	Number of rungs	Standing height [m]	Stile height [mm]	Weight approx. [kg]	Ref. No.
1.90	6	0.80	65	5.5	1052.206 🛎
2.45	8	1.35	65	7.5	1052.208 🛎
2.99	10	1.85	65	9.5	1052.210 🛎



Suitable accessories





Suspended Wood stile platform extension set EasyFix

Ladder shoe Ladder wall for wooden mounting

Other accessories can be found on page 26.

n page 26.

Other accessories can be found on page 26.

ladder

Wooden single ladder for builders 1036

The classic wooden single ladder is ideal for many applications, e.g. rugged use on construction sites. Stiles and rungs made of narrow-ringed spruce. Due to its conical design with pointed bar ends, the builder's ladder 1036 corresponds to the DIN 4567-3 and is therefore not subject to cross-piece obligation according to DIN EN 131.

Stile width:	40 m	m
Outer width at top:	385 I	mm
Rung spacing:	280 I	mm





Length [m]	Number of rungs	Standing height [m]	Stile height [mm]	Outer width at bottom [mm]	Weight approx. [kg]	Ref. No.
3.00	10	1.85	85	430	11.9	1036.010
4.00	14	2.90	90	450	16.6	1036.014
5.00	17	3.70	95	470	20.2	1036.017
6.00	21	4.75	100	490	25.0	1036.021



Suitable accessories



Ladder wall mounting

Other accessories can be found on page 26.



Combination single ladder 1029

mm mm mm

The classic single ladder has remarkable weight advantages thanks to the aluminium rungs which are suitable for regular and continuous use. Ideal for electricians and craftsmen as the ladder is electrically non-conductive. Information on the insulation resistance, in accordance with VDE 0100, is available. From a length of 3 m the ladder 1029 does not correspond to the newest version of the DIN EN 131.

Available while stocks last.

Clear width:	300 mr
Outer width:	350 mr
Rung spacing:	280 mr
Stile height:	75 mm



Combination single ladder 1029

Length [m]	Number of rungs	Standing height [m]	Stile height [mm]	Weight approx. [kg]	Ref. No.
2.40	8	1.30	75	5.8	1029.008
2.95	10	1.85	75	6.8	1029.010
3.50	12	2.40	75	8.6	1029.012
4.05	14	2.90	75	9.6	1029.014
4.35	15	3.15	75	10.2	1029.015
4.90	17	3.70	75	11.8	1029.017



Suitable accessories





Extension step ladder TOPIC 1032



The Extension Step Ladder *TOPIC* 1032 has the proven torsionstiff stile sections for high loads with a low weight. It also has, in accordance with DIN EN 131-1, a 1130 mm wide cross-piece to widen the base.

The extending ladder (top section) is behind the bottom section, enabling smooth ascents and descents while reducing the risk of stumbling.

Clear width:390 mmOuter width:450 mmRung spacing:250 mmCross-piece width:1130 mmStile height:76 mm





Extension step ladder TOPIC 1032

Length contr. [m]	Length extend. [m]	Number of rungs	Standing height [m]	Weight approx. [kg]	Ref. No.
2.29	3.30	2 x 8	2.10	15.0	1032.008 🖷
2.79	4.30	2 x 10	3.10	17.8	1032.010 🖷
3.29	5.30	2 x 12	4.00	20.5	1032.012 🖷
3.79	6.30	2 x 14	4.95	23.3	1032.014 🖷

THE BENEFITS FOR YOU

other (like a platform).

Step spacing of 250 mm.
Maximum load of 150 kg.

Cross-piece for all four ladder sizes.

Comfortable width of 390 mm.

resistance.

Steps made of aluminium, grooved for better anti-slip

Comfortable stance with two steps one behind the

Sturdy aluminium fittings and engaging hooks.

▶ 80 mm deep steps, conforming to TRBS 2121-2 guidelines.



Suitable accessories







Top rollers Suspension hook

Cross-piece \ castors

Wall bracket Ins



Extension ladder TOPIC 1035

Clear width top section:

Outer width:

TIP:

Rung spacing:

Clear width bottom section:

Length contr. [m]	Length extend. [m]	Number of rungs	Standing height [m]	Stile height [mm]	Weight approx. [kg]	Ref. No.	
1.75	2.85	2 x 6	1.80	64	7.6	1035.006 🛎	
2.39	3.80	2 x 8	2.65	64	12.5	1035.008	()
2.94	4.80	2 x 10	3.70	76	14.6	1035.010	()
3.49	5.95	2 x 12	4.75	76	18.4	1035.012	()
4.09	7.05	2 x 14	5.85	100	22.2	1035.014	()
4.64	8.00	2 x 16	6.60	100	24.6	1035.016	(
5.19	9.10	2 x 18	7.65	100	28.8	1035.018	()

Ladders, highlighted with (1) will be delivered ex works with cross-piece.



Other accessories can be found on page 26.

Length contr. [m]	Length extend. [m]	Number of rungs	Standing height [m]	Weight approx. [kg]	Ref. No.	
4.09	7.15	2 x 14	5.80	23.6	1037.014	(j)
4.64	8.30	2 x 16	6.85	26.2	1037.016	1
5.19	9.10	2 x 18	7.60	31.0	1037.018	()
5.74	10.25	2 x 20	8.70	34.4	1037.020	1
6.29	11.35	2 x 22	9.75	37.6	1037.022	1

Ladders, highlighted with (1) will be delivered ex works with cross-piece.



Wooden double ladder with steps 1020

The classic craftsman's ladder. With 80 mm wide steps, access from either side and complete with tool bag, over-spreading prevented by 2 polyester straps, adjustable clamping pins, sturdily designed and galvanized steel hinges with bucket hook, metal catch at bottom of ladder to secure it during transport. Stiles of solid red pine. Rungs made of sturdy beechwood. Thanks to the special square-section studs and a special gluing process, a durable and permanent connection between stile and rung is achieved.



Wooden double ladder 1038

The classic craftsman's ladder. Access from either side and complete with tool bag, over-spreading prevented by 2 polyester straps, adjustable clamping pins, sturdily designed and galvanized steel hinges with bucket hook, metal catch at bottom of ladder to secure it during transport. Stiles of solid red pine. Rungs made of sturdy beechwood. Thanks to the special square-section studs and a special gluing process, a durable and permanent connection between stile and rung is achieved.



Wooden double ladder with steps 1020

Length [m]	Number of steps	Standing height [m]	Outer width at bottom [mm]	Weight approx. [kg]	Ref. No.	
1.15	2 x 4	0.47	0.50	7.7	1020.004	
1.40	2 x 5	0.70	0.53	9.6	1020.005	
1.65	2 x 6	0.94	0.56	11.6	1020.006	
1.90	2 x 7	1.18	0.58	13.6	1020.007	
2.15	2 x 8	1.41	0.61	15.7	1020.008	
2.40	2 x 9	1.64	0.64	17.8	1020.009	
2.65	2 x 10	1.88	0.66	20.0	1020.010	



Suitable accessories



ladder

Other accessories can be found on page 26.

Wooden double ladder 1038

Length [m]	Number of rungs	Standing height [m]	Outer width at bottom [mm]	Stile height [mm]	Weight approx. [kg]	Ref. No.
0.95	2 x 3	0.30	0.47	65	5.7	1038.203
1.25	2 x 4	0.55	0.50	65	7.4	1038.204
1.55	2 x 5	0.80	0.53	65	8.9	1038.205
1.80	2 x 6	1.05	0.56	65	10.4	1038.206
2.10	2 x 7	1.30	0.59	65	12.5	1038.207
2.35	2 x 8	1.60	0.62	65	14.3	1038.208
2.65	2 x 9	1.85	0.65	65	15.7	1038.209
2.95	2 x 10	2.10	0.68	65	17.5	1038.210
3.50	2 x 12	2.65	0.74	70	25.5	1038.212
4.05	2 x 14	3.15	0.80	70	30.0	1038.214 🛎



Suitable accessories





Wood stile Suspended platform extension set EasyFix

Ladder shoe for wooden ladder

Wooden double ladder acc. to Ö-Norm Z1501 1053

The both side accessible wooden ladder for special professional use. It contains ergonomic needs of painters, wallpaperers while long standing on the rungs. The ladders according to the additional Austrian standard Z1501 are made accordingly to EN 131-1 and -2, excepting the two top rung spacings. They are 320 mm for comfortable standing on the ladder.



Combination double ladder 1028

The wood / aluminium ladder, tried, tested and praised by craftsmen. Ideal for electricians and craftsmen, as it is not electrically conductive. Information on the insulation resistance, in accordance with **VDE 0100** is available. Sturdy and torsion-stiff design. Extra-strong steel hinges, tear-proof polyester straps to prevent over-spreading.



Wooden double ladder 1053 acc. to Ö-Norm

Length [m]	Number of rungs	Standing height [m]	Outer width at bottom [mm]	Stile height [mm]	Weight approx. [kg]	Ref. No.
1.30	2 x 4	0.55	0.53	65	7.4	1053.204
1.60	2 x 5	0.80	0.56	65	9.2	1053.205
1.90	2 x 6	1.05	0.58	65	10.7	1053.206
2.15	2 x 7	1.30	0.61	65	12.8	1053.207
2.45	2 x 8	1.60	0.64	65	14.6	1053.208
2.70	2 x 9	1.85	0.67	65	16.0	1053.209
3.00	2 x 10	2.10	0.70	65	17.8	1053.210
3.56	2 x 12	2.65	0.76	70	25.8	1053.212

Standing height (max. 3rd rung from the top)

Suitable accessories



Ladder shoe for wooden ladder

Other accessories can be found on page 26.

Combination double ladder 1028

Length [m]	Number of rungs	Standing height [m]	Outer width at bottom [mm]	Weight approx. [kg]	Ref. No.	
1.55	2 x 5	0.80	0.50	7.6	1028.005	
1.80	2 x 6	1.05	0.53	9.0	1028.006	
2.10	2 x 7	1.30	0.56	11.0	1028.007	
2.35	2 x 8	1.60	0.59	12.6	1028.008	
2.95	2 x 10	2.10	0.65	16.0	1028.010	
3.50	2 x 12	2.65	0.71	19.2	1028.012	



Suitable accessories



Double step ladder TOPIC 1043

The classic double ladder design with comfortable and wide steps. Plastic-sheathed steel hinges, angle reinforcements and tear-proof polyester straps are quality features. The two top steps make up a platform. The *TOPIC* 1043 is also available with chain as protection against over-spreading.



Double step ladder TOPIC 1043.1

An extension of the classic step ladder with comfortable and wide steps, **plastic-sheathed steel hinges**, angle reinforcements and tear-proof polyester straps are quality features. Parallel stiles with a stile height of 76 mm, aclear width of 390 mm and cross-pieces on both sides guarantee a high level of safety plus convenient access.



Double step ladder TOPIC 1043

Length [m]	Number of steps	Standing height [m]	Outer width at bottom [mm]	Max. load [kg]	Weight approx. [kg]	Ref. No.
0.75	2 x 3	0.25	0.46	250	5.6	1043.003
1.00	2 x 4	0.50	0.48	250	6.8	1043.004
1.25	2 x 5	0.70	0.51	250	8.4	1043.005
1.50	2 x 6	0.95	0.53	200	9.8	1043.006
1.75	2 x 7	1.20	0.57	200	11.4	1043.007
2.00	2 x 8	1.40	0.60	200	13.4	1043.008
2.50	2 x 10	1.90	0.66	150	16.2	1043.010
3.00	2 x 12	2.40	0.72	150	19.8	1043.012

Double step ladder TOPIC 1043.1

Length [m]	Number of steps	Standing height [m]	Weight approx. [kg]	Ref. No.	
3.39	2 x 13	2.60	25.6	1043.113	Θ
3.64	2 x 14	2.85	26.6	1043.114	<u></u>
3.89	2 x 15	3.05	27.6	1043.115	
4.14	2 x 16	3.30	28.6	1043.116	



Standing height (max. 3rd rung from the top)

Suitable accessories





TOPIC Box Cross-

Suitable accessories

Cross-piece In castors

Other accessories can be found on page 26.

Double step ladder with access on one side TOPIC 1064

A safer stance at all times from the platform, extended stiles and knee bar shaped as a storage tray. The amply dimensioned platform folds up for transport. Tear-proof polyester straps to prevent over-spreading. The TOPIC 1064 is also available with chain as protection against over-spreading.



Double step ladder with access on one side TOPIC 1064

Length [m]	Number of steps	Standing height [m]	Outer width at bottom [mm]	Weight approx. [kg]	Ref. No.	
1.45	3	0.70	0.46	6.2	1064.003	~
1.70	4	0.95	0.48	7.0	1064.004	
1.95	5	1.20	0.51	8.0	1064.005	
2.20	6	1.40	0.53	9.2	1064.006	
2.45	7	1.65	0.57	10.4	1064.007	
2.70	8	1.90	0.60	11.6	1064.008	
2.95	9	2.10	0.64	13.2	1064.009	<u></u>
3.20	10	2.35	0.66	14.0	1064.010	
3.70	12	2.80	0.72	16.4	1064.012	<u>=</u>



Suitable accessories



Other accessories can be found on page 26.

Platform ladder TOPIC 1074



The TOPIC 1074 platform ladder for access from one side is a comfortable aid to doing lengthy work on the ladder. The large 480 x 420 mm platform using a non-slip grooved metal plate ensures a sure footing particularly for lengthy work on the ladder. Handrails fitted to the stile on both sides permit a safer grip when climbing up and down the ladder.



Platform ladder TOPIC 1074

Length [m]	Number of steps	Standing height [m]	Projection [m]	Weight approx. [kg]	Ref. No.
2.09	4	0.90	0.99	12.0	1074.004
2.34	5	1.20	1.14	13.2	1074.005
2.59	6	1.40	1.27	14.7	1074.006
2.84	7	1.60	1.41	15.6	1074.007
3.09	8	1.90	1.55	16.3	1074.008

Working height Standing height = form height

Suitable accessories





Cross-piece Ladder wall castors mounting

Insert hook

Stair Double Ladder With Steps TOPIC 1062

The professional solution not just for stairways. With the stairway double ladder, level equalization on uneven surfaces or stairways is no problem. The sturdy design and well thought-out details ensure optimum handling.

The stile extensions permanently attached to the ladder are quick to lock and easy to use thanks to rotary knobs fitted on the inside of the stile.



Stair Double Ladder TOPIC 1061



The stile extensions permanently attached to the ladder are quick to lock and easy to use thanks to rotary knobs fitted on the inside of the stile. The stile extensions have an adjustment range of 40 cm on one side and of 102 cm on the other side.

280 mm Rung spacing: Stile height: 64 mm



Stair Double Ladder With Steps TOPIC 1062

Length [m]	Number of rungs	Standing height [m]	Outer width of ladder stiles at bottom [m]	Weight approx. [kg]	Ref. No.	
1.25	2 x 5	0.70	0.58	14.3	1062.005	
1.50	2 x 6	0.95	0.61	15.3	1062.006	
1.75	2 x 7	1.20	0.65	17.3	1062.007	
2.00	2 x 8	1.40	0.68	19.3	1062.008	



Suitable accessories

Spike

Stair Double Ladder TOPIC 1061

Length [m]	Number of rungs	Standing height [m]	Projection [m]	Weight approx. [kg]	Ref. No.
1.55	2 x 5	0.80	1.20	13.3	1061.005
1.85	2 x 6	1.05	1.40	14.6	1061.006
2.10	2 x 7	1.30	1.60	15.7	1061.007
2.40	2 x 8	1.60	1.75	17.1	1061.008



Suitable accessories







Suspended platform

Suspended bag with hook Insert hook

Spike

Other accessories can be found on page 26.

TOPIC Box

Double rung ladder TOPIC 1039



The traditional double ladder with a wide range of safety features: Plastic-sheathed steel hinges, tear-proof polyester straps to prevent over-spreading, slip-resistant plastic shoes. Additional stiffeners at the end of the stile ensure that the values specified in DIN EN 131 are bettered. The *TOPIC* 1039 is also available with chain as protection against over-spreading.



Folding ladder TOPIC 1056

The Layher folding Ladder *TOPIC* 1056 is the perfect choice if you're using a double ladder that can be turned quickly and easily into a simple ladder. Strong and securely engaging steel joints ensure the required working position. For optimum stability, the Layher folding Ladder is fitted on one side with an 890 mm wide cross-piece. All-round grooved triangular rungs, quadruple-folded with the stile, ensure comfortable and sure footing at all times.



Stile neight:64 mmOuter width:393 mmRung spacing:280 mmCross-piece width:890 mm





Folding ladder TOPIC 1056

Max. length [m]	Min. length [m]	Number of rungs	Standing height double ladders [m]	Standing height single ladders [m]	Weight approx. [kg]	Ref. No.
2.45	1.34	4	0.55	1.30	7.8	1056.008 🛎
3.60	1.94	6	1.10	2.35	9.5	1056.012 🖴
4.70	2.49	8	1.60	3.40	11.6	1056.016 🚔





Suitable accessories



Suspended Insert hook platform

Other accessories can be found on page 26.

Double rung ladder TOPIC 1039

Length [m]	Number of rungs	Standing height [m]	Projection [m]	Stile height [mm]	Weight approx. [kg]	Ref. No.	
1.30	2 x 4	0.55	1.00	64	6.0	1039.004	
1.55	2 x 5	0.80	1.20	64	6.8	1039.005	
1.85	2 x 6	1.05	1.40	64	8.0	1039.006	
2.10	2 x 7	1.30	1.60	64	9.2	1039.007	
2.40	2 x 8	1.60	1.75	64	10.4	1039.008	
2.70	2 x 9	1.85	1.95	64	12.0	1039.009	
2.95	2 x 10	2.10	2.15	64	13.2	1039.010	
3.50	2 x 12	2.65	2.55	64	16.0	1039.012	
4.10	2 x 14	3.15	2.90	64	18.8	1039.014	
4.65	2 x 16	3.70	3.30	76	24.9	1039.016	Θ
5.20	2 x 18	4.20	3.70	76	30.1	1039.018	



Suitable accessories



Suspended platform

bag with hook

All-purpose ladder 3-part TOPIC 1040

Options to use as an extension ladder, single ladder, double ladder or extendable double ladder – all possible thanks to special joints. Safer free standing of ladder thanks to cross-piece. Aluminium stiffener with pushbutton locking. Also the assembly is done within only a few second. Manual length adjustment rung by rung using engaging hook. Secured against lifting out and sliding out of position. Easy handling in all variants. Securing flaps prevent a lateral movement of the ladder pieces while carrying.

The *TOPIC* 1040 can optionally be equipped with rollers.

Clear width: 454/377/300 mm Rung spacing: 280 mm

 $\begin{array}{l} \mbox{Cross-piece width: $890 mm} \\ \mbox{with } 6-8 \mbox{ rungs} \\ \mbox{Cross-piece width: $1130 mm} \\ \mbox{with 10 rungs} \\ \mbox{Cross-piece width: $1370 mm} \\ \mbox{with $12-14$ rungs} \end{array}$

All-purpose ladder 3-part TOPIC 1040

Min. length [m]	Max. length [m]	Number of rungs	Standing heigth double ladder [m]	Standing height extension ladder [m]	Standing height top section extended [m]	Stile height [mm]	Weight approx. [kg]	Ref. No.
1.94	3.65	3 x 6	1.05	2.85	1.60	76	15.6	1040.006
2.49	5.05	3 x 8	1.55	3.90	2.10	76	19.5	1040.008
3.04	6.45	3 x 10	2.05	5.20	3.15	76	23.2	1040.010
3.64	8.10	3 x 12	2.55	6.80	4.20	100	31.7	1040.012
4.19	9.80	3 x 14	3.05	8.35	5.25	100	35.5	1040.014



Car boot ladder TOPIC 1057

With the changes of the standard DIN EN 131 Part 4, multi-purpose ladders, like the Layher car boot ladder *TOPIC* 1057.112 with 4 x 3 rungs, which can be used as work platform, have to be equipped with suitable platform kits. For smallest transport and storage dimensions. Very versatile. As step ladder, single ladder, single ladder with wall clearance and as working platform (only with decking). Safety hinges automatically locking, to be released with light pressure.

1057.043

Stile height: **64 mm** Rung spacing: **280 mm** Outer width: **395 mm** Cross-piece width: **620 mm** Standing height as working platform: **890 mm**

Transport / packaging dimensions: 1057.043 0.95 x 0.89 x 0.28 m





1057.116

Stile height: 64 mm Rung spacing: 280 mm Outer width: 395 mm Cross-piece width: 890 mm Note: The 1057.116 cannot be used as a working platform.

Transport/packaging dimensions: 1057.116 1.20 x 0.89 x 0.28 m

Assembly variants

up to 150 kg

up to 150 kg up to 150 kg

Max. length [m]	Number of rungs	Standing height double ladder [m]	Standing height single ladder [m]	Standing height single ladder with wall clearance [m]	Weight approx. [kg]	Ref. No.		
3.45	4 x 3	1.00	2.30	1.50	18.0	1057.043	***	
4.60	4 x 4	1.55	3.35	2.55	16.5	1057.116		1

Telescopic ladder TOPIC 1058

Very versatile in use: as double ladder with variable height adjustment on one side. As a classic single ladder. And as two separate work trestles. Manual length adjustment rung by rung. Sturdy pin joints secure the ladder in the appropriate setting for use. The standing width of the *TOPIC* 1058 with base widening corresponds to the latest version of the DIN EN 131-4.



Telescopic ladder TOPIC 1058

Max. length [m]	Number of rungs	Standing height double ladder [m]	Standing height single ladder [m]	Weight approx. [kg]	Ref. No.
4.15 5.25	4 x 4	1.35	3.00	14.0 16.7	1058.016 1058.020
6.40	4 x 6	2.45	5.15	20.5	1058.024

Transport/packaging dimensions:

1058.016: 1.33 x 0.60 x 0.22 m **1058.020:** 1.55 x 0.67 x 0.22 m **1058.024:** 1.85 x 0.72 x 0.22 m

Stile extension

Usable as stile extension and as a cross-piece. Max. permissible stile extension: 450 mm



1.6 **1058.001** 🛎







Base widening - see page 28

Alu telescopic stage

The Alu telescopic stage offers a wide and variable range of possible applications. For transport, the telescopic stage can be simply pushed together, resulting in low transport dimensions. Since the Alu telescopic stage is extendable, it can be pulled out or pushed together to provide any required length. The automatic locking mechanism ensures that the inner extending element cannot slide out by mistake. The supporting structure is made of specially developed and torsion-stiff extruded aluminium sections. All section ends are provided with plastic caps. They act as sliding elements and provide protection from injury. Thanks to these plastic sliding elements, the effort required to slide the telescopic stage in and out is very low.



Alu telescopic stage

Max. length [m]	Min.length [m]	Weight approx [kg]	Ref. No.
2.9	1.64	13.0	1351.290
3.5	1.92	16.0	1351.350
4	2.27	18.0	1351.400
4.4	2.49	20.0	1351.440





Working plattform *TOPIC* 1065

NEW

The foldable work platform *TOPIC* 1065 is the convenient tool for both indoor and outdoor work. The high-quality plywood plate has a non-slip surface and a practical recessed grip, making the working platform easy to transport with its low weight.





Increased slip resistance due to 80 mm wide steps made of aluminum with slip resistance **R12** in the direction of steps.



Working plattform TOPIC 1065

Length [m]	Number of steps Standing height [m] Outer width at bottom [m] Maximum load [kg		Maximum load [kg]	Weight approx. [kg]	Ref. No.	
1.59	2 x 2	0.65	0.57	300	15.7	1065.065









THE BENEFITS FOR YOU:

- Lightweight and stable construction made of aluminum stiles in the familiar Layher design.
- Quick and easy assembly thanks to hinges with quick-release fasteners that automatically lock into place.
- 80 mm wide grooved steps with a slip resistance class R12, for a comfortable and safe ascent and descent.
- Safe working on a standing surface of 1500 x 500 mm.
- > Anti-slip platform covering (R12 rating group).
- > The working platform is approved for 2 persons and max. 300 kg.
- Non-slip 2-component shoes.
- Quickly foldable for transport and storage.

Alu heavy-duty step TOPIC 1043.3

The classic step design with comfortable and wide steps. Plastic-sheathed steel hinges, angle reinforcements and tear-proof polyester straps are quality features. The platform at the top can be footed. The heavy-duty step conforms to European Standard DIN EN 14183 -B.



Alu heavy-duty step TOPIC 1043.3

Length [m]	Number of rungs	Standing height [m]	Outer width at bottom [mm]	Weight approx. [kg]	Ref. No.
0.90	2 x 3	0.70	0.64	8.4	1043.303 🖷
1.15	2 x 4	0.95	0.67	9.6	1043.304 🚆





Work trestle TOPIC 1047

Aluminium work trestle. Safe access on one side thanks to wide steps. Ideal as a lightweight, simple and small scaffolding for construction work. Folds together for transport. One side with round tubes for suspension of rolling tower deck sections (0.68 m wide) or 2 Alu telescopic stages as working platform.



Work trestle TOPIC 1047

Length [m]	Number of rungs	Standing height [m]	Stile Maximum Weigl height load [kg] appro [mm] [kg]		Weight approx. [kg]	Ref. No.	
1.15	4	0.98	76	150	9.6	1047.704	2



More information about the bridging deck, see page 118/119.



Machine step 1075

The machine step made of aluminium is a safer and more convenient aid to assembly and maintenance work on machinery, and for access to high shelves in warehouse logistics. The sturdy welded tube design with a large platform to stand on (540 x 310 mm) ensures a safer footing in particular during work over lengthy periods. Wide steps (580 x 225 mm) ensure safer ascents and descents. The platform and the steps are made from a grooved aluminium plate to makethem non-slip. The machine step 1075 conforms to European Standard DIN EN 14183-C.



Steps with access on one side for fitting and servicing work. Ideal for plasterers, drywall installers and painters. Amply sized standing surface and wide steps for safer and comfortable working. For ease of transport, a practical grip hole has been cut out from the standing surface. Protection against over-spreading made of galvanized steel. Stiles made of narrow-ringed yellow pine. Grooved steps made of sturdy beechwood.



Step spacing: Step length: Platform dimension: Outer width: 250 mm 115 mm 215 x 565 mm 565 mm



Machine step 1075

Length [m]	Number of rungs	Standing Projection N height [m] [m] a		Weight approx. [kg]	Ref. No.				
0.80	2	0.40	0.53	6.8	1075.002	<u></u>			
0.75	3	0.60	0.73	10.0	1075.003				
0.95	4	0.80	0.94	13.5	1075.004	<u> </u>			
1.15	5	0.99	1.14	17.2	1075.005				

Castors for machine step

Thanks to the optional castors, the machine step 1075 can be moved horizontally from place to place both quickly and ergonomically. The castors can be fitted in a quick operation by the user to all length versions.





Folding wooden steps 1055

Length [m]	Number of rungs	Standing height [m]	Projection Weight [m] approx		Ref. No.
0.75	3	0.65	0.70	6.8	1055.003
1.00	4	0.85	0.85	8.5	1055.004



Wallpaperer's trestle 1045

The sturdy structure for the professional user. Sturdy, galvanized steel hinges. Stiles made of pine wood and rungs made of solid beechwood.

The wallpaperer's trestle may not be used as a ladder and stepping on the rungs is not allowed.

Support strip: 650 mm



Truck ladder 1060

Ultra-light simple ladder made of aluminium. Ideal for accessing the truck loading surface. Optimum stability and functionality from soft rubber shoes around the stile ends. This means that the ladder is suitable not only for access to the loading surface, but also for leaning up against the cab to clean its windscreen without damaging the vehicle paintwork.

Clear width:	300 mm
Outer width:	350 mm
Rung spacing:	280 mm



Wallpaperer's trestle 1045

Length [m]	Projection [m]	Support height [m]	Weight approx. [kg]	Ref. No.
0.85	0.75	0.80	4.4	1045.202
1.00	0.80	0.95	5.2	1045.203

Truck ladder 1060

Length [m]	Number of rungs	Standing height [m]	Stile height [mm]	Maximum load [kg]	Weight approx. [kg]	Ref. No.	
2.10	7	1.05	50	150	3.3	1060.007	<u> </u>

A matching holder is available for optimum attachment of truck ladder 1060 to the vehicle. Ref. No. 1060.001



Suitable accessories



Ladder shoe for wooden ladder

Accessories

































Pos.	Description		Dimen- sions [m]	Weight approx. [kg]	Ref. No.		VE	1020	1028	1029	1035	1037	1038	1040	1042	1043	1043.1	1043.3 1045	1052	1054	1056 1057	1061	1062	1064 1074
1	Suspended platform for use on all TOPIC rung or double s ladders; easy fitting over the rungs o	step or steps		0.8	1016.003			Þ	•		Þ	Þ	Þ	•						Þ	•	•		
2	Gutter holder Secure attachment for all ladders			0.5	1016.006							×		•	•					Þ				
3	Suspended bag with hook as tool box for all TOPIC rung double ladders	Yellow orange RAL 2000		0.5	1016.014				•													•		
4	TOPIC Box for use on all TOPIC rung or double step ladders; easy fitting over the rungs or steps	Silver grey RAL 7001		0.8	1016.021				•							•	•					•		
5	Wood stile extension set EasyFix 1.25 m (1 pcs.) for wooden double lade 1038 (up to 10 rungs) and the wallpap 1045, fixation material with wing bolts	ders 1020 and erer's trestle i included	1.25 1.65	1.9 2.2	1016.022 1016.023	11		•					•						•					
6	Top rollers with rubber tyres to protect the wall surface when extending / retracting ladder, usable on the TOPIC ladders 1035, 1037 and 1040	Anthracite grey RAL 7016		1.5	1016.027	***					• •	×		•										
7	Suspension hook DIY-assembly, usable on tubes up to (1 pcs.)	d=50 mm,		0.1	1016.050						• •	Þ		•	•					•	• •			
8	Ladder shoe for wooden ladder DIY-assembly, fits onto ladders 1053 and 1038 up to 10 rungs and onto wallpaperer's trestles 1045	Yellow orange RAL 2000		0.2	1016.052 1016.053	<u></u>	2 III 2 III	Þ					•					•	•					
9	Cross-piece castors for easy movement of large ladders; easy fitting by large dimensioned wi	ng bolts		0.7	1016.072	<u></u>	2 🎟				• •	Þ		•	Þ		•			Þ	• •			•
10	Wall bracket for easy supspension of ladders with hooks, Axial dim. = 640 mm, Wall spa	n suspension acing = 123 mm		2.5	1016.090	***					• •	•		•	•					•	• •			
11	Ladder wall mounting for an ideal storage of ladders on the	e wall		1.8	1016.092	<u></u>				×		Þ			Þ	Þ				Þ				• •
12	Insert hook self-securing, usable on all Layher TO	OPIC ladders		0.1	1016.100				•			•		• •	•	•	Þ	•		Þ	×	•	•	• •
13	Spike For better stability on grass or soil; e without drilling or riveting. Usable or ladders with Combigrip ladder foot.	asy fitting n all TOPIC		0.1	1016.101	***	2 🎟					Þ			•	•		•		Þ		•	۱.	Þ
14	Step attachment can be used with stile height 100 mm of ladders 1037, 1035, 1040	Yellow orange RAL 2000		3.3 3.0	1016.103 1016.763	<u>1</u>					•	•		•										
	TOPIC Stile Extension		64 mm	1.5	1016.108	***					•				►					•				
15	(1 pcs.) for stile extension on stairwa	ays or podia;	76 mm	1.7	1016.109	***					•					►				•				•
15	adjustment area up to 400 mm; easy	/ fitting	84 mm	1.9	1016.110	***																		
	by 2 large unitensioned wing polts		100 mm	2.1	1016.111	***					•									•				
16	Castors for machine step			0.5	1016.751	***																		

Spare parts



The Layher Combigrip ladder foot is made of a 2-component plastic: a hard inner section (orange) for secure mounting inside the stile, and a soft outer covering (black), non-slip on every floor surface. That ensures:

Play-free mounting in ladder stile.

5

- High slipping resistance, for maximum
- stability of ladders.
- Long service life no cutting or reshaping of the foot.

The Layher Combigrip ladder foot ensures easy retrofitting of a ladder cross-piece.

The cross-piece is simply inserted into the cutout provided for it in the foot, and then firmly screwed to the stile ends using hexagonal-head screws.

TIP: With the Layher Combigrip ladder foot, you automatically comply with the new requirements of DIN EN 131-1, which will specify a cross-piece for simple ladders of 3 metres and more length.



lmage can differ from original.



Pictogram description

Labels acc. to new DIN EN 131-3 - label see pos. 7



Spare parts

Pos.	Description		Dimensions [m]	Weight approx. [kg]	PU	Ref. No.		
1	Combigrip ladder foot of 2-component plastic for secure mounting inside the non-slip on every floor surface	e stile and	64-mm-stile 76-mm-stile 84-mm-stile 100-mm-stile	0.2 0.2 0.2 0.2	2 III 2 III 2 III 2 III	6492.810 = 6492.811 = 6492.812 = 6492.813 =		
2	TOPIC ladder foot for ladder heads and inner ladders of multi-purpose la	ıdders	64-mm-stile 76-mm-stile 84-mm-stile 100-mm-stile	0.3 0.3 0.3 0.4	2 III 2 III 2 III 2 III	6492.011 Image: Control of the second se		
3	Ladder cross-piece for even more safety, easy fitting with the Combigrip ladder foot	1032.008 - 1032.014 1054.006 - 1054.024 1042.006 - 1042.018 1043.113 - 1043.116	1.13	3.0		1016.081 🖴		
		1035.006–1035.010 1035.012–1035.018 1037.014–1037.024	0.89 1.36	3.0 3.0		1016.082 🖷 1016.084 🖷		
		1040.006-1040.008	0.89	3.0		6492.114 🛎		
		1040.010	1.13	3.0		6492.115 🛎		
		1040.012-1040.014	1.36	3.0		6492.116 😐		
	acc. to UVV "Ladders and steps" DGUV Information 20 be checked to their proper condition. By the ladder co controlling and protocolling.	8-016 § 29, ladders and steps must ntrol sheet you have a check list for	downloads.layher.com					
5	Foot for cross-piece for all ladder cross-pieces			1.1	2 🎟	6492.015 🖷		
6	Universal- and check plaquette German operating safety regulations require that ladd	ers are inspected.		0.2	10 🎟	6493.002 🖷		
7	Pictogram labels as replacement Manual for label replacement	For platform ladder TOPIC 1074		0.01	10 🎟	6493.007 🖴		
	is added to the label!	For multifunction ladders 1040, 1056, 1057, 1058		0.01	10 🎟	6493.008 🖴		
		For double ladders 1039, 1043, 1061, 1064, 1043.1		0.01	10 🎟	6493.010 🖷		
		For single ladders 1035, 1037, 1042, 1054, 1060, 1032		0.01	10 🎟	6493.011 🖷		
		Für Holzstehleitern 1028, 1038, 1053, 1020		0.01	10 🎟	6493.012 🕒		
		For wooden single ladders 1029, 1052		0.01	10 🎟	6493.013 🕒		
8	Base widening, kit	For telescopic ladder 1058		0.9		1016.175 🖷		

Wooden roofer's ladder 1046

Special ladder in craftsman's quality, curved rungs with recesses for roof hooks. Double-screwed to stiles. In conformity with the regulations of German professional builders' associations. The roofer's ladder 1046 permit a variable operating range up to a roof pitch of 75° and hung in roof hooks. The roofer's ladder 1046 ist equipped with tear-proof polyester straps as breaking cut-out.



Outer width: Rung spacing: 365 mm 280 mm

Wooden roofer's ladder 1046

Length [m]	Number of rungs	Weight approx. [kg]	Ref. No.
2.35	8	4.8	1046.108
2.85	10	5.5	1046.110
3.50	12	6.3	1046.112
4.15	14	7.0	1046.114
4.50	16	7.8	1046.116
4.63	18	9.2	1046.118



Layher roof ladders are laid on house roofs for temporary maintenance and inspection work, for example on chimneys or satellite dishes. High-grade roofs are protected from scratching during assembly and use by the unique and EPDM protective section of Layher roof ladders. Layher roof ladders permit a variable operating range up to a roof pitch of 73°.



Clear width: Rung spacing: Outer width: Stile height: 300 mm 280 mm 340 mm 95 mm

The Layher roof ladders are available in 4 colour variants:

- Natural aluminium
- RAL 7016 (Anthracite grey)
- RAL 8004 (Copper brown)
- RAL 8011 (Nut brown)

Roof ladder as per DIN 4567-4 1051

Number of rungs	Weight approx. [kg]	Colour	Ref. No.
7	3.8	Aluminium nat.	1051.007 🖷
10	5.5	Aluminium nat.	1051.010 🛎
15	8.3	Aluminium nat.	1051.015 🛛 🛎
7	3.8	RAL 8004	1051.107 🖷
10	5.5	RAL 8004	1051.110 🖷
15	8.3	RAL 8004	1051.115 🛛 🖴
7	3.8	RAL 8011	1051.207 🖷
10	5.5	RAL 8011	1051.210 🖷
15	8.3	RAL 8011	1051.215 🛛 🚔
7	3.8	RAL 7016	1051.307 🖷
10	5.5	RAL 7016	1051.310 🖷
15	8.3	RAL 7016	1051.315 🛛 🚔



Connect the roof ladders using the connecting straps, Ref. No. 1049.x03. The bolts, washers and locking nuts are included. Use four bolts per strap. At least two safety hooks must be used. Up to three ladders can be joined without an additional roof hook and fastening bracket being needed.















Exemplary application of the safety hook model Z (Pos. 1)



Pos.	Description		Dimensions [m]	Weight approx. [kg]	PU	Ref. No.	
		steel galvanized		0.9		1049.011	20
	Safety hook, model Z according to DIN EN 517-Type B For use on tiled roofs, incl. nails	Copper brown RAL 8004		0.9		1049.111	<u></u>
1		Nut brown RAL 8011	0.46 x 0.23 x 0.03	0.9		1049.211	201
		Anthracite grey RAL 7016		0.9		1049.311	***
		steel galvanized		0.8		1049.012	***
	Safety hook, model B according to DIN EN 517-Type A For use on slate roofs, incl. nails	Copper brown RAL 8004	0.33 x 0.18 x 0.03	0.8		1049.112	
2		Nut brown RAL 8011		0.8		1049.212	—
		Anthracite grey RAL 7016		0.8		1049.312	
		Alu natural		0.5	2 🆽	1049.003	<u> </u>
	Connecting stron	Copper brown RAL 8004		0.5	2 🔳	1049.103	***
3	Including bolts, washers and nuts of stainless steel	Nut brown RAL 8011	0.20 x 0.02 x 0.005	0.5	2 🏼	1049.203	2
		Anthracite grey RAL 7016		0.5	2 🏼	1049.303	***
4	Fastening bracket according to DIN 18160-5, galvanized			0.1		1049.000	—

Instructions for assembly and use can be found at mediathek.layher-steigtechnik.com

The roof ladder TOPIC 1051 plus the above accessory parts (apart from the fastening bracket) are available in 4 colour variants:

RAL 8004

Copper brown PU = packaging unit 🚔 = available ex works 🕒 = delivery time on request 🖽 = only available in this packaging unit

RAL 8011

Nut brown

RAL 7016

LAYHER ACCESSES

Different inclinations





Different step types (see accessories)



Standard steps of aluminium with grooved surface Slip resistance: R12 in step direction



Alternative steps made of steel grating* Slip resistance: R11



Alternative steps made of aluminium grating* Slip resistance: R11



Alternative steps made of steel perforated plate* Slip resistance: R11



Alternative steps made of aluminium perforated plate* Slip resistance: R11

* Delivery time on request



Standard accesses with inclination of 45° and 60° and step widths of 0.60 m and 0.80 m as listed in the catalogue are quickly available (15 workdays after receipt of order). Further sizes, designs and inclina-

tions are possible on request.





TECHNICAL DATA:

- Step load 150 kg
- Total load 300 kg

THE BENEFITS FOR YOU:

- 200 mm deep steps with grooved aluminium surface with slip resistance R12 in the step direction (included in the price in the standard version).
- Handrails and guardrails of 40 mm round tube with cast aluminium connectors, orange, powder-coated.
- High flexibility for expansions, additions and adaptations thanks to the "new" modular principle.
- > Separate ordering possible for handrails, platform guardrails, end

guardrails and accessories.

- Quick and easy assembly and dismantling of stair guardrails and other guard rails or of additional stair guardrail or other guardrail as preassembled units at no extra charge.
- To aid decision-making, quick technical support in the form of sketches or drawings can be supplied.



			A CONTRACTOR	A REAL PROPERTY OF		ALL
Stair type		Alu start-stairway 110	Alu stairway 111	Alu stairway with platform 112	Alu maintenance platform 113	Alu bridging stairway 114
Description		Ideal for machinery access with a comfortable stance.	Fixed access to higher levels.	Fixed access to higher levels with large platform, e.g. for door openings.	Mobile access to higher-level shelves or for maintenance work at greater heights.	Machinery crossover with ample width.
Step width		0.60 m or 0.80 m	0.60 m or 0.80 m	0.60 m or 0.80 m	0.60 m or 0.80 m	0.60 m or 0.80 m
Width	0.60 m	0.68 m, 0.87 m*	0.73 m**	0.73 m**	soo tabla 112	0.79 m**
vviutii	0.80 m	0.88 m, 1.07 m*	0.93 m**	0.93 m**	See lable 113	0.99 m**
Step length		200 mm	200 mm	200 mm	200 mm	200 mm
Inclination		45°	45° or 60°	45° or 60°	45° or 60°	45°or 60°
Platform len	gth	0.40 m	0.20 m	0.60 m	0.60 m	0.80 m
Dieser	45°	200 mm	200 mm	200 mm	200 mm	200 mm
niser	60°		240 mm	240 mm	240 mm	240 mm
Max. step lo	ad	150 kg	150 kg	150 kg	150 kg	150 kg
Max. total lo	ad	300 kg	300 kg	300 kg	300 kg	300 kg

All dimensions are guideline values. Subject to technical modification. Delivery exclusively in accordance with our currently valid General Terms of Sale. Delivery incl. assembly drawing. Cannot be returned.

* Dimensions including crosspiece ** Width with stair guardrail on one side

Aluminium access steps, fixed or rolling 110

For loading of containers, servicing machinery etc. Special stile made of strong aluminium section. Step profile grooved for sure footing.





Platform height:

Max. 0.99 m (dimension from floor to top edge of platform)

Platform length:

0.40 m

Width:

Step width + 0.08 m

Crosspiece:

For sure footing:

With step width 0.60 m = 0.87 m $\,$

With step width 0.80 m = 1.07 m

Crosspiece wheels (optional):

For moving the access steps like a wheelbarrow

Inclination	Step width [mm]	Platform height [m]	0.40	0.60	0.80	1.00
45°		Number of steps	2	3	4	5
		Base-to-base distance [m]	0.75	1.0	1.25	1.5
	600	Weight [kg]	10.3	13.4	16.6	19.9
		Ref. No.	1106.702	1106.703	1106.704	1106.705
	800	Weight [kg]	11.9	15.4	18.9	22.6
		Ref. No.	1108.702	1108.703	1108.704	1108.705

Delivery exclusively in accordance with our currently valid General Terms of Sale. Delivery incl. assembly drawing. Cannot be returned. Component weights are subject to fluctuations due to tolerances and may therefore diverge from what is specified.

Aluminium stair 111

A safe and permanently fitted access. Wherever material, equipment and machinery have to be stored or operated at a height. Rapid working is assured by convenient and effortless movement even with loads.

Platform height:

Max. 3.84 m (dimension from floor to top edge of top step) Width:

Step width + 0.13 m with stair guardrail on one side Step width + 0.17 m with stair guardrail on both sides

Stair guardrail/guardrail:

The standard scope of delivery includes a stair guardrail (which can be optionally fitted either left or right). DIN EN ISO 14122-3 must be complied with. Accordingly, for a stairway with a 45° inclination a stair guardrail is specified for **at least** one side. For a 45° angle and a wall clearance > 200 mm, or for 60°, a handrail must be provided on both sides.

Base-to-base distance:

Dimension from front edge of stair to wall

Hole for fastening strap:

 $9\,\text{mm}$



The safe transfer of the loads into the structure or the building ground must be approved by the customer.

Inclination	Step width [mm]	Platform height [m]	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.20
45°		Number of steps	3	4	5	6	7	8	9	10	11
		Base-to-base distance [m]	0.67	0.87	1.07	1.27	1.47	1.67	1.87	2.07	2.27
	600	Weight [kg]	14.5	17.0	19.7	22.6	25.5	28.7	33.3	34.6	39.3
		Ref. No.	1116.403	1116.404	1116.405	1116.406	1116.407	1116.408	1116.409	1116.410	1116.411
	800	Weight [kg]	15.7	18.7	21.8	25.1	28.4	32.0	37.1	40.4	44.0
		Ref. No.	1118.403	1118.404	1118.405	1118.406	1118.407	1118.408	1118.409	1118.410	1118.411
Extra charge for 2nd stair guardrail		Weight [kg]	6.0	6.1	6.3	6.7	7.1	7.8	10.0	10.4	11.0
		Ref. No.	1110.403	1110.404	1110.405	1110.406	1110.407	1110.408	1110.409	1110.410	1110.411
Inclination	Step width [mm]	Platform height [m]	0.72	0.96	1.20	1.44	1.68	1.92	2.16	2.40	2.64
Inclination	Step width [mm]	Platform height [m] Number of steps	0.72 3	0.96 4	1.20 5	1.44 6	1.68 7	1.92 8	2.16 9	2.40 10	2.64 11
Inclination	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m]	0.72 3 0.522	0.96 4 0.661	1.20 5 0.799	1.44 6 0.938	1.68 7 1.076	1.92 8 1.215	2.16 9 1.354	2.40 10 1.493	2.64 11 1.632
Inclination	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg]	0.72 3 0.522 14.3	0.96 4 0.661 16.9	1.20 5 0.799 19.6	1.44 6 0.938 22.2	1.68 7 1.076 25.0	1.92 8 1.215 28.1	2.16 9 1.354 32.4	2.40 10 1.493 35.4	2.64 11 1.632 38.3
Inclination 60°	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No.	0.72 3 0.522 14.3 1116.603	0.96 4 0.661 16.9 1116.604	1.20 5 0.799 19.6 1116.605	1.44 6 0.938 22.2 1116.606	1.68 7 1.076 25.0 1116.607	1.92 8 1.215 28.1 1116.608 1116.608	2.16 9 1.354 32.4 1116.609	2.40 10 1.493 35.4 1116.610	2.64 11 1.632 38.3 1116.611
Inclination 60°	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg]	0.72 3 0.522 14.3 1116.603 15.5	0.96 4 0.661 16.9 1116.604 18.6	1.20 5 0.799 19.6 1116.605 21.7	1.44 6 0.938 22.2 1116.606 24.8	1.68 7 1.076 25.0 1116.607 28.0	1.92 8 1.215 28.1 1116.608 31.4	2.16 9 1.354 32.4 1116.609 36.2	2.40 10 1.493 35.4 1116.610 39.6	2.64 11 1.632 38.3 1116.611 43.0
Inclination 60°	Step width [mm] 600 800	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg] Ref. No.	0.72 3 0.522 14.3 1116.603 15.5 1118.603	0.96 4 0.661 16.9 1116.604 18.6 1118.604	1.20 5 0.799 19.6 1116.605 21.7 1118.605	1.44 6 0.938 22.2 1116.606 24.8 1118.606	1.68 7 1.076 25.0 1116.607 28.0 1118.607	1.92 8 1.215 28.1 1116.608 31.4 1118.608 31.4	2.16 9 1.354 32.4 1116.609 36.2 1118.609	2.40 10 1.493 35.4 1116.610 39.6 1118.610	2.64 11 1.632 38.3 1116.611 43.0 1118.611
Inclination 60° Extra charge	Step width [mm] 600 800 800 600	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg] Weight [kg]	0.72 3 0.522 14.3 1116.603 15.5 1118.603 5.8	0.96 4 0.661 16.9 1116.604 18.6 1118.604 6.0	1.20 5 0.799 19.6 1116.605 21.7 1118.605 6.2	1.44 6 0.938 22.2 1116.606 24.8 1118.606 6.4	1.68 7 1.076 25.0 1116.607 28.0 1118.607 6.7	1.92 8 1.215 28.1 1116.608 31.4 1118.608 7.3	2.16 9 1.354 32.4 1116.609 36.2 1118.609 9.2	2.40 10 1.493 35.4 1116.610 39.6 1118.610 9.7	2.64 11 1.632 38.3 1116.611 43.0 1118.611 10.2

Intermediate heights are possible on request when the appropriate platform is specified. Quotation and Technical Data Sheet will follow within 72 hours of receipt of the enquiry. All dimensions are guideline values. Subject to technical modification. Delivery exclusively in accordance with our currently valid General Terms of Sale. Delivery incl. assembly drawing. Cannot be returned. Component weights are subject to fluctuations due to tolerances and may therefore diverge from what is sp-ecified.


Detailed view of fastening strap



Inclination	Step width [mm]	Platform height [m]	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80
		Number of steps	12	13	14	15	16	17	18	19
		Base-to-base distance [m]	2.47	2.67	2.87	3.07	3.27	3.47	3.67	3.87
150	600	Weight [kg]	42.4	47.0	64.8	69.0	74.6	78.8	82.9	87.0
40	000	Ref. No.	1116.412	1116.41	3 1116.414	1116.415	1116.416	1116.417	1116.418	1116.419
	000	Weight [kg]	47.5	52.5	70.7	75.3	81.4	86.0	90.5	95.0
	000	Ref. No.	1118.412	1118.41	3 1118.414	1118.415	1118.416	1118.417	1118.418	1118.419
Extra charge for 2nd stair guardrail		Weight [kg]	11.6	13.7	14.2	14.8	16.9	17.5	18.0	18.5
		Ref. No.	1110.412	1110.41	3 1110.414	1110.415	1110.416	1110.417	1110.418	1110.419
Inclination	Step width [mm]	Platform height [m]	2.88		3.12	3.	36	3.60		3.84
Inclination	Step width [mm]	Platform height [m] Number of steps	2.88 12		3.12 13	3 .	36 4	3.60 15		3.84 16
Inclination	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m]	2.88 12 1.77		3.12 13 1.9	3 . 1 2.	36 4 05	3.60 15 2.19		3.84 16 2.32
Inclination	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg]	2.88 12 1.77 41.4		3.12 13 1.9 45.8	3. 1 2. 63	36 4 05 3.5	3.60 15 2.19 67.5		3.84 16 2.32 71.5
Inclination 60°	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No.	2.88 12 1.77 41.4 1116.61	2	3.12 13 1.9 45.8 1116.613	3. 1 2. 63 1116	36 4 05 3.5 5.614	3.60 15 2.19 67.5 1116.615	1	3.84 16 2.32 71.5 116.616
Inclination 60°	Step width [mm] 600	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg]	2.88 12 1.77 41.4 1116.61 46.5	2	3.12 13 1.9 45.8 1116.613 51.3	3. 1 2. 63 1116 65	36 4 05 8.5 6.614 0.4	3.60 15 2.19 67.5 1116.615 73.8	1	3.84 16 2.32 71.5 116.616 78.3
Inclination 60°	Step width [mm] 600 800	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg] Ref. No.	2.88 12 1.77 41.4 1116.61 46.5 1118.61	2	3.12 13 1.9 45.8 1116.613 51.3 1118.613	3. 1 2. 63 1116 65 1118	36 4 05 5 6.614 6 9.4 6	3.60 15 2.19 67.5 1116.615 73.8 1118.615	1	3.84 16 2.32 71.5 116.616 78.3 118.616
Inclination 60° Extra charge	Step width [mm] 600 800 for 600	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg] Ref. No. Weight [kg]	2.88 12 1.77 41.4 1116.61 46.5 1118.61 10.8	2	3.12 13 1.9 45.8 1116.613 51.3 1118.613 12.7	3. 1 2. 63 1111 65 11118 1118	36 4 05 5 3.5 5 5.614 6 3.614 6 3.2 5	3.60 15 2.19 67.5 1116.615 73.8 1118.615 13.7	1	3.84 16 2.32 71.5 116.616 78.3 118.616 14.2

Alu stairway with platform 112

Can be fixed to buildings as an emergency exit, at machines, as a raised workplace, etc.

Platform height:

Max. 3.84 m (dimension from floor to top edge of platform)

Platform length:

0.60 m

Width:

Step width + 0.13 m with stair guardrail on one side Step width + 0.17 m with stair guardrail on both sides

Stair guardrail / platform guardrail:

The standard scope of delivery includes a stair guardrail and a platform guardrail (both of which can be optionally fitted either left or right). DIN EN ISO 14122-3 must be complied with. Accordingly, for a stairway with a 45° inclination a stair guardrail is specified for **at least** one side. For a 45° angle and a wall clearance > 200 mm, or for 60°, a handrail must be provided on both sides.

Base-to-base distance:

Dimension from front edge of stair to wall

Hole for fastening strap:

9 mm

The safe transfer of the loads into the structure or the building ground must be approved by the customer.

Inclination	Step width [mm]	Platform height [m]	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.20
		Number of steps	3	4	5	6	7	8	9	10	11
459 000		Base-to-base distance [m]	1.07	1.27	1.47	1.67	1.87	2.07	2.27	2.47	2.67
	Weight [kg]	25.0	27.7	30.4	33.0	36.0	39.1	43.7	46.7	49.9	
40	000	Ref. No.	1126.403	1126.404	1126.405	1126.406	1126.407	1126.408	1126.409	1126.410	1126.411
	900	Weight [kg]	27.1	30.2	33.3	36.4	39.8	43.3	48.3	51.7	55.4
	000	Ref. No.	1128.403	1128.404	1128.405	1128.406	1128.407	1128.408	1128.409	1128.410	1128.411
Extra charge for 2nd stair guardrail		Weight [kg]	5.7	5.9	6.1	6.3	6.8	7.4	9.5	10.0	10.8
		Ref. No.	1160.403	1160.404	1160 405	1160.406	1160.407	1160.408	1160.409	1160.410	1160.411
Ŭ					11001100						
Inclination	Step width [mm]	Platform height [m]	0.72	0.96	1.20	1.44	1.68	1.92	2.16	2.40	2.64
Inclination	Step width [mm]	Platform height [m] Number of steps	0.72 3	0.96 4	1.20 5	1.44 6	1.68 7	1.92 8	2.16 9	2.40 10	2.64 11
Inclination	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m]	0.72 3 0.93	0.96 4 1.07	1.20 5 1.21	1.44 6 1.35	1.68 7 1.48	1.92 8 1.62	2.16 9 1.76	2.40 10 1.90	2.64 11 2.04
Inclination	Step width [mm]	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg]	0.72 3 0.93 24.8	0.96 4 1.07 27.3	1.20 5 1.21 30.1	1.44 6 1.35 32.6	1.68 7 1.48 35.4	1.92 8 1.62 38.5	2.16 9 1.76 42.8	2.40 10 1.90 45.8	2.64 11 2.04 48.7
Inclination 60°	Step width [mm] 600	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No.	0.72 3 0.93 24.8 1126.603	0.96 4 1.07 27.3 1126.604	1.20 5 1.21 30.1 1126.605	1.44 6 1.35 32.6 1126.606	1.68 7 1.48 35.4 1126.607	1.92 8 1.62 38.5 1126.608	2.16 9 1.76 42.8 1126.609	2.40 10 1.90 45.8 1126.610	2.64 11 2.04 48.7 1126.611
Inclination 60°	Step width [mm] 600	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg]	0.72 3 0.93 24.8 1126.603 26.9	0.96 4 1.07 27.3 1126.604 29.9	1.20 5 1.21 30.1 1126.605 33.0	1.44 6 1.35 32.6 1126.606 36.0	1.68 7 1.48 35.4 1126.607 39.2	1.92 8 1.62 38.5 1126.608 42.7	2.16 9 1.76 42.8 1126.609 47.5	2.40 10 1.90 45.8 1126.610 50.9	2.64 11 2.04 48.7 1126.611 54.2
Inclination 60°	Step width [mm] 600 800	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg] Ref. No.	0.72 3 0.93 24.8 1126.603 26.9 1128.603	0.96 4 1.07 27.3 1126.604 29.9 1128.604	1.20 5 1.21 30.1 1126.605 33.0 1128.605	1.44 6 1.35 32.6 1126.606 36.0 1128.606 1128.606	1.68 7 1.48 35.4 1126.607 39.2 1128.607	1.92 8 1.62 38.5 1126.608 42.7 1128.608	2.16 9 1.76 42.8 1126.609 47.5 1128.609	2.40 10 1.90 45.8 1126.610 50.9 1128.610	2.64 11 2.04 48.7 1126.611 54.2 1128.611
Inclination 60° Extra charge	Step width [mm] 600 800 for 600	Platform height [m] Number of steps Base-to-base distance [m] Weight [kg] Ref. No. Weight [kg] Ref. No. Weight [kg]	0.72 3 0.93 24.8 1126.603 26.9 1128.603 5.4	0.96 4 1.07 27.3 1126.604 29.9 1128.604 5.5	1.20 5 1.21 30.1 1126.605 33.0 1128.605 5.8	1.44 6 1.35 32.6 1126.606 36.0 1128.606 5.9	1.68 7 1.48 35.4 1126.607 39.2 1128.607 6.2	1.92 8 1.62 38.5 1126.608 42.7 1128.608 6.8	2.16 9 1.76 42.8 1126.609 47.5 1128.609 8.7	2.40 10 1.90 45.8 1126.610 50.9 1128.610 9.2	2.64 11 2.04 48.7 1126.611 54.2 1128.611 9.7

Intermediate heights are possible on request when the appropriate platform is specified. Quotation and Technical Data Sheet will follow within 72 hours of receipt of the enquiry. All dimensions are guideline values. Subject to technical modification. Delivery exclusively in accordance with our currently valid General Terms of Sale. Delivery incl. assembly drawing. Cannot be returned. Component weights are subject to fluctuations due to tolerances and may therefore diverge from what is specified.



Stairways with platform



Inclination	Step width [mm]	Platform height [m]	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80
		Number of steps	12	13	14	15	16	17	18	19
		Base-to-base distance [m]	2.87	3.07	3.27	3.47	3.67	3.87	4.07	4.27
100	600	Weight [kg]	52.7	57.4	74.7	78.8	83.0	88.6	92.8	96.9
40	600	Ref. No.	1126.412	1126.41	3 1126.414	1126.415	1126.416	1126.417	1126.418	1126.419
	000	Weight [kg]	58.6	63.7	81.5	86.0	90.6	96.7	101.3	105.8
	800	Ref. No.	1128.412	1128.41	3 1128.414	1128.415	1128.416	1128.417	1128.418	1128.419
Extra charge for		Weight [kg]	11.1	13.3	13.8	14.3	14.9	17.0	17.6	18.1
2nd stair gua	ırdrail	Ref. No.	1160.412	1160.41	3 1160.414	1160.415	1160.416	1160.417	1160.418	1160.419
Inclination	Step width [mm]	Platform height [mm]	2.88		3.12	3.	36	3.60		3.84
		Number of steps	12		13	1	4	15		16
		Base-to-base distance [m]	2.17		2.30 2.4		45	2.59		2.73
600	600	Weight [kg]	51.8		56.2	73	3.4	77.5		81.5
00	000	Ref. No.	1126.61	12	1126.613	112	6.614	1126.615	1	126.616
	000	Weight [kg]	57.7		62.5	80).2	84.7		89.1
	800	Ref. No.	1128.61	12	1128.613	1128	3.614	1128.615	1	128.616
Extra charge	for	Weight [kg]	10.3		12.2	12	2.7	13.2		13.7
2nd stair guardrail		Ref. No.	1160.61	12	1160.613	116).614	1160.615	1	160.616

Step Width

Base-to-base distance

Alu maintenance platform 113

Versatile servicing device for machinery, containers, trucks, buses, shelving systems etc. that do not permit the attachment of permanent equipment.

Platform height:

Max. 3.60 m (dimension from floor to top edge of platform)

Platform length:

0.60 m

Width:

 $\begin{array}{l} \mbox{Step width} + 0.12 \mbox{ m with stair guardrail on one side} \\ \mbox{Step width} + 0.17 \mbox{ m with stair guardrail on both sides} \end{array}$

Stair guardrail/guardrail:

The standard scope of supply includes all-round guardrails, in each case with the following parts: stair guardrail on both sides of the stair, platform guardrail on both sides, and the respective end guardrail. The parts can be fitted or removed to suit the situation on the spot, for example to allow crossover to adjacent structures at the end or at the sides. DIN EN ISO 14122-3 must be complied with here. Accordingly, for a stairway with a 45° inclination a stair guardrail is specified for **at least** one side. For a 45° angle and a wall clearance > 200 mm, or for 60°, a handrail must be provided on both sides.

Crosspiece:

For sure footing (see table of wheel set widths for dimensions)



			Supplied in the fully assembled state		Only guardrails have to be fitted on the spot				pot		
Inclination	Step width [mm]	Platform height [m]	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.20
		Number of steps	3	4	5	6	7	8	9	10	11
150		Base-to-base distance [m]	1.23	1.43	1.63	1.83	2.03	2.23	2.43	2.63	2.83
		Weight [kg]	54.9	59.1	63.5	67.7	72.9	77.9	85.8	90.8	97.7
	600	Wheel set width [m]	0.94	0.94	1.00	1.00	1.10	1.10	1.10	1.15	1.15
4J		Ref. No.	1136.403	1136.404	1136.405	1136.406	1136.407	1136.408	1136.409	1136.410	1136.411
	800	Weight [kg]	58.7	63.2	68.4	72.9	78.4	83.8	92.2	97.8	105.1
		Wheel set width [m]									
		Ref. No.	1138.403	1138.404	1138.405	1138.406	1138.407	1138.408	1138.409	1138.410	1138.411
Inclination	Step width [mm]	Platform height [m]	0.72	0.96	1.20	1.44	1.68	1.92	2.16	2.40	2.64
		Number of steps	3	4	5	6	7	8	9	10	11
		Base-to-base distance [m]	1.11	1.25	1.38	1.53	1.66	1.8	1.94	2.08	2.22
		Weight [kg]	54.6	58.5	63.1	67.4	71.7	76.6	84.3	91.5	96.4
600	600	Wheel set width [m]	0.94	0.94	1.00	1.10	1.10	1.15	1.25	1.25	1.25
00		Ref. No.	1136.603	1136.604	1136.605	1136.606	1136.607	1136.608	1136.609	1136.610	1136.611
		Weight [kg]	58.4	62.7	67.9	72.4	77.2	82.3	90.8	98.5	103.8
	800	Wheel set width [m]									
		Ref. No.	1138.603	1138.604	1138.605	1138.606	1138.607	1138.608	1138.609	1138.610	1138.611

Intermediate heights are possible on request when the appropriate platform is specified. Quotation and Technical Data Sheet will follow within 72 hours of receipt of the enquiry. All dimensions are guideline values. Subject to technical modification. Delivery exclusively in accordance with our currently valid General Terms of Sale. Delivery incl. assembly drawing. Cannot be returned. Component weights are subject to fluctuations due to tolerances and may therefore diverge from what is specified.

Maintenance platforms



without lateral projection at the sides, taking into account the ballasting then necessary

Delivery time and data on required ballasting: on request!

Inclination	Step width [mm]	Platform height [m]	2.40	2.60	2.80	3.00
		Number of steps	12	13	14	15
		Base-to-base distance [m]	3.03	3.23	3.43	3.63
		Weight [kg]	103.0	111.5	130.4	136.6
6	600	Wheel set width [m]	1.25	1.25	1.30	1.30
40		Ref. No.	1136.412	1136.413	1136.414	1136.415
	000	Weight [kg]	110.9	119.8	138.5	145.4
800		Wheel set width [m]	1.50	1.50	1.50	1.50
		Ref. No.	1138.412	1138.413	1138.414	1138.415
Inclination	Step width [mm]	Platform height [m]	2.88	3.12	3.36	3.60
				10	1.4	15
		Number of steps	12	13	14	10
		Number of steps Ausladung [m]	12 2.36	2.49	2.63	2.77
		Number of steps Ausladung [m] Weight [kg]	12 2.36 101.5	2.49 109.4	2.63 128.7	2.77 135.2
60°	600	Number of steps Ausladung [m] Weight [kg] Wheel set width [m]	12 2.36 101.5 1.25	2.49 109.4 1.30	2.63 128.7 1.40	2.77 135.2 1.50
60°	600	Number of steps Ausladung [m] Weight [kg] Wheel set width [m] Ref. No.	12 2.36 101.5 1.25 1136.612	13 2.49 109.4 1.30 1136.613	14 2.63 128.7 1.40 1136.614	2.77 135.2 1.50 1136.615
60°	600	Number of steps Ausladung [m] Weight [kg] Wheel set width [m] Ref. No. Weight [kg]	12 2.36 101.5 1.25 1136.612 109.3	13 2.49 109.4 1.30 1136.613 117.9	14 2.63 128.7 1.40 1136.614 137.1	2.77 135.2 1.50 1136.615 144.0
60°	600 800	Number of steps Ausladung [m] Weight [kg] Wheel set width [m] Ref. No. Weight [kg] Wheel set width [m]	12 2.36 101.5 1.25 1136.612 109.3 1.50	13 2.49 109.4 1.30 1136.613 117.9 1.60	14 2.63 128.7 1.40 1136.614 137.1 1.60	2.77 135.2 1.50 1136.615 144.0 1.70



Wheels with lock to immobilise the wheel and fork head can be fixed using a direction lock in the access direction or sideways direction.

PU = packaging unit 🛎 = available ex works 🕒 = delivery time on request 🖽 = only available in this packaging unit

Further variants on request

Alu bridging stairway, statical 114

For crossovers of containers, machinery, conveyor belts, assembly lines etc. Fastened using angled mounting sections to bottom of stair; standard version.

Platform height:

Max. 3.30 m (dimension from floor to top edge of platform) **Clear height vertical:**

Platform height - x (see sketch on page 43)

Width:

Step width + 0.19 m with stair guardrail on one side and on both sides $% \left({{{\rm{D}}_{\rm{B}}}} \right)$

Clear width:

 $45^{\circ} \ge 0.75 \text{ m}$

 $60^\circ \le 0.65 \text{ m}$

Stair guardrail / platform guardrail:

The standard scope of delivery includes per crossover a stair guardrail on one side and a platform guardrail (both of which can be optionally fitted either left or right). DIN EN ISO 14122-3 must be complied with. Accordingly, for a stairway with a 45° inclination a stair guardrail is specified for **at least** one side. For a 45° angle and a wall clearance > 200 mm, or for 60°, a handrail must be provided on both sides.

Platform length:	fastening bracket hole:
0.80 m	9 mm

Aluminium bridging stairways must be fastened to the floor (e.g. dowelled).

The safe transfer of the loads into the structure or the building ground must be approved by the customer.

			Supplied in the fully assembled state		Only guardrails have to be fitted on the spot					
Inclination	Step width [mm]	Platform height [m]	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00
		Number of steps	3	4	5	6	7	8	9	10
		Base-to-base distance [m]	1.90	2.30	2.70	3.10	3.50	3.90	4.30	4.70
150	600	Weight [kg]	40.0	45.4	50.7	56.1	62.1	68.2	77.4	83.3
40	000	Ref. No.	1146.403	1146.404	1146.405	1146.406	1146.407	1146.408	1146.409	1146.410
	000	Weight [kg]	43.4	49.6	55.8	62.0	68.8	75.8	85.8	92.6
800	800	Ref. No.	1148.403	1148.404	1148.405	1148.406	1148.407	1148.408	1148.409	1148.410
Extra charge	per	Weight [kg]	5.7	5.9	6.1	6.3	6.8	7.4	9.5	10.0
Stair guardra	il	Ref. No.	1160.403	1160.404	1160.405	1160.406	1160.407	1160.408	1160.409	1160.410

Intermediate heights are possible on request when the appropriate platform is specified. Quotation and Technical Data Sheet will follow within 72 hours of receipt of the enquiry. All dimensions are guideline values. Subject to technical modification. Delivery exclusively in accordance with our currently valid General Terms of Sale. Delivery incl. assembly drawing. Cannot be returned. Component weights are subject to fluctuations due to tolerances and may therefore diverge from what is specified.



EXTRA CHARGE FOR PLATFORM EXTENSION PER 200 MM PLATFORM EXPANDABLE TO MAX. 1.20 M



Step width 0.60 m Ref. No. 1152.602

Step width 0.80 m Ref. No. 1152.802

EXTRA CHARGE FOR PLATFORM GUARDRAIL (IN COMBINATION WITH THE ORDER FOR AN ALUMINIUM STAIR 114)

Ref. No. 1141.000



Platform guardrail	
Platform guardrail Stairway guard rail	

			Supplied in the fully assembled state			Only guardrails have to be fitted on the spot				
Inclination	Step width [mm]	Platform height [mm]	0.72	0.96	1.20	1.44	1.68	1.92	2.16	2.40
		Number of steps	3	4	5	6	7	8	9	10
		Base-to-base distance [m]	1.52	1.79	2.07	2.35	2.63	2.90	3.18	3.46
c0°	600	Weight [kg]	39.1	44.2	49.7	54.9	60.4	66.5	75.2	81.2
00	000	Ref. No.	1146.603	1146.604	1146.605	1146.606	1146.607	1146.608	1146.609	1146.610
	900	Weight [kg]	42.5	48.5	54.8	60.8	67.2	74.3	83.7	90.5
	000	Ref. No.	1148.603	1148.604	1148.605	1148.606	1148.607	1148.608	1148.609	1148.610
Extra charge	per	Weight [kg]	5.4	5.5	5.8	5.9	6.2	6.8	8.7	9.2
Stair guardra	il	Ref. No.	1160.603	1160.604	1160.605	1160.606	1160.607	1160.608	1160.609	1160.610

ACCESSORIES ACCESSES













Alternative steps made of steel grating Slip resistance: R11					
Width [m]	0.60	0.80			
Ref. No.	1151.601	1151.801			

Alternative steps made of aluminium grating Slip resistance: R11					
Width [m]	0.60	0.80			
Ref. No.	1151.602	1151.802			

Alternative steps made of steel perforated plate Slip resistance: R11					
Width [m]	0.60	0.80			
Ref. No.	1151.603	1151.803			

Alternative steps made of aluminium perforated plate Slip resistance: R11					
Width [m]	0.60	0.80			
Ref. No. 1151.604 1151.804					

Wall bracket for supporting and platform	d fastening of aluminium stairs with
Ref. No.	1171.000
To match:	Aluminium stairs with platform for step width 0.60 m

Wall bracket for supporting and fastening of aluminium stairs with platform		
Ref. No.	1172.000	
To match:	Aluminium stairs with platform for step width 0.80 m	









Swing doors for installation where exits are open at the sides in the platform area		
Ref. No.	1153.502	
To match:	Sides with step widths 0.60 m and 0.80 m	

Swing doors for installation where exits are open at the end in the platform area		
Ref. No.	1153.602	
To match:	End with step width 0.60 m	

Swing doors for installation where exits are open at the end in the platform area		
Ref. No.	1153.802	
To match:	End with step width 0.80 m	

Barrier chain for hanging across open exits		
Ref. No.	1153.601	
To match:	End with step width 0.60 m, sides with step widths 0.60 m and 0.80 m	
Ref. No.	1153.801	
To match:	End with step width 0.80 m	

LAYHER ROLLING TOWERS



Layher rolling towers offer professionals in the building trade and in industry individualised solutions for every task, but without extensive material being needed. Thanks to the modular principle, many assembly variants are possible with a few components. That reduces the need for stocks and cuts logistic costs. The lightweight and handy system components made of aluminium with snap-on claw not only permit quick and easy assembly, but also ensure high stability for concentrated working at a height of nearly 14 meters. Layher rolling towers are a persuasive solution thanks to their ample working platform and working height adjustment. Their adaptability to site conditions enables every professional on the scaffolding to work ergonomically and so improve their individual safety and efficiency.

For top performance at great heights, you need high stability. Layher has, with its consistent approach to safety and quality, designed products which conform to statutory safety requirements. Inspections by independent institutes have corroborated this. The Layher brand stands for more than 75 years of experience in the design and manufacture of rolling towers at the central production location in Gueglingen. Quality "Made by Layher" means "Made in Germany".

With its rolling tower family, Layher offers customers from the building trades and from industry scaffolding systems for economical working at any height, both indoors and outdoors.

THE BENEFITS FOR YOU

- Layher offers for every site requirement the rolling tower to match. Thanks to the modular principle, many assembly variants are possible with a few components.
- The option of using the Layher Safety Structure P2 enable you to conform to the German Ordinance on Industrial Safety and Health without extra expense.
- Ergonomic assembly and high profitability thanks to the handy system components made of aluminium.
- You can rely on maximum quality and safety thanks to a recognised quality management system and inspections by independent institutes.





WHEELS

Sturdy wheels for high manoeuvrability and stable stance during work. Various wheel coatings permit use even on sensitive floor coverings. The steel base plates ensure easy and precise height equalisation while transmitting the loads centrally into the locked wheel. This improves the stability, enabling the user to work efficiently.



LADDER FRAMES

The ladder frame doubles as the scaffolding frame and as an access. The grooves of the rungs ensure maximum slip prevention and secure grip for vertical access.

The ladder frames are available in the lengths 1.00 m and 2.00 m and in the widths 0.75 m and 1.50 m.

Long and conical spigots ensure a secure and easy-action connection of the ladder frames to one another, easily made safer by spring clips.



GUARDRAILS AND DIAGONAL BRACES WITH SNAP-ON CLAWS

Unbeatably fast connection without using tools. A slight pressure, and the claw snaps into place by itself. Various colours of the claw fingers for guardrails and diagonal braces help to tell the components apart – that saves time.





DECKS

Sturdy decks made from aluminium frames with plywood insert and snap-on claws ensure easy handling. They have a non-slip surface for a firmer and safer stance even in wet weather. A maximum-size working surface is obtained with a width of 68 cm. The differently shaped snap-on claws permit easy 1-man assembly and at the same time provide quadruple lift-off prevention. The toe board for protection from falling material or tools form a self-holding rim to ensure a maximum working surface.

STABILITY

The stability of the rolling tower must be assured for every phase of its assembly and dismantling. Depending on the assembly height and whether the tower is assembled outdoors or in a closed room, the following measures must be taken:

- installation of mobile beam
- use of stabilizers
- ballasting

LAYHER ROLLING TOWERS

THE RIGHT ROLLING TOWER FOR EACH TASK



LAYPLAN ROLLING TOWER-CONFIGURATOR



By using this LayPLAN module, it is possible to choose between standard and individual rolling tower solutions – quickly and easily. After entering of working height, the required working space and selection of the equal assembly structure, the program gives you a solution offer with pictures and material lists. Applications with internal ladder access, wall support or console brackets can be chosen – also as structures with mobile beam or stabilizers. All assembly structures according to the user manuals are available.

THE BENEFITS FOR YOU

- Quick planning and selection of the equal rolling tower type. No matter if standard or individual.
- > Download of all user manuals of the Layher rolling towers.
- Optionally the material list can be generated with or without required ballastings.
- Single components can be edited, added or deleted from the material list.



When you buy, you receive instructions for assembly and use that must be followed without fail for assembly, dismantling and use. * According to the max. working surface



LayPLAN Rolling Tower Configurator
Order now for free at fg-konfigurator.layher.com





STANDARD DIN EN 1004, MOBILE WORKING PLATFORMS

AMENDMENT OF STANDARD EN 1004

The standard / rules, and hence state of the art, for mobile working platforms is the European standard:

DIN EN 1004

This standard has been subdivided into separate parts since 2021, and containing specifications for the manufacture, inspection and use of the appropriate products.

SUBDIVISION OF STANDARD DIN EN 1004:

- DIN EN 1004-1 Part 1
 - Title: "Mobile access and working towers made of prefabricated elements – Part 1: Materials, dimensions, design loads, safety and performance requirements"
 - Publication date: 01.02.2021
 - Supersedes the standard: DIN EN 1004:2005-03
- DIN EN 1004-2 Part 2
 - Title: "Mobile access and working towers made of prefabricated elements – Part 2: Rules and guidelines for the preparation of an instruction manual"
 - Publication date: 01.03.2022
 - Supersedes the standard: DIN EN 1298:1996-04

AMENDMENTS DUE TO NEW VERSION DIN EN 1004-1:2021-02

Part 1 of the new version came into effect upon the end of the transition period on 30.11.2021, after which date manufacturers may only market mobile working platforms conforming to the new version and indicating conformity to standard DIN EN 1004.

CHANGE IN SCOPE OF APPLICATION

PREVIOUSLY: The previous version of DIN EN 1004 applied for a platform height of 2.50 metres and above. Platform heights below that were governed by national rules. Even if these had been already withdrawn over the years, they were still deemed to be state of the art.

NEW: The scope of the new version now covers mobile working platforms of and above a platform height of "> 0 metres". All structures, even those below 2.50 metres, are thus taken into account and must conform to the standard in all respects, with appropriate indication thereof.

An important aspect here:

3-part side protection starting at platform height > 0 m

Changes in the product portfolio:

All models with a platform height below 2 metres are now designed "conforming to the standard" with 3-part side protection.

Recommendation by Layher

- New purchases always in accordance with the new standard DIN EN 1004-1:2021: Models conforming to the standard, i.e. with 3-part side protection (guardrail/guardrail at 0.5 m height/toe board)
- For expansion / retrofitting: Parts according to retrofit set table

Example:

PREVIOUSLY: Zifa Tower 1406210







MAXIMUM DISTANCE BETWEEN THE DECK SURFACES

PREVIOUSLY: In the previous version of DIN EN 1004, a maximum distance of 4.20 metres between the deck surfaces applied. This related to the models that were listed with the remark "Minimum requirement DIN EN 1004:2005".

NEW: In the new version, the maximum distance between the deck surfaces is now set at 2.25 metres. As a result, mobile working platforms not exceeding this maximum distance may be marketed in conformity to standard DIN EN 1004-1:2021. These requirements have already been met by models with Safety Assembly P2 since 2009, and therefore are and remain in conformity to the standard – even after amendment.

Changes in the product portfolio:

All models previously listed with the remark "Minimum requirement DIN EN 1004:2005" will no longer be advertised and marketed with the indication of conformity to standard DIN EN 1004-1:2021.

Recommendation by Layher

- New purchases always in accordance with the new standard DIN EN 1004-1:2021: Models conforming to standard DIN EN 1004-1:2021 with Safety Assembly P2 (as since 2009, but now conforming to the standard only in this form)
- > For expansion / retrofitting: Parts according to retrofit set table

PREVIOUSLY: Uni Standard 1104

NEW: Uni Standard 1401104



AMENDMENTS DUE TO NEW VERSION DIN EN 1004-2:2022-03

Part 2 of the new version came into effect on 01.03.2022 with a transition period until 01.05.2022. After that date, the manufacturers may only prepare instructions for assembly and use conforming to this new version.

REQUIREMENTS FOR ASSEMBLY AND DISMANTLING PRO-CESSES IN THE INSTRUCTIONS FOR ASSEMBLY AND USE

PREVIOUSLY: The previous standard DIN EN 1298:1996-04 required that the procedure for construction of the mobile working platform be described in the instructions for assembly and use. The intention here was to explain assembly and dismantling to the user in an understandable way and to indicate potential risks arising from non-compliance.

NEW: In the new version DIN EN 1004-2:2022-03 which supersedes the standard DIN EN 1298:1996-04, it is required from the manufacturer of mobile working platforms that the description of assembly and dismantling incorporates the following passage when the instructions for assembly and use are drafted:

"The assembly and dismantling processes must ensure that no person may stand on a platform without guardrail and intermediate side protection. For example by a lower platform with guardrail and intermediate side protection or by another method having the same effectiveness." (see Fig. 1)



Guardrail = guardrail at 1 m height Intermediate side protection = guardrail at 0.5 m height (knee height)

Taking into account this amendment, guardrails in the form of handrails at 1 m height, for the Safety Assembly P2 process deemed SAFE for years, are now no longer sufficient and must be supplemented by intermediate guardrails at 0.5 m height before access to the level to be constructed.

Changes in the product portfolio:

The amendment to the standard does not affect the product portfolio.

Changer for the user when assembling and dismantling:

Fitting and removing of the intermediate guardrails will in future be performed in a sitting position from the hatch *(see Fig. 2)*.

Fitting of the additional guardrails permits access to the respective level in its state with 2-part side protection all round. The instructions for assembly and use have been supplemented with additional steps for description in conformity with the standard of the fitting and removal of intermediate guardrails during

the assembly and dismantling procedure. For Safety Assembly P2, only the updated instructions for assembly and use remain valid after the standard has come into effect.





WHAT DO THE AMENDMENTS TO STANDARD DIN EN 1004-2 MEAN FOR DEALERS?

Mobile working platforms marketed in the past remain, even after publication of the new version of the standard, in conformity with the standard and do not become dangerous or unsafe per se. All components can still be advertised and marketed without restriction.

To ensure that health and safety are protected during use of the products for their intended purpose and in conformity with the standard, Layher continues to recommend Safety Assembly P2 with the amended assembly and dismantling procedure in accordance with the amended instructions for assembly and use.

WHAT DOES THE AMENDMENT TO STANDARD DIN EN 1004-2 MEAN FOR END USERS?

Newly purchased or already stocked mobile working platforms can be used / can continue to be used without restrictions while taking into account Safety Assembly P2. Assembly and dismantling must be performed in future in accordance with the updated instructions for assembly and use.

- For users already applying Safety Assembly P2, there is no need to change their stocks. There are thus no costs incurred by the amendment of Part 2 of the standard.
- To be and remain up to date in respect of both statutory and in particular safety requirements and also in respect of the state of the art, and also to ensure use of products for their intended purpose and in conformity with the standard, Layher recommends when purchasing new mobile working platforms to use Safety Assembly P2 or models having indication of conformity to standard DIN EN 1004-1:2021 = "Safety Included". Layher further recommends checking and where necessary adaptation of the risk assessment and where necessary to upgrade existing stocks using the retrofit sets, and also to perform assembly and dismantling in accordance with the updated instructions for assembly and use.

More safety, when using Layher rolling towers

Because of the standard changes, which are described on the previous pages and because of European industrial safety laws, you as an employer must ensure that your workforce is only provided with equipment that, when used for its intended purpose, guarantees both safety and health protection. Appropriate safety measures have to be taken by you. Collective risk prevention takes precedence here over individual risk prevention.

To comply in full with all requirements, Layher has now devised the Safety Structure P2. The Layher Safety Structure P2 represents the collective safety measure.

The Safety Structure P2

- Platforms with a vertical spacing of 2 m.
- Safer design with integrated collective side protection.

Thanks to the platforms assembled with a 2 meter spacing, the rear guardrails can already be fitted from the level below. Additionally intermediate guardrails are fitted through the trapdoor. By doing so, there is already a two-part side protection when the next platform is accessed.

CAN BE RETROFITTED WITH THE LAYHER MODULAR SYSTEM:

If you already have a Layher rolling tower, you can upgrade it to the P2 design without any problem.

THE BENEFITS FOR YOU

The ingeniously simple assembly principle

- All round side protection already in place when accessing the next platform up.
- More stability in the rolling tower thanks to additional stiffeners.

Platforms spaced 2 meters apart:

- Maximum safety during assembly, ascent and descent and during the actual work.
- Easy passing on of rolling tower parts or work materials from one level to the next.

The innovative Uni assembly hook:

 Considerably simplifies assembly and ensures fast and hitch-free assembly and dismantling.



The principle – Simple. Swift. Safe.

1 Fit the first ladder frame.

Attach the Uni assembly hooks and position the second ladder frame for fitting of the rear guardrails.



3 Insert diagonal braces and access deck.



2 Swing ladder frame with rear guardrail upwards and fit into place.



4 Fitting the intermediate guardrails through the trapdoor.





SOLOTOWER

FASTER, EASIER AND SAFER ASSEMBLY BY ONE PERSON



The SoloTower from Layher is a small rolling tower that can be assembled quickly, safely and easily by a single person, up to a working height of 6.15 metres.

Current industrial safety regulations for working at heights are increasingly restricting the use of ladders. These regulations are frequently detrimental to the profitability of businesses. Previously, businesses have had to plan with high-volume work platforms. The result is a major logistic effort, plus an increased personnel requirement of at least two persons.

This additional economic burden is avoided by using the SoloTower.

Thanks to its compact dimensions, the SoloTower can be transported to its place of use in normal commercial vans or trucks. Transport and assembly can be handled by a single person all the way.

TECHNICAL DATA

- Working height: 6.15 m
- Area of working platform: 0.75 x 1.13 m
- Permissible live load: 2 kN / m² (load class 3)





LOGISTICS

The compact dimensions of all components permit economical and efficient logistics for storage and transport and at the site. A few of the components are used to construct, without any tools, a "transport trolley" in which the other scaffolding parts can be moved quickly and ergonomically to the intended location. This "transport trolley" fits through any normal door.



SAFE ASSEMBLY AND DISMANTLING

With the specified assembly and dismantling sequence of the SoloTower using the 3-T method (Through The Trapdoor \blacktriangleright i.e. seated in the access hatch), the user is already in a secure area when moving up to the next platform up, due to the pre-assembled double guardrail, in compliance with the valid regulations for industrial and work safety.



SINGLE-PERSON ASSEMBLY

Lightweight, handy and compact components made of aluminium in combination with the SoloTower assembly hook make it easy to pass individual components from level to level, permitting efficient and economical assembly and dismantling by only one person.



TOOL-FREE ASSEMBLY

Layher's proven connection technology using the snap-on claw permits the accustomed tool-free, fast and easy assembly of the sturdy aluminium components. Layher rolling tower components are synonymous with durability and stability.



TOE BOARD UNIT

The end and side toe boards made of aluminium are already preassembled to create a fold-out toe board unit. The toe boards can be spread out and folded up in next to no time, and fitted to the platform quickly and easily.



TELESCOPING STABILIZERS

Quickly and easily attached stabilizers ensure a firm standing of the SoloTower on uneven ground too.



WHEELS

Sturdy wheels for high manoeuvrability and stable stance during work. The steel base plates ensure easy and precise height equalisation while transmitting the loads centrally into the locked wheel. This improves the stability and enables the user to work efficiently.



QUALITY AND SAFETY

The SoloTower has been designed to meet the requirements in the European standard DIN EN 1004 for mobile work platforms, ensuring maximum quality and safety.

ECONOMIC EFFICIENCY

The ladder frames of the SoloTower are, thanks to the Layher construction kit system, also used for the proven Zifa, Uni Standard and Uni Light rolling towers.



SoloTower

Part list	The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards)			
Tower model	Ref. No.	1600102	1600103	1600104
Toe board unit 1.13 m x 0.75 m	1240.113	1	1	1
SoloTower access deck 1.13 m	1242.113	1	2	2
Telescoping stabilizer - 1.25 m	1248.000	4	4	4
Rotation preventer for stabilizers	1248.261	4	4	4
Spring clip	1250.000	8	12	16
Ladder frame 75/4 - 1.00 m	1297.004	6	8	10
SoloTower assembly hook (set 4 pieces)	1300.002	1	1	1
SoloTower assembly bag	1300.003	1	1	1
Castor	1300.150	4	4	4
Double guardrail	1342.113	4	6	7
Ballast	1249.000		For requirement see table below	





Tower model	1600102 SoloTower aluminium rolling tower	1600103 SoloTower aluminium rolling tower	1600104 SoloTower aluminium rolling tower
Working height [m]	4.15	5.15	6.15
Tower height [m]	3.38	4.38	5.38
Platform height [m]	2.15	3.15	4.15
Weight [kg] (without ballast)	118.8	151.9	167.6
Ballast (stated in units)			
In closed areas			
Assembly central	0	0	0
Assembly off-set	LO R5	LO R8	LO R10
Assembly off-set with wall bracing	0	0	0
Outdoors			
Assembly central	0	0	0
Assembly off-set	LO R5	LO R8	LO R10
Assembly off-set with wall bracing	0	0	0

X = not possible/not permissible 0 = no ballast required For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guidel **Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points** (see instructions for assembly and use). In central assembly, the ballast weights are distributed evenly over all four ladder frame standards. The remainder not divisible by 4 must be fitted in accordance with the instructions for assembly and use. In off-set assembly on mobile beams, the ballast weights must be distributed evenly over the two ladder frame standards are standards are standards.

SOLOTOWER WITH TELESCOPIC GUARDRAIL

A HELPFUL ADDITION FOR ROLLING TOWERS



The Layher SoloTower with 4.15 m work height and system integrated advanced guardrails.

To keep the investment costs of the users as low as possible, Layher expanded the SoloTower with an additional assembly variant – SoloTower with telescopic guardrails. Additionally to the well-known assembly variant with 3T-method, the SoloTower with telescopic guardrails enhances the support of the German BG Bau.

Tower model	1600202 Aluminum rolling tower with telescopic guardrail
Working height [m]	4.15
Tower height [m]	3.38
Platform height [m]	2.15
Weight [kg] (without ballast)	121.1
Ballast (stated in units)	
In closed areas	
Assembly central	0
Assembly off-set	LO R5
Assembly off-set with wall bracing	0
Outdoors	
Assembly central	0
Assembly off-set	LO R5
Assembly off-set with wall bracing	0

Tower model	Ref. No.	1600202
SoloTower telescopic guardrail 1.13 m	1204.113	4
Toe board unit 1.13 m x 0.75 m	1240.113	1
SoloTower access deck 1.13 m	1242.113	1
Telescoping stabilizer - 1.25 m	1248.000	4
Rotation preventer for stabilizers	1248.261	4
Spring clip	1250.000	8
Ladder frame 75/4 - 1.00 m	1297.004	6
SoloTower assembly hook (set 4 pieces)	1300.002	1
SoloTower assembly bag	1300.003	1
Uni assembly hook	1300.010	2
Castor	1300.150	4
Double guardrail	1342.113	2
Ballast	1249.000	For requirement see table above

SOLOTOWER STAIR KIT SOLUTION

THE ADDITIONAL KIT FOR YOUR SOLOTOWER

The stair kit for the SoloTower permits safer use of rolling towers inside stairwells while ensuring flexible working. By expanding standard rolling tower models with a few individual components, the SoloTower offers in combination with the stair kit an economically smarter, swifter and safer alternative for working at heights, and in particular an alternative to rung ladders, which are now only usable to a limited extent due to current occupational safety regulations.



		SoloTower stair kit TYPE 1	SoloTower stair kit TYPE 2
Tower model	Ref. No.	1600001	1600003
Suspended ladder for passageway ladder frame	1247.006	0	1
Adjustable base plate 60 with lock	1257.060	4	4
Tele distance tube 1.25 m	1275.001	2	2
Passageway ladder frame 75/8 - 2.00 m	1296.008	1	2
Ladder frame 75/2 - 0.50 m	1297.002	1	1
Rubber underlay for base plate	4000.500	4	4
Double coupler	4700.019	4	4
Hand wheel with bush	6491.422	8	8

THE BENEFITS FOR YOU

- Use of rolling towers in stairwells up to platform height of 5 m.
- Passageways to suit the site complete blocking off of the stair not needed.
- > Passageway also as entrance for upward access.
- Adaptation to stair steps riser and tread is possible.
- Single-person assembly.



SOLOTOWER WITH STAIR KIT SOLUTION

THE COMPLETE KITS WITH STAIR SOLUTION



Tower model	1600193 SoloTower aluminium rolling tower	1600195 SoloTower aluminium rolling tower
Working height [m]	4.65	6.65
Tower height [m]	3.88	5.88
Platform height [m]	2.65	4.65
Weight [kg] (without ballast)	150.3	199.1
Ballast (stated in units)		
In closed areas		
Assembly central	I3 r3	17 r7
Structure with restraint between the walls	0	0
Assembly off-set with wall bracing	18 r0	I16 r0

Tower model	Ref. No.	1600193	1600195
Toe board unit 1.13 m x 0.75 m	1240.113	1	1
SoloTower access deck 1.13 m	1242.113	1	2
Suspended ladder for passageway ladder frame	1247.006	1	1
Telescoping stabilizer - 1.25 m	1248.000	4	4
Rotation preventer for stabilizers	1248.261	4	4
Spring clip	1250.000	6	14
Adjustable base plate 60 with lock	1257.060	4	4
Tele distance tube 1.25 m	1275.001	2	2
Passageway ladder frame 75/8 - 2.00 m	1296.008	2	2
Ladder frame 75/2 - 0.50 m	1297.002	1	1
Ladder frame 75/4 - 1.00 m	1297.004	2	6
SoloTower assembly hook (set 4 pieces)	1300.002	1	1
SoloTower assembly bag	1300.003	1	1
Double guardrail	1342.113	6	9
Rubber underlay for base plate	4000.500	4	4
Double coupler	4700.019	4	4
Hand wheel with bush	6491.422	8	8
Ballast	1249.000	For requirement	see table above

ZIFA THE READY-MADE TOWER FOR WORKING AT LOW HEIGHTS





The Zifa tower is practically a "ready-made tower" for working at low heights: Folded together flat for storage and transport – fold it out, insert the deck – that's all.

The basic unit can be passed through standard room doors when assembled and fully loaded.

Basic tower of aluminium for alternating-sequence push-fit assembly; rear guardrails and diagonal braces of aluminium snap in easily.

Work decks with aluminium frame and plywood insert, also as a hatch-type deck for risk-free internal access.

Strong castors (permanently fitted) ensure particular stability.

The zifa family can also be equipped with stabilizers. Learn more about that on page 64.

TECHNICAL DATA

- Max. working height: 7.76 m
- Area of working platform: 0.75 x 1.80 m
- Permissible live load: 2 kN / m² (load class 3)





Part list		The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards)							
Tower model	Ref. No.	1406200	1406210	1406213	1406214	1406215	1406216	1406300	1406310
Guardrail 1.80 m	1205.180	0	2	4	9	8	13	3	4
Diagonal brace 2.50 m	1208.180	0	0	1	2	4	4	0	0
Diagonal brace 1.95 m	1208.195	0	0	0	1	0	1	0	0
Basic tube 1.80 m	1211.180	0	0	1	1	1	1	0	0
Deck 1.80 m	1241.180	1	0	1	0	1	0	1	0
Access deck 1.80 m	1242.180	0	1	1	2	2	3	0	1
Spring clip	1250.000	0	4	8	12	12	16	0	4
Ladder frame 75/4 - 1.00 m	1297.004	0	2	0	2	0	2	0	2
Ladder frame 75/8 - 2.00 m	1297.008	0	0	2	2	4	4	0	0
Zifa 75 basic tower 1.80 m x 0.75 m	1300.006	1	1	1	1	1	1	1	1
Uni assembly hook	1300.010	0	0	1	1	1	1	0	0
Castor 400 - 4 kN	1301.150	4	4	4	4	4	4	4	4
Mobile beam 1.80 m with bar	1323.180	0	0	2	2	2	2	0	0
End toe board 0.75 m	1438.075	0	0	2	2	2	2	2	2
Toe board 1.80 m with claw	1439.180	0	0	2	2	2	2	2	2
Ballast	1249.000				For requirement	see table belov	V		

Retrofitting table	Simply safe with the P2 retrofit kits:	h the P2 retrofit kits: The rollings can be easily retrofitted to the safety structure P2, to conform to the current standards			
Retrofit set		Ref. No.	1400035		
for tower model			1406210		
Guardrail 1.80 m		1205.180	2		
End toe board 0.75 m		1438.075	2		
Toe board 1.80 m with claw		1439.180	2		
* Any mobile beam 1.80 m (1214.180) in stock can remain in u Any double guardrails (1206.180) available can also remain in	se. n use.				

Working height Scaffolding height with spigot	1		
Platform height			
The Zifa family		No and No and No.	

		12
Tower model	1406200	1406210
	Zifa P2	Zifa P2
Working height [m]	2.86	3.61
Tower height [m]	2.09	2.84
Platform height [m]	0.86	1.61
Weight [kg] (without ballast)	41.9	59.7
Ballast (stated in units)		
In closed areas		
Assembly central	14 r4	16 r6
Assembly off-set	Х	Х
Assembly off-set with wall bracing	14 r0	16 r0
Outdoors		
Assembly central	14 r4	l6 r6
Assembly off-set	Х	Х
Assembly off-set with wall bracing	14 r0	16 r0

The product shown (Ref. no. 1406210) is only standard-compliant by purchasing the retrofit set (Ref. nos. 1400035) according to DIN EN 1004:2021.

* The here shown ballasting is only necessary when climbing outsides.

The rele shown balasting is only necessary when clinitary dustes. X = not possible 0 = no balast required For balasting, use Layher balast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guidel **Do not use any liquid or granular ballast meterials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).** In central assembly, the ballast weights are distributed evenly over all four ladder frame standards. The remainder not divisible by 4 must be fitted in accordance with the instructions for assembly and use. In off-set assembly on mobile beams, the ballast weights must be distributed evenly over the two ladder frame standards are standards away from the wall.

Zifa

SAFETY ASSEMBLY 7

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.





1406310 Zifa P2	1406213 Zifa P2	1406214 Zifa P2	1406215 Zifa P2	1406216 Zifa P2
3.61	4.76	5.76	6.76	7.76
2.84	3.99	4.99	5.99	6.99
1.61	2.76	3.76	4.76	5.76
75.9	141.7	170.8	193.4	219.2
l6 r6	0 0	l2 r2	l4 r4	l4 r4
Х	LO R2	LO R4	LO R6	LO R8
16 r0	0 0	L2 R0	L6 R0	L8 R0
16 r6	0 0	l2 r2	14 r4	14 r4
Х	LO R2	LO R6	LO R8	Х
16 r0	0 0	L4 R0	L8 R0	L16 R0



All dimensions and weights are guideline values. Subject to technical modification. Our deliveries shall be made exclusively in accordance with our currently valid General Terms of Sale. Title to the delivered goods shall be retained until full payment has been made. When purchasing, you receive instructions for assembly and use that must be followed without fail or assembly, dismantling and use.

Zifa with stabilizers, extendable

Part list	TI	The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards				
Tower model	Ref. No.	1406233	1406234	1406235	1406236	1406237
Guardrail 1.80 m	1205.180	4	9	8	13	12
Diagonal brace 2.50 m	1208.180	1	2	4	4	6
Diagonal brace 1.95 m	1208.195	0	1	0	1	0
Deck 1.80 m	1241.180	1	0	1	0	1
Access deck 1.80 m	1242.180	1	2	2	3	3
Telescoping stabilizer - 2.60m	1248.260	4	4	4	4	4
Rotation preventer for stabilizers	1248.261	4	4	4	4	4
Spring clip	1250.000	4	8	8	12	12
Ladder frame 75/4 - 1.00 m	1297.004	0	2	0	2	0
Ladder frame 75/8 - 2.00 m	1297.008	2	2	4	4	6
Zifa 75 basic tower 1.80 m x 0.75 m	1300.006	1	1	1	1	1
Uni assembly hook	1300.010	1	1	1	1	1
Castor 400 - 4 kN	1301.150	4	4	4	4	4
End toe board 0.75 m	1438.075	2	2	2	2	2
Toe board 1.80 m with claw	1439.180	2	2	2	2	2
Ballast	1249.000		For	requirement see table b	elow	



Tower model	1406233 Zifa P2 with stabilizers	1406234 Zifa P2 with stabilizers
Working height [m]	4.61	5.61
Tower height [m]	3.84	4.84
Platform height [m]	2.61	3.61
Weight [kg] (without ballast)	144.6	174.1
Ballast (stated in units)		
In closed areas		
Assembly central	0	0
Assembly off-set	LO R4	LO R6
Assembly off-set with wall bracing	0	0
Outdoors		
Assembly central	0	0
Assembly off-set	LO R6	LO R10
Assembly off-set with wall bracing	0	0

X = not possible/not permissible 0 = no ballast required For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guidel **Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).** In central assembly, the ballast weights are distributed evenly over all four ladder frame standards. The remainder not divisible by 4 must be fitted in accordance with the instructions for assembly and use. In off-set assembly on mobile beams, the ballast weights must be distributed evenly over the two ladder frame standards away from the wall.

SAFETY ASSEMBLY 7

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.



1406235 Zifa P2 with stabilizers	1406236 Zifa P2 with stabilizers	1406237 Zifa P2 with stabilizers
6.61	7.61	8.61
5.84	6.84	7.84
4.61	5.61	6.61
196.7	222.5	245.1
0	l2 r2	l2 r2
LO R8	LO R10	LO R14
0	0	0
l2 r2	14 r4	18 r8
LO R12	L0 R18	L0 R22
0	0	0

All dimensions and weights are guideline values. Subject to technical modification. Our deliveries shall be made exclusively in accordance with our currently valid General Terms of Sale. Title to the delivered goods shall be retained until full payment has been made. When purchasing, you receive instructions for assembly and use that must be followed without fail or assembly, dismantling and use.



UNI LIGHT

THE PRACTICAL ROLLING TOWER FOR WORKING IN CRAMPED CONDITIONS



The Uni Light tower is a compact and lightweight rolling tower for safer and comfortable working wherever you formerly needed a ladder – the standing surface of a full 1.30 m^2 permits unimpeded movement and the carrying of tools and material.

Its low weight and handy dimensions make the Uni Light particularly easy to transport, even in a van. Ladder frames of aluminium for push-fit assembly; rear guardrails and diagonal braces of aluminium snap in easily.

Work decks with aluminium frame and plywood insert, as a hatch-type deck for risk-free internal access.

Strong castors (permanently fitted) ensure particular stability.

Mobile rigid beam, made of steel, for widening the base; with spigots for optional mounting of the ladder frames for work on ceilings or walls.

The Uni Light family can also be equipped with stabilizers. Learn more about that on page 70.

TECHNICAL DATA

- Max. working height: 9.26 m
- Area of working platform: 0.75 x 1.80 m
- Permissible live load: 2 kN / m² (load class 3)



Uni Light

Part list		The l	_ayher modular sys	tem permits proble	m-free expansion o	of your rolling towe	r (for pictures see p	oage 114 onwards).
Tower model	Ref. No.	1403201	1403202	1403203	1403204	1403205	1403206	1403207
Guardrail 1.80 m	1205.180	0	4	9	8	13	12	17
Double guardrail 1.80 m	1206.180	2	0	0	0	0	0	0
Diagonal brace 2.50 m	1208.180	0	2	2	4	4	6	6
Diagonal brace 1.95 m	1208.195	0	0	2	0	2	0	2
Basic tube 1.80 m	1211.180	0	1	1	1	1	1	1
Deck 1.80 m	1241.180	0	1	0	1	0	1	0
Access deck 1.80 m	1242.180	1	1	2	2	3	3	4
Spring clip	1250.000	0	8	8	12	12	16	16
Ladder frame 75/4 - 1.00 m	1297.004	0	2	0	2	0	2	0
Ladder frame 75/8 - 2.00 m	1297.008	2	2	4	4	6	6	8
Uni assembly hook	1300.010	0	1	1	1	1	1	1
Castor 400 - 4 kN	1301.150	4	4	4	4	4	4	4
Mobile beam 1.80 m with bar	1323.180	0	2	2	2	2	2	2
End toe board 0.75 m	1438.075	2	2	2	2	2	2	2
Toe board 1.80 m with claw	1439.180	2	2	2	2	2	2	2
Ballast	1249.000		For requirement see table below					



The Uni Light family

Tower model	1403201 Uni Light P2	1403202 Uni Light P2	1403203 Uni Light P2
Working height [m]	3.11	4.26	5.26
Tower height [m]	2.34	3.49	4.49
Platfrom height [m]	1.11	2.26	3.26
Weight [kg] (without ballast)	65.5	134.2	160.8
Ballast (stated in units)			
In closed areas			
Assembly central	l4 r4	0	0
Assembly off-set	Х	0	LO R2
Assembly off-set with wall bracing	Х	0	0
Outdoors			
Assembly central	l4 r4	0	0
Assembly off-set	Х	0	LO R4
Assembly off-set with wall bracing	Х	0	0

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required
 For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
 All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guidel
 **Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
 Example: I2, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side.
 L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side.
 r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding, I and L relate to the side facing the scaffolding (see instructions for assembly and use).**

SAFETY ASSEMBLY 7

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.



1403204 Uni Light P2	1403205 Uni Light P2	1403206 Uni Light P2	1403207 Uni Light P2
6.26	7.26	8.26	9.26
5.49	6.49	7.49	8.49
4.26	5.26	6.26	7.26
182.6	209.2	231.0	257.6
l2 r2	l3 r3	l5 r5	l6 r6
L0 R4	LO R6	L2 R8	L2 R10
L2 R2	L4 R2	L6 R4	L6 R6
l3 r3	l5 r5	19 r9	l13 r13
LO R6	LO R10	L4 R14	Х
L4 R2	L6 R4	L10 R8	Х

All dimensions and weights are guideline values. Subject to technical modification. Our deliveries shall be made exclusively in accordance with our currently valid General Terms of Sale. Title to the delivered goods shall be retained until full payment has been made. When purchasing, you receive instructions for assembly and use that must be followed without fail or assembly, dismantling and use.



Uni Light with stabilizers, extendable

Part list	The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards).						
Tower model	Ref. No.	1403223	1403224	1403225	1403226	1403227	
Guardrail 1.80 m	1205.180	10	10	14	14	18	
Diagonal brace 2.50 m	1208.180	2	4	4	6	6	
Diagonal brace 1.95 m	1208.195	2	0	2	0	2	
Access deck 1.80 m	1242.180	2	2	3	3	4	
Telescoping stabilizer - 2.60m	1248.260	4	4	4	4	4	
Rotation preventer for stabilizers	1248.261	4	4	4	4	4	
Spring clip	1250.000	4	8	8	12	12	
Ladder frame 75/4 - 1.00 m	1297.004	0	2	0	2	0	
Ladder frame 75/8 - 2.00 m	1297.008	4	4	6	6	8	
Uni assembly hook	1300.010	1	1	1	1	1	
Castor 400 - 4 kN	1301.150	4	4	4	4	4	
End toe board 0.75 m	1438.075	2	2	2	2	2	
Toe board 1.80 m with claw	1439.180	2	2	2	2	2	
Ballast	1249.000	For requirement see table below					



The Uni Light family with stabilizers

Tower model	1403223 Uni Light P2 with stabilizers	1403224 Uni Light P2 with stabilizers
Working height [m]	5.10	6.10
Tower height [m]	4.33	5.33
Platform height [m]	3.10	4.10
Weight [kg] (without ballast)	166.4	177.2
Ballast (stated in units)		
In closed areas		
Assembly central	0	0
Assembly off-set	LO R4	LO R8
Assembly off-set with wall bracing	0	0
Outdoors		
Assembly central	0	0
Assembly off-set	LO R6	LO R10
Assembly off-set with wall bracing	0	0

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guide!
 **Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use). Example:
 I2, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side. L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side. r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).**

SAFETY ASSEMBLY 7

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.



1403225 Uni Light P2 with stabilizers	1403226 Uni Light P2 with stabilizers	1403227 Uni Light P2 with stabilizers
7.10	8.10	9.10
6.33	7.33	8.33
5.10	6.10	7.10
214.8	225.6	263.2
0	l2 r2	l2 r2
LO R10	LO R12	L0 R14
0	0	0
l3 r3	l6 r6	l8 r8
LO R14	Х	Х
0	0	l2 r0

All dimensions and weights are guideline values. Subject to technical modification. Our deliveries shall be made exclusively in accordance with our currently valid General Terms of Sale. Title to the delivered goods shall be retained until full payment has been made. When purchasing, you receive instructions for assembly and use that must be followed without fail or assembly, dismantling and use.

Uni Light

Part list		The La	ayher modular syste	em permits problem	n-free expansion o	f your rolling towe	r (for pictures see	page 114 onwards).
Gerüsttyp	Artikel-Nr.	3201	3202	3203	3204	3205	3206	3207
Guardrail 1.80 m	1205.180	0	6	2	6	8	12	10
Double guardrail 1.80 m	1206.180	2	0	2	0	2	0	2
Diagonal brace 2.50 m	1208.180	0	2	2	4	4	6	6
Horizontal diagonal brace 1.95 m	1209.180	0	0	0	1	1	1	1
Mobile beam 1.80 m without bar	1214.180	0	2	2	2	2	2	2
Access deck 1.80 m	1242.180	1	1	1	1	2	2	2
Spring clip	1250.000	0	8	8	12	12	16	16
Ladder frame 75/4 - 1.00 m	1297.004	0	2	0	2	0	2	0
Ladder frame 75/8 - 2.00 m	1297.008	2	2	4	4	6	6	8
Castor 400 - 4 kN	1301.150	4	4	4	4	4	4	4
End toe board 0.75 m	1438.075	0	2	2	2	2	2	2
Toe board 1.80 m with claw	1439.180	0	2	2	2	2	2	2
Ballast	1249.000	For requirement see table below						



The Uni Light family

Tower model	3201 Uni Light	3202 Uni Light	3203 Uni Light
Working height [m]	3.11	4.26	5.26
Tower height [m]	2.34	3.49	4.49
Platform height [m]	1.11	2.26	3.26
Weight [kg] (without ballast)	52.2	110.4	120.6
Ballast (stated in units)			
In closed areas			
Assembly central	14 r4	0	4
Assembly off-set	Х	2	6
Assembly off-set with wall bracing	Х	0	4
Outdoors			
Assembly central	l4 r4	0	4
Assembly off-set	Х	4	8
Assembly off-set with wall bracing	Х	0	4

The products shown (pages 70 and 71) are only standard-compliant by purchasing the retrofit set (page 71) according to DIN EN 1004:2021.

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible/not permissible 0 = no ballast required
 For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
 All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guide!
 Do not use any liquid or granular ballast meterials. The ballast weights must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
 Example: I2, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side. r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).
| Simp | bly safe with the P2 re | etrofit kits: The rollings | can be easily retrofitt | ed to the safety struct | ure P2, to conform to t | the current standa |
|----------|---|---|--|--|--|--|
| Ref. No. | 1400021 | 1400022 | 1400023 | 1400024 | 1400025 | 1400026 |
| | 3202 | 3203 | 3204 | 3205 | 3206 | 3207 |
| 1205.180 | 0 | 3 | 4 | 1 | 2 | 3 |
| 1208.195 | 0 | 2 | 0 | 2 | 0 | 2 |
| 1211.180 | 1 | 1 | 1 | 1 | 1 | 1 |
| 1242.180 | 0 | 1 | 1 | 1 | 1 | 2 |
| 1300.010 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Ref. No. 1205.180 1208.195 1211.180 1242.180 1300.010 | Ref. No. 1400021 3202 3202 1205.180 0 1208.195 0 1211.180 1 1242.180 0 1300.010 1 | Ref. No. 1400021 1400022 3202 3203 1205.180 0 3 1208.195 0 2 1211.180 1 1 1242.180 0 1 | Ref. No. 1400021 1400022 1400023 3202 3203 3204 1205.180 0 3 4 1208.195 0 2 0 1211.180 1 1 1 1242.180 0 1 1 1300.010 1 1 1 | Ref. No. 1400021 1400022 1400023 1400024 3202 3203 3204 3205 1205.180 0 3 4 1 1208.195 0 2 0 2 1211.180 1 1 1 1 1208.010 1 1 1 1 1211.180 1 1 1 1 1200.010 1 1 1 1 | Ref. No. 1400021 1400022 1400023 1400024 1400025 3202 3203 3204 3205 3206 1205.180 0 3 4 1 2 1208.195 0 2 0 2 0 1211.180 1 1 1 1 1 1242.180 0 1 1 1 1 1300.010 1 1 1 1 1 |



1				
ł	5			
t			2	
		Lange State	\leq	
ľ				
[
1	$\langle \rangle$	-	5A	
f	7			
	-	XA		
k	\triangleleft	LX.		
t	\geq	10	\geq	
ŀ	\triangleleft	1		
Į.	-	\sim		
ŀ		\wedge		
ł	-			
ļ.	H		1	
ļ.				
ľ			Z	
ļ.	7		\square	
ł	1	$\mathbf{\nabla}$		
t	-			
	1	6		
L.	\leq			
10		-		M
		39		

3204 Uni Light	3205 Uni Light	3206 Uni Light	3207 Uni Light
6.26	7.26	8.26	9.26
5.49	6.49	7.49	8.49
4.26	5.26	6.26	7.26
138.1	177.1	191.1	205.9
8	12	12	16
10	14	12	16
8	10	12	14
10	14	20	26
12	20	20	26
8	10	12	14

UNI LIGHT STAIR KIT SOLUTION

FOR MORE SAFETY AND FLEXIBILITY



The stair kit for Uni Light permits safer and more flexible use of rolling tower parts in stairwells: it does not require any modification work, since the stair remains accessible despite the scaffolding.

By expanding standard scaffolding models with a few individual components, the stair kit offers in combination with Uni Light an economically smarter, swifter and safer solution for working at heights – also as an alternative to rung ladders, which are now only usable to a limited extent due to current occupational safety regulations. After mounting the base on the stair steps, assembling of the required scaffolding levels can be performed with the already proven Safety Assembly P2.

THE BENEFITS FOR YOU

- Use of rolling tower parts in stairwells up to platform height of 5 m.
- Passageways to suit the site complete blocking off of the stair not needed.
- Adaptation to stair steps riser and tread is possible.
- Passageway also as entrance for upward access.
- Thanks to the modular principle, many assembly variants are possible.

		Uni Light Stair Kit TYPE 1	Uni Light Stair Kit TYPE 2
Tower model	Ref. No.	1603291	1603292
Beam 1.80 m	1207.180	2	2
Diagonal brace 1.95 m	1208.195	2	2
Suspended ladder for passageway ladder frame	1247.006	0	1
Adjustable base plate 60 with lock	1257.060	4	4
Tele distance tube 1.25 m	1275.001	2	2
Passageway ladder frame 75/8 - 2.00 m	1296.008	1	2
Ladder frame 75/2 - 0.50 m	1297.002	1	1
Rubber underlay for base plate	4000.500	4	4
Double coupler	4700.019	4	4
Hand wheel with bush	6491.422	8	8

OPTIONAL

Item description	Ref. No.	Stabilizers kit			
		1600090			
Rotation preventer	1248.261	4			
Alu stabilizer, extendable	1248.260	4			

UNI LIGHT WITH STAIR KIT

THE COMPLETE KITS WITH STAIR SOLUTION

Working height Scaffolding height with spigot		
Tower model	1603293 Uni Light P2	1603295 Uni Light P2
Working height [m]	5.03	7.03
Tower height [m]	4.26	6.26
Platform height [m]	3.03	5.03
Weight [kg] (without ballast)	175.1	223.5
Ballast (stated in units)		
In closed areas		
Assembly central	l6 r6	l12 r12
Structure with restraint between the walls	0	0
Assembly off-set with wall bracing	16 r0	114 rO

Tower model	Ref. No.	1603293	1603295
Guardrail 1.80 m	1205.180	4	8
Beam 1.80 m	1207.180	2	2
Diagonal brace 2.50 m	1208.180	2	4
Diagonal brace 1.95 m	1208.195	2	2
Access deck 1.80 m	1242.180	1	2
Suspended ladder for passageway ladder frame	1247.006	1	1
Telescoping stabilizer - 2.60m	1248.260	4	4
Rotation preventer for stabilizers	1248.261	4	4
Spring clip	1250.000	4	8
Adjustable base plate 60 with lock	1257.060	4	4
Tele distance tube 1.25 m	1275.001	2	2
Passageway ladder frame 75/8 - 2.00 m	1296.008	2	2
Ladder frame 75/4 - 1.00 m	1297.004	1	1
Ladder frame 75/8 - 2.00 m	1297.008	1	3
Uni assembly hook	1300.010	1	1
End toe board 0.75 m	1438.075	2	2
Toe board 1.80 m with claw	1439.180	2	2
Rubber underlay for base plate	4000.500	4	4
Double coupler - AF19	4700.019	4	4
Hand wheel with bush	6491.422	8	8
Ballast	1249.000	For reauirement	see table above

UNI COMPACT

THE COMPACT UNIVERSAL TOWER WITH DOUBLE-WIDTH WORKING SURFACE



The universal tower with double-width working surface yet with compact basic dimensions – offering sufficient room for working at heights, even with materials, yet still leaving plenty of freedom to move.

Ladder frames (1.50 m wide) of aluminium for push-fit assembly; rear guardrails and diagonal braces of aluminium snap in easily.

Work decks with aluminium frame and plywood insert, as a hatch-type deck for risk-free internal access.

Sturdy castors with concentric load transmission after locking for particular stability, long steel spindles for levelling.

Base widening: With mobile beam made of steel, telescoping for work on ceilings or walls to choice, only needed at working heights of 8.38 m and above.

The Uni Compact family can also be equipped with stabilizers. Learn more about that on page 80.

TECHNICAL DATA

- Working height: 10.38 m
- Area of working platform: 1.50 x 1.80 m
- Permissible live load: 2 kN / m² (load class 3)



Uni Compact

Part list		The	Layher modular	system permits	problem-free exp	pansion of your r	olling tower (for	pictures see pag	ge 114 onwards).
Tower model	Ref. No.	1405001	1405002	1405003	1405004	1405005	1405006	1405007	1405008
Guardrail 1.80 m	1205.180	0	6	10	10	14	12	17	16
Double guardrail 1.80 m	1206.180	2	0	0	0	0	0	0	0
Diagonal brace 2.50 m	1208.180	0	2	2	4	4	6	6	8
Diagonal brace 1.95 m	1208.195	0	0	2	0	2	0	2	0
Basic tube 1.80 m	1211.180	0	0	0	0	0	1	1	1
Deck 1.80 m	1241.180	1	2	2	3	3	4	4	5
Access deck 1.80 m	1242.180	1	1	2	2	3	3	4	4
Spring clip	1250.000	0	4	4	8	8	16	16	20
Ladder frame 150/4 - 1.00 m	1299.004	0	2	0	2	0	2	0	2
Ladder frame 150/8 - 2.00 m	1299.008	2	2	4	4	6	6	8	8
Uni assembly hook	1300.010	0	1	1	1	1	1	1	1
Mobile beam 3.20 m with bar adj.	1323.320	0	0	0	0	0	2	2	2
Access ledger 0.75 m	1344.003	0	2	1	2	1	0	0	0
Castor 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4
End toe board 1.44 m	1438.144	2	2	2	2	2	2	2	2
Toe board 1.80 m with claw	1439.180	2	2	2	2	2	2	2	2
Ballast	1249.000				For requirement	t see table belov	V		



The Uni Compact family

Conforms to

Tower model	1405001 Uni Compact P2	1405002 Uni Compact P2	1405003 Uni Compact P2	1405004 Uni Compact P2
Working height [m]	3.20	4.20	5.20	6.20
Tower height [m]	2.43	3.43	4.43	5.43
Platform height [m]	1.20	2.20	3.20	4.20
Weight [kg] (without ballast)	108.3	152.4	191.9	223.9
Ballast (stated in units)				
In closed areas				
Assembly central	0	l1 r1	l1 r1	14 r4
Assembly off-set	Х	Х	Х	Х
Assembly off-set with wall bracing	0	12 r0	12 r0	14 r0
Outdoors				
Assembly central	0	l1 r1	13 r3	17 r7
Assembly off-set	Х	Х	Х	Х
Assembly off-set with wall bracing	0	12 r0	14 r0	110 r4

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guide!
**Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use). Example:
I2, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side. L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side. r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).**

SAFETY ASSEMBLY

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

PZ

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.



1405005 Uni Compact P2	1405006 Uni Compact P2	1405007 Uni Compact P2	1405008 Uni Compact P2
7.20	8.38	9.38	10.38
6.43	7.61	8.61	9.61
5.20	6.38	7.38	8.38
263.4	377.3	442.5	448.8
14 r4	0	0	l1 r1
Х	0	0	l1 r1
14 r0	0	0	l1 r1
l11 r11	l13 r13	l17 r17	Х
Х	l13 r13	l17 r17	Х
114 r4	l13 r13	l17 r17	Х



Uni Compact with stabilizers, extendable

Part list	The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards).					
Tower model	Ref. No.	1405024	1405025	1405026	1405027	1405028
Guardrail 1.80 m	1205.180	10	14	14	18	18
Diagonal brace 2.50 m	1208.180	4	4	6	6	8
Diagonal brace 1.95 m	1208.195	0	2	0	2	0
Deck 1.80 m	1241.180	2	3	3	4	4
Access deck 1.80 m	1242.180	2	3	3	4	4
Telescoping stabilizer - 2.60m	1248.260	4	4	4	4	4
Rotation preventer for stabilizers	1248.261	4	4	4	4	4
Spring clip	1250.000	8	8	12	12	16
Ladder frame 150/4 - 1.00 m	1299.004	2	0	2	0	2
Ladder frame 150/8 - 2.00 m	1299.008	4	6	6	8	8
Uni assembly hook	1300.010	1	1	1	1	1
Access ledger 0.75 m	1344.003	1	1	1	1	1
Castor 700 - 7 kN	1359.200	4	4	4	4	4
End toe board 1.44 m	1438.144	2	2	2	2	2
Toe board 1.80 m with claw	1439.180	2	2	2	2	2
Ballast	1249.000		For r	equirement see table b	elow	



The Uni Compact family with stabilizers

Tower model	1405024 Uni Compact P2 with stabilizers	1405025 Uni Compact P2 with stabilizers
Working height [m]	6.20	7.20
Tower height [m]	5.43	6.43
Platform height [m]	4.20	5.20
Weight [kg] (without ballast)	252.5	308.6
Ballast (stated in units)		
In closed areas		
Assembly central	0	0
Assembly off-set	LO R2	LO R2
Assembly off-set with wall bracing	0	0
Outdoors		
Assembly central	12 r2	14 r4
Assembly off-set	LO R4	LO R6
Assembly off-set with wall bracing	0	0

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guide!
Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
Example: I2, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side.
L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side.
r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).

SAFETY ASSEMBLY

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

PZ

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.



1405026 Uni Compact P2 with stabilizers	1405027 Uni Compact P2 with stabilizers	1405028 Uni Compact P2 with stabilizers
8.20	9.20	10.20
7.43	8.43	9.43
6.20	7.20	8.20
324.0	380.1	395.5
0	0	0
LO R4	LO R4	LO R6
0	0	0
l9 r9	l12 r12	Х
LO R10	L0 R14	Х
0	0	Х



Uni Compact

Part list		The Layh	er modular syste	em permits prob	lem-free expans	ion of your rollir	ng tower (for pic	tures see page	114 onwards).	
Tower model	Ref. No.	5001	5002	5003	5004	5005	5006	5007	5008	
Guardrail 1.80 m	1205.180	0	6	2	6	8	9	9	11	
Double guardrail 1.80 m	1206.180	2	0	2	0	2	0	2	0	
Diagonal brace 2.50 m	1208.180	0	2	2	4	4	6	6	8	
Deck 1.80 m	1241.180	1	1	1	1	2	2	2	2	
Access deck 1.80 m	1242.180	1	1	1	1	2	2	2	2	
Spring clip	1250.000	0	4	4	8	8	16	16	20	
Ladder frame 150/4 - 1.00 m	1299.004	0	2	0	2	0	2	0	2	
Ladder frame 150/8 - 2.00 m	1299.008	2	2	4	4	6	6	8	8	
Mobile beam 3.20 m with bar adj.	1323.320	0	0	0	0	0	2	2	2	
Base strut 1.80 m	1324.180	0	0	0	0	0	1	1	1	
Access ledger 0.75 m	1344.003	0	1	1	1	1	0	0	0	
Castor 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4	
End toe board 1.44 m	1438.144	0	2	2	2	2	2	2	2	
Toe board 1.80 m with claw	1439.180	0	2	2	2	2	2	2	2	
Ballast	1249.000	For requirement see table below								



The Uni Compact family

Tower model	5001 Uni Compact	5002 Uni Compact	5003 Uni Compact	5004 Uni Compact
Working height [m]	3.20	4.20	5.20	6.20
Tower height [m]	2.43	3.43	4.43	5.43
Platform height [m]	1.20	2.20	3.20	4.20
Weight [kg] (without ballast)	92.2	134.6	150.0	168.6
Ballast (stated in units)				
In closed areas				
Assembly central	0	0	4	8
Assembly off-set	Х	Х	Х	Х
Assembly off-set with wall bracing	0	Х	Х	Х
Outdoors				
Assembly central	0	0	6	14
Assembly off-set	Х	Х	Х	Х
Assembly off-set with wall bracing	0	Х	Х	Х

The products shown (pages 82 and 83) are only standard-compliant by purchasing the retrofit set (page 83) according to DIN EN 1004:2021.

The products shown (page 62 and 63) are only standard-compitating of purchasing the retroit set (page 63) according to Div Ex 1004:2021. * Assembly with adjustable mobile beam, which must be fully extended. X = not possible/not permissible 0 = no ballast required For ballasting, use Layher ballast weights, Ref. No. 1249:000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated without any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guide! Do not use any liquid or granular ballast meterials. The ballast weights must be distributed evenly to all ballasting fixing points (see instructions for assembly and use). Example: 12, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side. L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side. r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).

Retrofitting table Simply safe with the P2 retrofit kits: The rollings can be easily retrofitted to the safety structure P2, to conform to the current standards.									
Retrofit set	Ref. No.	1400027	1400028	1400029	1400030	1400031	1400032	1400033	
for tower model		5002	5003	5004	5005	5006	5007	5008	
Guardrail 1.80 m	1205.180	0	4	4	2	3	4	5	
Diagonal brace 1.95 m	1208.195	0	2	0	2	0	2	0	
Deck 1.80 m	1241.180	1	1	2	1	2	2	3	
Access deck 1.80 m	1242.180	0	1	1	1	1	2	2	
Uni assembly hook	1300.010	1	1	1	1	1	1	1	
Access ledger 0.75 m	1344.003	1	0	1	0	0	0	0	

* If there there are already mobile beams 1.80 m (1214.180) and / or double rear guardrails (1206.180) in your inventory, there's no need to replace them. They can still be used.



5005 Uni Compact	5006 Uni Compact	5007 Uni Compact	5008 Uni Compact
7.20	8.38	9.38	10.38
6.43	7.61	8.61	9.61
5.20	6.38	7.38	8.38
226.1	326.1	350.7	364.7
8	0	4	6
Х	0	4	8
Х	0	4	8
20	24	36	Х
Х	24	36	Х
Х	24	36	Х

UNI STANDARD

THE MOST FLEXIBLE ROLLING TOWER FOR VERY GREAT HEIGHTS



For work on walls and ceilings, on machinery, in technical plant, factories and warehouses, indoors and outdoors.

Ladder frames of aluminium for push-fit assembly; rear guardrails and diagonal braces of aluminium snap in easily.

Work decks with aluminium frame and plywood insert, also as a hatch-type deck for risk-free internal access.

Sturdy castors with concentric load transmission after locking for particular stability, long steel spindles for levelling.

Base widening: With mobile beam made of steel, rigid or telescopic, with spigots for optional mounting of ladder frames for work on ceilings and walls; alternatively with stabilizers see page 88.

TECHNICAL DATA

- Working height: 13.38 m
- Area of working platform: 0.75 x 2.85 m
- Permissible live load: 2 kN/m² (load class 3)

Convenient access

For even more safety and even more convenient access, the Uni Standard P2 can also be supplied with suspended ladders with wide steps.

For requirement see page 86.





Uni Standard

Part list		The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards).										
Tower model	Ref. No.	1401101	1401102	1401103	1401104	1401105	1401106	1401107	1401108	1401109	1401110	1401111
Guardrail 2.85 m	1205.285	0	4	9	8	13	12	17	16	21	20	25
Double guardrail 2.85 m	1206.285	2	0	0	0	0	0	0	0	0	0	0
Diagonal brace 3.35 m	1208.285	0	2	2	4	4	6	6	8	8	10	10
Diagonal brace 2.95 m	1208.295	0	0	2	0	2	0	2	0	2	0	2
Basic tube 2.85 m	1211.285	0	1	1	1	1	1	1	1	1	1	1
Deck 2.85 m	1241.285	0	1	0	1	0	1	0	1	0	1	0
Access deck 2.85 m	1242.285	1	1	2	2	3	3	4	4	5	5	6
Spring clip	1250.000	0	8	8	12	12	16	16	20	20	24	24
Ladder frame 75/4 - 1.00 m	1297.004	0	2	0	2	0	2	0	2	0	2	0
Ladder frame 75/8 - 2.00 m	1297.008	2	2	4	4	6	6	8	8	10	10	12
Uni assembly hook	1300.010	0	1	1	1	1	1	1	1	1	1	1
Mobile beam 1.80 m with bar	1323.180	0	2	2	2	2	2	0	0	0	0	0
Mobile beam 3.20 m with bar adj.	1323.320	0	0	0	0	0	0	2	2	2	2	2
Lenkrolle 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4	4	4	4
Stirnbordbrett 0.75 m	1438.075	2	2	2	2	2	2	2	2	2	2	2
Toe board 2.85 m with claw	1439.285	2	2	2	2	2	2	2	2	2	2	2
Ballast	1249.000					For requir	ement see ta	ble below				

Extra requirement for suspended step ladders - usable for safety structure P2

Tower model	Ref. No.	1401101	1401102	1401103	1401104	1401105	1401106	1401107	1401108	1401109	1401110	1401111
Suspended ladder, 8 rungs	1314.108	0	1	1	2	2	3	3	4	4	5	5
Ladder support set for 1314.108	1314.109	0	1	0	1	0	1	0	1	0	1	0



The Uni Standard family

Tower model	1401101 Uni Standard P2	1401102 Uni Standard P2	1401103 Uni Standard P2	1401104 Uni Standard P2	1401105 Uni Standard P2
Working height [m]	3.20	4.35	5.35	6.35	7.35
Tower height [m]	2.43	3.58	4.58	5.58	6.58
Platform height [m]	1.20	2.35	3.35	4.35	5.35
Weight [kg] (without ballast)	96.4	180.2	215.1	242.0	276.9
Ballast (stated in units)					
In closed areas					
Assembly central	l2 r2	0	0	0	0
Assembly off-set	Х	0	0	LO R4	LO R4
Assembly off-set with wall bracing	Х	0	0	0	0
Assembly central with 1 bracket	Х	0	0	LO R2	LO R4
Assembly central with 2 brackets	Х	0	0	0	0
Outdoors					
Assembly central	l2 r2	0	l1 r1	l5 r5	19 r9
Assembly off-set	Х	LO R2	LO R6	L0 R10	L4 R16
Assembly off-set with wall bracing	Х	0	0	0	L4 R0
Assembly central with 1 bracket	Х	LO R4	LO R8	L2 R12	L6 R16
Assembly central with 2 brackets	Х	l2 r2	l5 r5	18 r8	Х

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required
For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guide!
Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
Example: 12, r2 > 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side.
L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side.
r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).

SAFETY ASSEMBLY

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

PZ

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.



1401106 Uni Standard P2	1401107 Uni Standard P2	1401108 Uni Standard P2	1401109 Uni Standard P2	1401110 Uni Standard P2	1401111 Uni Standard P2
8.35	9.38	10.38	11.38	12.38	13.38
7.58	8.61	9.61	10.61	11.61	12.61
6.35	7.38	8.38	9.38	10.38	11.38
303.8	389.9	418.0	452.9	479.8	514.7
0	0	0	0	0	0
LO R6	LO R4	LO R6	LO R6	LO R8	L0 R10
0	0	0	0	0	0
LO R6	0	0	0	0	0
0	0	0	0	0	0
l15 r15	l2 r2	Х	Х	Х	Х
L10 R22	L0 R18	Х	Х	Х	Х
L10 R0	0	Х	Х	Х	Х
L12 R22	Х	Х	Х	Х	Х
Х	Х	Х	Х	Х	Х



Uni Standard with stabilizers

Part list

The Layner modular system permits problem-free expansion of your foiling tower (for pictures see page 114 onwa
--

Tower model	Ref. No.	1401124	1401125	1401126	1401127	1401128	1401129	1401130	1401131	1401145	1401146	1401147	1401148	1401149	1401150	1401151
Guardrail 2.85 m	1205.285	10	14	14	18	18	22	22	26	14	14	18	18	22	22	26
Diagonal brace 3.35 m	1208.285	4	4	6	6	8	8	10	10	4	6	6	8	8	10	10
Diagonal brace 2.95 m	1208.295	0	2	0	2	0	2	0	2	2	0	2	0	2	0	2
Access deck 2.85 m	1242.285	2	3	3	4	4	5	5	6	3	3	4	4	5	5	6
Telescoping stabilizer - 2.60m	1248.260	4	4	4	4	4	4	4	4	0	0	0	0	0	0	0
Rotation preventer for stabilizers	1248.261	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Stabilizer 5 m	1248.500	0	0	0	0	0	0	0	0	4	4	4	4	4	4	4
Spring clip	1250.000	8	8	12	12	16	16	20	20	8	12	12	16	16	20	20
Ladder frame 75/4 - 1.00 m	1297.004	2	0	2	0	2	0	2	0	0	2	0	2	0	2	0
Ladder frame 75/8 - 2.00 m	1297.008	4	6	6	8	8	10	10	12	6	6	8	8	10	10	12
Uni assembly hook	1300.010	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Access ledger 0.30 m	1344.002	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Castor 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
End toe board 0.75 m	1438.075	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Toe board 2.85 m with claw	1439.285	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Ballast	1249 000						For	requiren	nent see	table be	wole					



The Uni Standard family with stabilizers, extendable

Tower model	1401124 Uni Standard P2 with stabilizers	1401125 Uni Standard P2 with stabilizers	1401126 Uni Standard P2 with stabilizers	1401127 Uni Standard P2 with stabilizers
Working height [m]	6.20	7.20	8.20	9.20
Tower height [m]	5.43	6.43	7.43	8.43
Standing height [m]	4.20	5.20	6.20	7.20
Weight [kg] (without ballast)	232.1	283.4	293.9	345.2
Ballast (stated in units)				
In closed areas				
Assembly central	0	0	0	0
Assembly off-set	LO R6	LO R8	L0 12R	L0 R12
Assembly off-set with wall bracing	0	0	0	0
Outdoors				
Assembly central	0	0	0	0
Assembly off-set	L0 R16	L0 R20	L0 R28	L0 R34
Assembly off-set with wall bracing	0	0	0	0

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required
For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guide!
Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
Example: 12, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side
L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side.
r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).

Uni Standard with stabilizers

Tower model	1401145 Uni Standard P2 with stabilizers – 5m	1401146 Uni Standard P2 with stabilizers – 5m	1401147 Uni Standard P2 with stabilizers – 5m	1401148 Uni Standard P2 with stabilizers — 5m	1401149 Uni Standard P2 mit Gerüststützen – 5m	1401150 Uni Standard P2 with stabilizers – 5m	1401151 Uni Standard P2 with stabilizers — 5m
Working height [m]	7.20	8.20	9.20	10.20	11.20	12.20	13.20
Tower height [m]	6.43	7.43	8.43	9.43	10.43	11.43	12.43
Standing height [m]	5.20	6.20	7.20	8.20	9.20	10.20	11.20
Weight [kg] (without ballast)	309.0	319.5	370.8	381.3	432.6	443.1	494.4
Ballast (stated in units)							
In closed areas							
Assembly central	0	0	0	0	0	0	0
Assembly off-set	LO R6	LO R8	LO R8	L0 R10	L0 R12	L0 R14	L0 R14
Assembly off-set with wall bracing	0	0	0	0	0	0	0
Outdoors							
Assembly central	0	0	0	Х	Х	Х	Х
Assembly off-set	LO R16	L0 R20	Х	Х	Х	Х	Х
Assembly off-set with wall bracing	0	0	0	Х	Х	Х	Х



1401128 Uni Standard P2 with stabilizers	1401129 Uni Standard P2 with stabilizers	1401130 Uni Standard P2 with stabilizers	1401131 Uni Standard P2 with stabilizers
10.20	11.20	12.20	13.20
9.43	10.43	11.43	12.43
8.20	9.20	10.20	11.20
355.7	407.0	417.5	216.3
0	0	0	0
LO R16	LO R18	L0 R20	L0 R22
0	0	0	0
Х	Х	Х	Х
Х	Х	Х	Х
Х	Х	Х	Х

Uni Standard

Part list		The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards).										
Tower model	Ref. No.	1101	1102	1103	1104	1105	1106	1107	1108	1109	1110	1111
Guardrail 2.85 m	1205.285	0	5	1	5	7	9	9	11	13	15	15
Double guardrail 2.85 m	1206.285	2	0	2	0	2	0	2	0	2	0	2
Diagonal brace 3.35 m	1208.285	0	2	2	4	4	6	6	8	8	10	10
End toe board 0.75 m	1242.285	1	1	1	1	2	2	2	2	3	3	3
Spring clip	1250.000	0	8	8	12	12	16	16	20	20	24	24
Ladder frame 75/4 - 1.00 m	1297.004	0	2	0	2	0	2	0	2	0	2	0
Ladder frame 75/8 - 2.00 m	1297.008	2	2	4	4	6	6	8	8	10	10	12
Mobile beam 1.80 m with bar	1323.180	0	2	2	2	2	2	0	0	0	0	0
Mobile beam 3.20 m with bar adj.	1323.320	0	0	0	0	0	0	2	2	2	2	2
Base strut 2.85 m	1324.285	0	1	1	1	1	1	1	1	1	1	1
Castor 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4	4	4	4
End toe board 0.75 m	1438.075	0	2	2	2	2	2	2	2	2	2	2
Toe board 2.85 m with claw	1439.285	0	2	2	2	2	2	2	2	2	2	2
Ballast	1249.000					For require	ement see t	able below				



Tower model	1101 Uni Standard	1102 Uni Standard	1103 Uni Standard	1104 Uni Standard	1105 Uni Standard
Working height [m]	3.20	4.35	5.35	6.35	7.35
Tower height [m]	2.43	3.58	4.58	5.58	6.58
Platform height [m]	1.20	2.35	3.35	4.35	5.35
Weight [kg] (without ballast)	81.8	161.0	170.4	186.8	239.4
Ballast (stated in units)					
In closed areas					
Assembly central	l2 r2	0	0	0	0
Assembly off-set	Х	0	10 r2	10 r4	10 r5
Assembly off-set with wall bracing	Х	0	0	0	0
Assembly central with 1 bracket	Х	0	LO R8	LO R4	LO R4
Assembly central with 2 brackets	Х	0	0	0	0
Outdoors					
Assembly central	l2 r2	0	10 r1	14 r4	19 r9
Assembly off-set	Х	0	10 r5	10 r9	l2 r14
Assembly off-set with wall bracing	Х	0	0	0	12 r0
Assembly central with 1 bracket	Х	LO R4	LO R8	L2 R12	L6 R16
Assembly central with 2 brackets	Х	Х	Х	Х	Х

The products shown (pages 90 and 91) are only standard-compliant by purchasing the retrofit set (page 91) according to DIN EN 1004:2021.

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required
For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guide!
**Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
Example: I2, r2 > 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side.
L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weight so f10 kg each to its right-hand side.
r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).**

Retrofitting table	Simply safe with the P2 retrofit kits: The rollings can be easily retrofitted to the safety structure P2, to conform to the current standards.										
Retrofit set	Ref. No.	1400001	1400002	1400003	1400004	1400005	1400006	1400007	1400008	1400009	1400010
for tower model		1102	1103	1104	1105	1106	1107	1108	1109	1110	1111
Guardrail 2.85 m	1205.285	0	4	3	2	3	4	5	4	5	6
Diagonal brace 2.95 m	1208.295	0	2	0	2	0	2	0	2	0	2
Deck 2.85 m	1241.285	1	0	1	0	1	0	1	0	1	0
Access deck 2.85 m	1242.285	0	1	1	1	1	2	2	2	2	3
Uni assembly hook	1300.010	1	1	1	1	1	1	1	1	1	1
* If there there are already mobile be	eams 1.80 m (121	4.180) and/or do	ouble rear guardra	ils (1206.180) in	your inventory, th	nere's no need to	replace them. Th	ey can still be us	ed.		



1106 Uni Standard	1107 Uni Standard	1108 Uni Standard	1109 Uni Standard	1110 Uni Standard	1111 Uni Standard
8.35	9.38	10.38	11.38	12.38	13.38
7.58	8.61	9.61	10.61	11.61	12.61
6.35	7.38	8.38	9.38	10.38	11.38
248.6	323.6	332.8	385.4	394.6	418.4
12 r2	0	0	0	0	0
10 r8	LO R6	LO R8	LO R9	L0 R10	L0 R12
0	0	0	0	0	0
LO R8	0	0	0	0	0
l2 r2	0	0	0	Х	Х
l12 r13	L1 R1	Х	Х	Х	Х
l6 r18	L0 R17	Х	Х	Х	Х
16 r0	L1 R0	Х	Х	Х	Х
L10 R20	0	0	0	Х	Х
Х	Х	Х	Х	Х	Х

UNI STANDARD STAIR KIT SOLUTION

FOR MORE SAFETY AND FLEXIBILITY



The stair kit for Uni Standard permits safer and more flexible use of rolling tower parts in stairwells: it does not require any modification work, since the stair remains accessible despite the scaffolding.

By expanding standard scaffolding models with a few individual components, the stair kit offers in combination with Uni Standard an economically smarter, swifter and safer solution for working at heights – also as an alternative to rung ladders, which are now only usable to a limited extent due to current occupational safety regulations. After mounting the base on the stair steps, assembling of the required scaffolding levels can be performed with the already proven Safety Assembly P2.

THE BENEFITS FOR YOU

- Use of rolling tower parts in stairwells up to platform height of 6 m.
- Passageways to suit the site complete blocking off of the stair not needed.
- Adaptation to stair steps riser and tread is possible.
- > Passageway also as entrance for upward access.
- > Thanks to the modular principle, many assembly variants are possible.

		Uni Standard Stair Kit TYPE 1	Uni Standard Stair Kit TYPE 2
Tower model	Ref. No.	1601191	1601192
Beam 2.85 m	1207.285	2	2
Diagonal brace 2.95 m	1208.295	2	2
Suspended ladder for passageway ladder frame	1247.006	0	1
Adjustable base plate 60 with lock	1257.060	4	4
Tele distance tube 1.25 m	1275.001	2	2
Passageway ladder frame 75/8 - 2.00 m	1296.008	1	2
Ladder frame 75/2 - 0.50 m	1297.002	1	1
Rubber underlay for base plate	4000.500	4	4
Double coupler	4700.019	4	4
Hand wheel with bush	6491.422	8	8

OPTIONAL

Item description	Ref. No.	Stabilizers kit
		1600090
Rotation preventer	1248.261	4
Alu stabilizer, extendable	1248.260	4

UNI STANDARD WITH STAIR KIT

THE COMPLETE KITS WITH STAIR SOLUTION



Tower model	1601193 Uni Standard P2	1601195 Uni Standard P2
Working height [m]	5.73	7.73
Tower height [m]	4.96	6.96
Platform height [m]	3.73	5.73
Weight [kg] (without ballast)	199.8	261.6
Ballast (stated in units)		
In closed areas		
Assembly central	l6 r6	l10 r10
Structure with restraint between the walls	0	0
Assembly off-set with wall bracing	16 r0	112 r0

Tower model	Ref. No.	1601193	1601195
Guardrail 2.85 m	1205.285	4	8
Beam 2.85 m	1207.285	2	2
Diagonal brace 3.35 m	1208.285	2	4
Diagonal brace 2.95 m	1208.295	2	2
Access deck 2.85 m	1242.285	1	2
Suspended ladder for passageway ladder frame	1247.006	1	1
Telescoping stabilizer - 2.60m	1248.260	4	4
Rotation preventer for stabilizers	1248.261	4	4
Spring clip	1250.000	6	10
Adjustable base plate 60 with lock	1257.060	4	4
Tele distance tube 1.25 m	1275.001	2	2
Passageway ladder frame 75/8 - 2.00 m	1296.008	2	2
Ladder frame 75/2 - 0.50 m	1297.002	1	1
Ladder frame 75/4 - 1.00 m	1297.004	1	1
Ladder frame 75/8 - 2.00 m	1297.008	1	3
Uni assembly hook	1300.010	1	1
End toe board 0.75 m	1438.075	2	2
Toe board 2.85 m with claw	1439.285	2	2
Rubber underlay for base plate	4000.500	4	4
Double coupler - AF19	4700.019	4	4
Hand wheel with bush	6491.422	8	8
Ballast	1249.000	For requirement	see table above

UNI WIDE

THE UNIVERSAL TOWER WITH DOUBLE-WIDTH WORKING SURFACE



The universal tower with double-width working surface provides a comfortable workplace at great heights.

Ideal for working with bulky materials while assuring the necessary freedom of movement.

Ladder frames (1.50 m wide) of aluminium for push-fit assembly; rear guard-rails and diagonal braces of aluminium snap in easily.

Work decks with aluminium frame and plywood insert, as a hatch-type deck for risk-free internal access.

Sturdy castors with concentric load transmission after locking for particular stability, long steel spindles for levelling.

Base widening: With mobile beam made of steel, telescopic for work on ceilings and walls if required; only necessary for working height of 8.60 m and above, alternatively with stabilizers (see page 98 in this respect and also instructions for assembly and use).

TECHNICAL DATA

- Working height: 13.38 m
- Area of working platform: 1.50 x 2.85 m
- Permissible live load: 2 kN / m² (load class 3)

Convenient access

For even more safety and even more convenient access, the Uni Wide P2 can also be supplied with suspended ladders with wide steps.

For requirement see page 96.





Uni Wide

Part list			The Layhe	er modular s	system perm	its problem-	free expansi	on of your ro	olling tower	for pictures	see page 11	4 onwards).
Tower model	Ref. No.	1402101	1402102	1402103	1402104	1402105	1402106	1402107	1402108	1402109	1402110	1402111
Guardrail 2.85 m	1205.285	0	6	10	10	14	12	17	16	21	20	25
Double guardrail 2.85 m	1206.285	2	0	0	0	0	0	0	0	0	0	0
Diagonal brace 3.35 m	1208.285	0	2	2	4	4	6	6	8	8	10	10
Diagonal brace 2.95 m	1208.295	0	0	2	0	2	0	2	0	2	0	2
Basic tube 2.85 m	1211.285	0	0	0	0	0	1	1	1	1	1	1
Deck 2.85 m	1241.285	1	2	2	3	3	4	4	5	5	6	6
Access deck 2.85 m	1242.285	1	1	2	2	3	3	4	4	5	5	6
Spring clip	1250.000	0	4	4	8	8	16	16	20	20	24	24
Ladder frame 150/4 - 1.00 m	1299.004	0	2	0	2	0	2	0	2	0	2	0
Ladder frame 150/8 - 2.00 m	1299.008	2	2	4	4	6	6	8	8	10	10	12
Uni assembly hook	1300.010	0	1	1	1	1	1	1	1	1	1	1
Mobile beam 3.20 m with bar adj.	1323.320	0	0	0	0	0	2	2	2	2	2	2
Access ledger 0.75 m	1344.003	0	2	1	2	1	0	0	0	0	0	0
Castor 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4	4	4	4
End toe board 1.44 m	1438.144	2	2	2	2	2	2	2	2	2	2	2
Toe board 2.85 m with claw	1439.285	2	2	2	2	2	2	2	2	2	2	2
Ballast	1249.000					For require	ement see ta	able below				

Extra requirement for suspended step ladders - usable for safety structure P2

Tower model	Ref. No.	1402101	1402102	1402103	1402104	1402105	1402106	1402107	1402108	1402109	1402110	1402111
Suspended step ladder, 8 rungs	1314.108	0	1	1	2	2	3	3	4	4	5	5
Ladder support set for 1314 108	1314 109	0	0	0	0	Ο	1	Ο	1	0	1	0



The Uni Wide family

Tower model	1402101 Uni Wide P2	1402102 Uni Wide P2	1402103 Uni Wide P2	1402104 Uni Wide P2	1402105 Uni Wide P2
Working height [m]	3.20	4.20	5.20	6.20	7.20
Tower height [m]	2.43	3.43	4.43	5.43	6.43
Platform height [m]	1.20	2.20	3.20	4.20	5.20
Weight [kg] (without ballast)	128.8	184.6	237.8	276.2	329.4
Ballast (stated in units)					
In closed areas					
Assembly central	0	0	0	l1 r1	l1 r1
Assembly off-set	Х	Х	Х	Х	Х
Assembly off-set with wall bracing	Х	Х	Х	Х	Х
Assembly central with 1 bracket	Х	10 r10	10 r10	l0 r12	10 r12
Assembly central with 2 brackets	Х	l3 r3	l2 r2	l5 r5	14 r4
Outdoors					
Assembly central	0	l3 r3	l6 r6	l11 r11	l16 r16
Assembly off-set	Х	Х	Х	Х	Х
Assembly off-set with wall bracing	Х	Х	Х	Х	Х
Assembly central with 1 bracket	Х	10 r18	10 r22	l6 r28	Х
Assembly central with 2 brackets	Х	114 r14	l16 r16	Х	Х

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required
For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guide!
Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
Example: 12, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side.
L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side.
r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).

SAFETY ASSEMBLY

- Conforms to standard DIN EN 1004:2021
- Platform in vertical spacing of 2 m
- Collective side protection
- Quick and easy assembly

RETROFITTABLE USING THE LAYHER MODULAR SYSTEM

PZ

If you already possess a Layher Rolling Tower, then you can convert it into the P2 variant without difficulty.



1402106 Uni Wide P2	1402107 Uni Wide P2	1402108 Uni Wide P2	1402109 Uni Wide P2	1402110 Uni Wide P2	1402111 Uni Wide P2
8.38	9.38	10.38	11.38	12.38	13.38
7.61	8.61	9.61	10.61	11.61	12.61
6.38	7.38	8.38	9.38	10.38	11.38
329.4	511.7	543.2	603.3	634.8	694.9
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	Х
0	0	Х	Х	Х	Х
0	0	Х	Х	Х	Х
LO R8	L0 R12	Х	Х	Х	Х
0	0	Х	Х	Х	Х
Х	Х	Х	Х	Х	Х
Х	Х	Х	Х	Х	Х



Uni Wide with stabilizers

Part list		Th	ie Layher m	nodular sys	tem permi	ts problem	-free expar	nsion of yo	ur rolling t	ower (for p	ictures see	e page 114	onwards).
Tower model	Ref. No.	1402126	1402127	1402128	1402129	1402130	1402131	1402146	1402147	1402148	1402149	1402150	1402151
Guardrail 2.85 m	1205.285	14	18	18	22	22	26	14	18	18	22	22	26
Diagonal brace 3.35 m	1208.285	6	6	8	8	10	10	6	6	8	8	10	10
Diagonal brace 2.95 m	1208.295	0	2	0	2	0	2	0	2	0	2	0	2
Deck 2.85 m	1241.285	3	4	4	5	5	6	3	4	4	5	5	6
Access deck 2.85 m	1242.285	3	4	4	5	5	6	3	4	4	5	5	6
Telescoping stabilizer - 2.60m	1248.260	4	4	4	4	4	4	0	0	0	0	0	0
Rotation preventer for stabilizers	1248.261	4	4	4	4	4	4	4	4	4	4	4	4
Stabilizer 5 m	1248.500	0	0	0	0	0	0	4	4	4	4	4	4
Spring clip	1250.000	12	12	16	16	20	20	12	12	16	16	20	20
Ladder frame 150/4 - 1.00 m	1299.004	2	0	2	0	2	0	2	0	2	0	2	0
Ladder frame 150/8 - 2.00 m	1299.008	6	8	8	10	10	12	6	8	8	10	10	12
Uni assembly hook	1300.010	1	1	1	1	1	1	1	1	1	1	1	1
Access ledger 0.75 m	1344.003	1	1	1	1	1	1	1	1	1	1	1	1
Castor 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4	4	4	4	4
End toe board 1.44 m	1438.144	2	2	2	2	2	2	2	2	2	2	2	2
Toe board 2.85 m with claw	1439.285	2	2	2	2	2	2	2	2	2	2	2	2
Ballast	1249.000					For re	quirement	see table	below				



Tower model	1402126 Uni Wide P2 with stabilizers	1402127 Uni Wide P2 with stabilizers	1402128 Uni Wide P2 with stabilizers
Working height [m]	8.20	9.20	10.20
Tower height [m]	7.43	8.43	9.43
Standing height [m]	6.20	7.20	8.20
Weight [kg] (without ballast)	389.7	466.2	481.3
Ballast (stated in units)			
In closed areas			
Assembly central	0	0	0
Assembly off-set	LO R2	LO R2	LO R2
Assembly off-set with wall bracing	0	0	0
Outdoors			
Assembly central	0	0	Х
Assembly off-set	L0 R14	L0 R18	Х
Assembly off-set with wall bracing	0	0	Х

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible / not permissible 0 = no ballast required For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assemby variant is listed in its assembly instruction guide!
**Do not use any liquid or granular ballast materials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use). Example:
I2, r2 → 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side. L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side. r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).**

Uni Wide with stabilizers

Tower model	1402146 Uni Wide P2 with stabilizers – 5m	1402147 Uni Wide P2 with stabilizers – 5m	1402148 Uni Wide P2 with stabilizers – 5m	1402149 Uni Wide P2 with stabilizers – 5m	1402150 Uni Wide P2 with stabilizers – 5m	1402151 Uni Wide P2 with stabilizers – 5m
Marking bailet [m]	0.20	0.20	10.20	11.00	10.00	10.00
vvorking neight [m]	8.20	9.20	10.20	11.20	12.20	13.20
Tower height [m]	7.43	8.43	9.43	10.43	11.43	12.43
Standing height [m]	6.20	7.20	8.20	9.20	10.20	11.20
Weight [kg] (without ballast)	415.3	491.8	506.9	583.4	598.5	675.0
Ballast (stated in units)						
In closed areas						
Assembly central	0	0	0	0	0	0
Assembly off-set	0	0	LO R2	LO R2	LO R2	LO R2
Assembly off-set with wall bracing	0	0	0	0	0	0
Outdoors						
Assembly central	0	0	Х	Х	Х	Х
Assembly off-set	L0 R10	L0 R12	Х	Х	Х	Х
Assembly off-set with wall bracing	0	0	Х	Х	Х	Х



1402129 Uni Wide P2 with stabilizers	⁷ 1402130 Uni Wide P2 with stabilizers	1402131 Uni Wide P2 with stabilizers
11.20	12.20	13.20
10.43	11.43	12.43
9.20	10.20	11.20
557.8	572.9	649.4
0	0	0
LO R2	LO R4	LO R4
0	0	0
Х	Х	Х
Х	Х	Х
Х	Х	Х

Uni Wide

Part list		The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwa						14 onwards				
Tower model	Ref. No.	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111
Guardrail 2.85 m	1205.285	0	6	2	6	8	9	9	11	13	15	15
Double guardrail 2.85 m	1206.285	2	0	2	0	2	0	2	0	2	0	2
Diagonal brace 3.35 m	1208.285	0	2	2	4	4	6	6	8	8	10	10
Deck 2.85 m	1241.285	1	1	1	1	2	2	2	2	3	3	3
Access deck 2.85 m	1242.285	1	1	1	1	2	2	2	2	3	3	3
Spring clip	1250.000	0	4	4	8	8	16	16	20	20	24	24
Ladder frame 150/4 - 1.00 m	1299.004	0	2	0	2	0	2	0	2	0	2	0
Ladder frame 150/8 - 2.00 m	1299.008	2	2	4	4	6	6	8	8	10	10	12
Mobile beam 3.20 m with bar adj.	1323.320	0	0	0	0	0	2	2	2	2	2	2
Base strut 2.85 m	1324.285	0	0	0	0	0	1	1	1	1	1	1
Access ledger 0.75 m	1344.003	0	1	1	1	1	0	0	0	0	0	0
Castor 700 - 7 kN	1359.200	4	4	4	4	4	4	4	4	4	4	4
End toe board 1.44 m	1438.144	0	2	2	2	2	2	2	2	2	2	2
Toe board 2.85 m with claw	1439.285	0	2	2	2	2	2	2	2	2	2	2
Ballast	1249 000					For requir	ement see t	ahle helow				



Tower model	2101 Uni Wide	2102 Uni Wide	2103 Uni Wide	2104 Uni Wide	2105 Uni Wide
Working height [m]	3.20	4.20	5.20	6.20	7.20
Tower height [m]	2.43	3.43	4.43	5.43	6.43
Standing height [m]	1.20	2.20	3.20	4.20	5.20
Weight [kg] (without ballast)	111.6	162.6	177.2	198.2	276.0
Ballast (stated in units)					
In closed areas					
Assembly central	0	0	l2 r2	14 r4	4 r4
Assembly off-set	0	0	l2 r2	14 r4	4 r4
Assembly off-set with wall bracing	0	0	12 r0	14 r0	14 r0
Assembly central with 1 bracket	Х	10 r8	10 r12	10 r14	10 r14
Assembly central with 2 brackets	Х	l3 r3	l16 r16	18 r8	17 r7
Outdoors					
Assembly central	0	l3 r3	l6 r6	l11 r11	116 r16
Assembly off-set	Х	Х	Х	Х	Х
Assembly off-set with wall bracing	Х	Х	Х	Х	Х
Assembly central with 1 bracket	Х	10 r18	l2 r22	l6 r26	112 r30
Assembly central with 2 brackets	Х	110 r10	Х	Х	Х

The products shown (pages 100 and 101) are only standard-compliant by purchasing the retrofit set (page 101) according to DIN EN 1004:2021.

* Assembly with adjustable mobile beam, which must be fully extended. X = not possible/not permissible 0 = no ballast required
For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler.
All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guide!
**Do not use any liquid or granular ballast meterials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use).
Example: I2, r2 > 2 ballast weights of 10 kg each must be fastened to the left-hand side of the ladder frame, and 2 ballast weights of 10 kg each to its right-hand side.
L6, R16 → 6 ballast weights of 10 kg each must be fastened to the left-hand side of the mobile beam, and 16 ballast weights of 10 kg each to its right-hand side.
r and R always relate, in the case of off-centre assembly, to that side facing away from the scaffolding; I and L relate to the side facing the scaffolding (see instructions for assembly and use).**

Retrofitting table		Simply safe with the P2 retrofit kits: The rollings can be easily retrofitted to the safety structure P2, to conform to the current standards.										
Retrofit set	Ref. No.	1400039	1400011	1400012	1400013	1400014	1400015	1400016	1400017	1400018	1400019	1400020
for tower model		2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111
Guardrail 2.85 m	1205.285	0	0	4	4	2	3	4	5	4	5	6
Diagonal brace 2.95 m	1208.295	0	0	2	0	2	0	2	0	2	0	2
Deck 2.85 m	1241.285	0	1	1	2	1	2	2	3	2	3	3
Access deck 2.85 m	1242.285	0	0	1	1	1	1	2	2	2	2	3
Uni assembly hook	1300.010	0	1	1	1	1	1	1	1	1	1	1
Access ledger 0.75 m	1344.003	0	1	0	1	0	0	0	0	0	0	0
End toe board 1.44 m	1438.144	2	0	0	0	0	0	0	0	0	0	0
Toe board 2.85 m with claw	1439.285	2	0	0	0	0	0	0	0	0	0	0
* If there is already a base strut (132	4.285) and / or dr	ouble rear guard	rails (1206.285)	in your inventory	/, there's no nee	ed to replace the	m. They can still	be used.				



2106 Uni Wide	2107 Uni Wide	2108 Uni Wide	2109 Uni Wide	2110 Uni Wide	2111 Uni Wide
8.38	9.38	10.38	11.38	12.38	13.38
7.61	8.61	9.61	10.61	11.61	12.61
6.38	7.38	8.38	9.38	10.38	11.38
377.6	406.6	420.4	498.2	512.0	541.0
0	0	0	0	0	0
0	0	0	0	LO R2	LO R2
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	Х	Х	Х
L1 R1	L5 R5	Х	Х	Х	Х
LO R6	L4 R14	Х	Х	Х	Х
L2 R0	L8 R2	Х	Х	Х	Х
LO R6	Х	Х	Х	Х	Х
Х	Х	Х	Х	Х	Х

UNI COMFORT THE UNIVERSAL TOWER WITH CONVENIENT STAIRWAY ACCESS



The Uni Comfort tower is the compact tower, ideally suited to assembly and maintenance work etc.

The convenient stairway access with full-length handrail facilitates frequent ascent and descent, easily overcomes great heights and leaves the hands free to carry tools and material.

Ladder frames (1.50 m wide) of aluminium for push-fit assembly; rear guardrails and diagonal braces of aluminium snap in easily.

Work decks with aluminium frame and plywood insert, as a hatch-type deck opening over the entire length for convenient internal access.

Sturdy castors with concentric load transmission after locking for particular stability, long steel spindles for levelling.

Outriggers for base widening can be attached without using tools; fitting them with castors permits safer movement of the tower without dismantling it.

TECHNCAL DATA

- Working height: 14.20 m
- Area of working platform: 1.50 x 1.80 m
- Permissible live load: 2 kN / m² (load class 3)



Uni Comfort

Part list		The Layher modular system permits problem-free expansion of your rolling tower (for pictures see page 114 onwards						
Tower model	Ref. No.	4201	4202	4203	4204	4205	4206	
Guardrail 1.80 m	1205.180	5	8	11	14	17	20	
Diagonal brace 2.50 m	1208.180	1	2	3	4	5	6	
Horizontal diagonal brace 2.95 m	1209.285	0	0	2	2	2	2	
Landing stairway 1.80 m	1212.180	1	2	3	4	5	6	
Stairway guardrail 3.07 m	1213.180	0	1	2	3	4	5	
Outrigger 1.50 m	1216.000	0	0	4	4	4	4	
Deck 1.80 m	1241.180	2	3	4	5	6	7	
Stairway access deck 1.80 m	1243.180	1	1	1	1	1	1	
Spring clip	1250.000	4	8	12	16	20	24	
Ladder frame 150/4 - 1.00 m	1299.004	2	2	2	2	2	2	
Ladder frame 150/8 - 2.00 m	1299.008	2	4	6	8	10	12	
Uni assembly hook	1300.010	1	1	1	1	1	1	
Horizontal diagonal brace, adj.	1318.000	0	0	2	2	2	2	
Base strut 1.80 m	1324.180	1	1	1	1	1	1	
Stairway guardrail 1.20 m	1327.120	1	1	1	1	1	1	
Access ledger 0.75 m	1344.003	2	2	2	2	2	2	
Castor 700 - 7 kN	1359.200	4	4	8	8	8	8	
End toe board 1.44 m	1438.144	2	2	2	2	2	2	
Toe board 1.80 m with claw	1439.180	2	2	2	2	2	2	
Ballast	1249.000			For requiremen	t see table below			

Conforms to contorms to standard DIN EN 1004:2021 Working height Scaffolding height with spigot Platform height

The Uni Comfort family







4201 Uni Comfort	4202 Uni Comfort
4.20	6.20
3.43	5.43
2.20	4.20
167.7	237.9
0	6
Δ	Δ
Δ	Δ
Δ	Δ
2	16
Δ	Δ
Δ	Δ
Δ	Δ
	4201 Uni Comfort 4.20 3.43 2.20 167.7 0 Δ Δ Δ Δ Δ Δ Δ Δ

 $X = not possible / not permissible 0 = no ballast required \Delta = Erection with additional parts, only possible after consulting the manufacturer. For ballasting, use Layher ballast weights, Ref. No. 1249.000, 10 kg each. These weights are attached quickly and securely at the right places using the star handle coupler. All height dimensions are calculated <u>without</u> any spindle travel. The maximum spindle travel of each assembly variant is listed in its assembly instruction guidel$ **Do not use any liquid or granular ballast meterials. The ballast weight must be distributed evenly to all ballasting fixing points (see instructions for assembly and use). In central assembly, the ballast weights are distributed evenly over all four ladder frame standards. The remainder not divisible by 4 must be fitted in accordance with the instructions for assembly and use. In off-set assembly on mobile beams, the ballast weights must be distributed evenly over the two ladder frame standards area standards area frame standards.**



4203 Uni Comfort	4204 Uni Comfort	4205 Uni Comfort	4206 Uni Comfort
8.20	10.20	12.20	14.20
7.43	9.43	11.43	13.43
6.20	8.20	10.20	12.20
389.5	459.7	529.9	600.1
Х	Х	Х	Х
0	0	0	0
2	4	6	8
0	0	0	0
Х	Х	Х	Х
0	0	Х	Х
20	Х	Х	Х
0	4	Х	Х

STARO ROLLING TOWER

THE READY-MADE TOWER FOR FREEDOM OF MOVEMENT AND A LARGE WORKING AREA





The Staro rolling tower is the "ready-made" tower with a large work surface. It is indispensable for fast work on large ceiling surfaces or for assembling components or installation work underneath the ceiling. The large work surface offers ample freedom of movement and space for storing tools and materials ready to hand.



Basic assembly in aluminium; rear guardrails are easily snapped in.

Work decks with aluminium frame and plywood insert.



Sturdy castors (d=150 mm) with concentric load transmission after locking, for particular stability. Leg tube (1.95 m long) with holes 11 cm apart for height adjustment.

TECHNICAL DATA

- Working height: 3.75 m
- Area of working platform: 1.95 x 1.95 m
- Permissible live load: 1.5 kN/m² (load class 2)



Type 7000

Part list				
Tower model	Ref. No.	7000	7001	
Staro basic tower 1.90m x 1.95 m	1224.000	1	1	
Intermediate guardrail 1.90 m	1224.190	0	2	
Staro guardrail 1.90 m	1227.190	2	4	
End toe board 1.90 m	1238.190	0	2	
Toe board 1.95 m with claw	1239.195	0	2	
Staro deck 1.90 m	1241.190	3	3	
Ladder for Staro rolling tower	1246.006	0	1	



132.5

Tower model	7000	7001
Working height [m]	2.80 - 3.75*	2.80 - 3.75
Tower heigth [m]	1.89 - 2.63*	1.89 - 2.63
Standing height [m]	0.80 - 1.75*	0.80 - 1.75

99.9

* from platform height of 1 m, the additional equipment is required.

The product shown, type 7000, is only in conformity with standards when using the additional equipment (intermediate guardrail 1.90 m = 2 x 1224.190, Staro guardrail = 2 x 1227.190), toe boards = 2 x 1438.190, 2 x 1439.195 and ladder for Staro rolling tower = 1246.006). The scaffolding may only be accessed via the ladder (1246.006).

Includes the additional equipment

Weight [kg]

ALU BRIDGING BEAM THE WORKING DECK UP TO 10 M LONG



TECHNICAL DATA

- Conforms to DIN EN 12811-1
- Permissible load class 2 (1.5 kN/m² up to 10 m length)
- Permissible load class 3 (2 kN / m² up to 7.10 m length)
The Alu bridging beam 600 is a quick and handy component. Lightweight, as it's made of aluminium, and stable, as it's made from special sections. It is possible to attach, depending on the application, a three-piece side protection to the Alu bridging beam. The Alu bridging beam 600, folding, can also be used in load class 2. A folding device allows it to be folded up into handy transport dimensions.





1331.000 clamp see page 123.

Description	Min. Length [m]	Max. Length [m]	Load [kN / m²]	Width [m]	Outer width [mm]	Height [m]	Height folded [m]	Weight [kg]	Ref. No.	Ref. No. side protection
	3.18	-	2.0	0.60	-	0.09	-	20.0	1348.318	6201
	4.12	-	2.0	0.60	-	0.09	-	26.0	1348.412	6202
	4.74	-	2.0	0.60	-	0.09	-	29.0	1348.475	6203
	5.21	-	2.0	0.60	-	0.12	-	38.0	1348.520	6204
Alu bridging	6.15	-	2.0	0.60	-	0.12	-	45.0	1348.615	6205
	7.08	-	2.0	0.60	-	0.12	-	52.0	1348.710	6206
	8.02	-	1.5	0.60	-	0.15	-	68.0	1348.800	6207
	9.11	-	1.5	0.60	-	0.15	-	76.0	1348.910	6208
	10.05	-	1.5	0.60	-	0.15	-	85.0	1348.100	6209
Alu bridging	2.60	5.16	1.5	0.60	0.75	0.12	0.38	47.0	1349.510	6210
beam 600,	3.70	7.36	1.5	0.60	0.75	0.12	0.38	61.0	1349.730	6211
folding	4.60	9.16	1.5	0.60	0.75	0.15	0.44	86.0	1349.915	6212







Side protection for Alu bridging beam 600 | Part list

KIT-No.	Ref. No.	6201	6202	6203	6204	6205	6206	6207	6208	6209	6210	6211	6212
Guardrail fixture	1330.000	2	4	4	4	4	6	6	6	8	4	4	8
Double guardrail	1332.200	0	2	1	1	0	2	1	0	2	2	0	4
Double guardrail	1332.300	1	0	1	1	2	1	2	3	2	0	2	0
Guardrail locking clip	1333.000	1	2	2	2	2	3	3	3	4	2	2	4

Alu telescopic stage 1351

The Alu telescopic stage offers a wide and variable range of possible applications. For transport, the telescopic stage can be simply pushed together, resulting in low transport dimensions. Since the Alu telescopic stage is extendable, it can be pulled out or pushed together to provide any required length.

Loading capacity: 150 kg

Max. Length [m]	Min. Length [m]	Weight approx. [kg]	Ref. No.
2.9	1.64	13.0	1351.290
3.5	1.92	16.0	1351.350
4	2.27	18.0	1351.400
4.4	2.49	20.0	1351.440

BRACKET DECK SURFACES

WORKING SERVICE WIDENING FOR UNI STANDARD AND UNI WIDE



Special designs are individualized tower structures that make work safer and faster at many construction sites.

The examples on this page show the widening of the top scaffolding level and the formation of several working levels using console brackets. For these tower forms, we have acquired the GS safety inspection certificate that is sufficient for the use of the tower and eliminates the need for structural strength verification otherwise required.

TECHNICAL DATA

- Subsequent attachment to completed towers is possible
- Rapid and easy widening of the working surface of up to 1.50 m
- Permissible live load: 1.5 kN / m² (load class 2)

Extension-KITS for attachment of 1 or 2 bracket deck surfaces for Uni Standard and Uni Wide

KIT-No.	Ref. No.	9100	9200
Guardrail 2.85 m	1205.285	2	2
Deck 2.85 m	1241.285	1	2
Spring clip	1250.000	4	8
Ladder frame 75/4 - 1.00 m	1297.004	2	4
Intermediate deck 2.85 m	1339.285	1	2
Alu console bracket 0.75 m	1341.075	2	4
End toe board 0.75 m	1438.075	2	4

The number of ballast weights required is stated in the appropriate instructions for assembly and use. All dimensions and weights are guideline values. Subject to technical modification. Our deliveries shall be made exclusively in accordance with our currently

valid General Terms of Sale. Title to the delivered goods shall be retained until full payment has been made. When purchasing, you receive instructions for assembly and use that must be followed without fail or assembly, dismantling and use.

BG BAU-SUPPORTED PRODUCTS

LADDERS AND ROLLING TOWERS



YOUR PATHWAY TO BONUS SUPPORT:

- > All Layher products shown here are supported by BG Bau.
- Members of BG Bau receive bonus support on the basis of the purchase costs
- > Send the application with a copy of the invoice to BG Bau.
- > You can find the application form, and other support schemes, at: bg-foerderung.layher-steigtechnik.com.
- > BG Bau will reimburse you for some of the costs. Examples for reimbursement can be found with the products.



Layher extension step ladder, 50%, up to max. € 300.-.



Layher aluminium heavy-duty steps (3 and 4 steps), **50%, up** to max. € 300.–.



Layher platform ladder (4, 5 and 6 steps), **50%, up to max**. €**500.**—.





SoloTower stair kit, 50%, up to max. €1500.-





of the Uni rolling tower family, **50 %, up to max. €500**.



CASTORS FROM LAYHER

Ref. No.	Description	Castor type	Illustration	Wheel	Wheel diameter [mm]	Bearing type (wheel hub)
1359.200	Castor 700	Height adjustable castor		Polyamide wheel	200	Plain bearing (steel sleeve in plastic hub)
1358.200	Polyurethane Castor 700	Height- adjustable castor		Polyamide wheel with polyurethane tire	200	Plain bearing (steel sleeve in plastic hub)
1260.201	Castor 1000	Height- adjustable castor		Polyamide wheel	200	Plain bearing (steel sleeve in plastic hub)
1260.202	Castor 1000 with electro- conductive polyurethane coating	Height- adjustable castor		Polyamide wheel with polyurethane tire	200	Sealed ball bearing
1267.200	Castor 1200 with half-coupler	Height- adjustable castor		Polyamide wheel	200	Plain bearing (steel sleeve in plastic hub)
1301.150	Castor 400	Castor with tube connector		Polyamide wheel	150	Plain bearing (steel sleeve in plastic hub)
1303.150	Polyurethane Castor 400	Castor with tube connector		Polyamide wheel with polyurethane tire	150	Plain bearing (steel sleeve in plastic hub)
1300.150	Castor d=150 mm with spindle 250	Height- adjustable castor		Polyamide wheel	150	Plain bearing (steel sleeve in plastic hub)

Max. perm. load [kg] – braked	Max. dyn. load [kg] – unbraked – at 4 km/h and over a distance of 2500 m without obstacles	Temperature resistance	Application
700	350	-40 °C to +90 °C	All firm ground! E.g.: Concrete / screed / cobbles / wooden boards / asphalt
700	350	-20 °C to +50 °C	Firm ground with sensitive surface! E.g.: Tiles/natural stone/parquet/laminate Careful with sprung floors such as floors of sports halls, the max. load of the floor applies here, otherwise provision of a load-distributing base (plywood boards) is essential!
1000	1000	-40 °C to +90 °C	All firm ground! E.g.: Concrete / screed / cobbles / wooden boards / asphalt
1000	800	25 °C to +70 °C, short-term to +90 °C	Firm ground with sensitive surface! E.g.: Tiles/natural stone/parquet/laminate Useable in explosive or EiSD areas, thanks to the bleeder resistance < $10^4 \Omega$. Careful with sprung floors such as floors of sports halls, the max. load of the floor applies here, otherwise provision of a load-distributing base (plywood boards) is essential!
1200	960	-40 °C to +90 °C	All firm ground! E.g.: Concrete / screed / cobbles / wooden boards / asphalt
400	200	-40 °C to +90 °C	All firm ground! E.g.: Concrete / screed / cobbles / wooden boards / asphalt
400	200	20 °C to +50 °C	Firm ground with sensitive surface! E.g.: Tiles/natural stone/parquet/laminate Careful with sprung floors such as floors of sports halls, the max. load of the floor applies here, otherwise provision of a load-distributing base (plywood boards) is essential!
400	400	-20 °C to +50 °C	All firm ground! E.g.: Concrete/screed/cobbles/wooden boards/asphalt



Pos.	Description	Dimensions [m]	Weight approx. [kg]	Ref. No.	SoloTower	Zifa	Uni Light	Uni Compact	Uni Standard	Uni Wide	Uni Comfort	Staro
1	Castor 400, d=150 mm Plastic wheel, with simple brake lever. Permissible load: 4 kN (\approx 400 kg)	d=0.15	2.5	1301.150		•	•					
2	Castor 400, d=150 mm with polyurethane tyre Plastic wheel with polyurethane tyre, special wheel for sensitive floor surfaces. Permissible load: 4 kN (\approx 400 kg)	d=0.15	2.7	1303.150 🖷		•	•					
3	Castor, d=150 mm with spindle 250 Plastic wheel, with base jack, adjustment range $0.2 - 0.35$ m, castor with double brake lever and load centering in the braked state. Permissible load: 7 kN (\approx 700 kg)	d=0.15	3.9	1300.150 🖷	•	•	•	•	•	•	•	
4	Castor 700 Plastic wheel, d=200 mm. With base jack, adjustment range $0.30-0.60$ m, spindle nut with lock, castor with double brake lever and load centering in the braked state. Permissible load: 7.0 kN (\approx 700 kg)	d=0.20	6.8	1359.200	•	•	•	•	•	•	•	
5	Castor 700, with polyurethane tyre Plastic wheel, d=200 mm. With base jack, adjustment range $0.30-0.60$ m, spindle nut with lock, castor with double brake lever and load centering in the braked state. Permissible load: 7.0 kN (\approx 700 kg)	d=0.20	7.0	1358.200 🖷	•	•	•	•	•	•	•	
6	Castor 1000 Plastic wheel, d=200 mm of polyamide. With base jack, adjustment range $0.30-0.60$ m, spindle nut with lock, castor with double brake lever and load centering in the braked state. Permissible load: 10 kN (\approx 1,000 kg)	d=0.20	6.3	1260.201	•	•	•	•	•	•	•	
7	Castor 1000, with electroconductive polyurethane coating Plastic wheel, d=200 mm of polyamide with coating of electroconductive polyurethane. With base jack, adjustment range 0.30-0.60 m, spindle nut with lock, castor with double brake lever and load centering in the braked state. Permissible load: 10 kN Special castor for sensitive floorings and thanks to electro- conductability also usable in explosive or ESD areas. Bleeder resistance according to DIN EN 12526 < 10 ⁴ Ω	d=0.20	6.8	1260.202 🖷	•	•	•	•	•	•	•	
8	Castor 1200, with half-coupler reinforced plastic wheel, d=200 mm, with base jack, adjustment range $0.30-0.60$ m, spindle nut with lock. Permissible load: 12 kN (\approx 1,200 kg)	d=0.20	12.0	1267.200 🛎	•	•	•	•	•	•	•	
9	Adjustable base plate 60 with lock steel, hot-dip galvanized, with nut, base plate 150 x 150 mm, max. spindle travel 0.40 m	0.60	3.8	1257.060	•	•	•	•	•	•	•	
10	Rubber pad for base plate		0.4	4000.500 🛎	•		•		•			
11	Mobile beam with bar Steel rectangular tube, hot-dip-galvanized. For widening the base of towers	1.80	16.9	1323.180		•	•		•			
12	Mobile beam with bar, adjustable Steel rectangular tube, hot-dip-galvanized. System component for base widening	2.30 - 3.20	42.5	1323.320				•	•	•		
13	Mobile beam with 2 spigots, adjustable Steel rectangular tube, hot-dip-galvanized. For widening the base for special mobile assemblies. System assemblies only possible in conjunction with Ref. No. 1337.000 (see page 117)	2.30 - 3.20	42.6	1338.320		•	•	•	•	•		
14	Mobile beam Steel rectangular tube, hot-dip-galvanized. For widening the base of towers	1.80	14.4	1214.180		•	•					

WS = wrench size PU = packaging unit = available ex works 🙂 = delivery time on request 🖽 = only available in this packaging unit 🕨 = included in tower kit 🕨 = optional accessory for tower model











Pos.	Description	Dimensions L/H x W [m]	Weight approx. [kg]	Ref. No.	SoloTower	Zifa	Uni Light	Uni Compact	Uni Standard	Uni Wide	Uni Comfort	Staro
1	Basic tube	1.80	7.7	1211.180 🛎		•	•	•				
	steel tube, hot-dip galvanized	2.85	12.2	1211.285					•	•		
2	Base strut	1.80	6.2	1324.180		•	•	•				
	with 2 half-couplers, steel tube, hot-dip galvanized	2.85	9.3	1324.285					•	•		
3	Telescopic spacer tube 1.25 m	1.25 — 1.90	3.0	1275.001 🖴	•		•		•			
4	Access ledger	0.30	2.9	1344.002 🛎								
	aluminium	0.75	3.3	1344.003				•		•	•	
5	Ballast (10 kg) steel, hot-dip galvanized with half-coupler. For ballasting of towers refer to the instructions for assembly and use of mobile work platforms		10.0	1249.000	•	•	•	•	•	•	•	
6	Spigot, adjustable steel, hot-dip galvanized. System assemblies only possible in conjunction with Ref. No. 1338.320 (see page 115)		2.1	1337.000		•	•	•	•	•		
7	Guardrail support	1.00	1.3	1297.100 🖴		•	•	•	•	•	•	
8	Ladder frame	0.50 x 0.75	2.7	1297.002 🛎	•							
	aluminium, Rungs with non-slip grooving	1.00 x 0.75	4.7	1297.004	•	•	•		•			
		2.00 x 0.75	8.6	1297.008								
		1.00 x 1.50	/.0	1299.004				ł			<u>}</u>	
		2.00 X 1.50	13.5	1299.008				1		1	1	
9	Passageway ladder frame aluminium, Rungs with non-slip grooving	2.00 x 0.75	10.1	1296.008 🕮	•		•		•			
10	Suspension ladder 75	1.00 x 0.75	6.3	1298.004 🕒								
	aluminium, Rungs with non-slip grooving Spigot bolted using 4 bolts M12 x 60 with nuts	2.00 x 0.75	10.3	1298.008 ^(b)		•	•		•			
11	Suspended ladder	0.40 x 1.80	2.8	1247.006 🕒	•		•		•			
12	Zifa 75 basic tower aluminium Dimensions when folded together: 0.95 x 1.50 x 0.30 m	1.80 x 1.50 x 0.75	20.2	1300.006		•						
13	Staro basic tower aluminium. Including 4 clips. Dimensions when folded together: 2.00 x 1.60 x 0.25 m	2.00 x 1.60 x 2.00	28.8	1224.000								•
14	Leg tube with castor 400 d=150 mm With simple brake lever and load centering in the braked state. Wheel and slewing ring can be locked. Steel, plastic wheel	1.95	6.6	1312.150								•



Pos.	Description	Dimensions L/H x W [m]	Weight approx. [kg]	Ref. No.	SoloTower	Zifa	Uni Light	Uni Compact	Uni Standard	Uni Wide	Uni Comfort	Staro
1	Spring clip, steel		0.1	1250.000	۲	×		۲	۲	۲		Þ
2	Guardrail, aluminium	1.80	2.3	1205.180		۲	۲	۲			Þ	
		2.85	3.6	1205.285					۲	۲		
3	Staro guardrail, aluminium	1.90	2.7	1227.190								Þ
4	Double guardrail, aluminium	1.80 x 0.50	5.8	1206.180		Þ		۲				
		2.85 x 0.50	8.0	1206.285					۲	۲		
5	SoloTower double guardrail, aluminium	1.13 x 0.50	5.9	1342.113 🖴	۲							
6	SoloTower telescopic guardrail, aluminium	1.13 - 1.72	3.0	1204.113 🖴	•							
7	Beam, aluminium for use as support beam in the modular system or as double guardrail	1.80 x 0.50 2.85 x 0.50	7.7 9.6	1207.180 🚔 1207.285		•	•	•	•	•	•	
8	Intermediate guardrail aluminium	1.90	1.9	1224.190								•
9	Diagonal brace	1.95	2.8	1208.195		•	Þ	•				
	alummum	2.50	3.3 3.8	1208.180			1	1	•	•	1	
		3.35	4.1	1208.285					•	•		
10	Deck diagonal brace aluminium	2.50 3.35	4.2 5.0	1347.250 🖴 1347.335		•	•	•	•	•	•	
11	Horizontal diagonal brace	1.95	3.5	1209.180		۲	۲					
12	Horizontal diagonal brace, adjustable aluminium	3.20 - 4.00	6.1	1318.000						•	•	
13	Deck	1.80 x 0.68	13.3	1241.180		►	►	•			▶	
	aluminium frame, with plywood deck and hatch with phenolic resin coating	2.85 x 0.68	20.0	1241.285					•	•		
14	Staro deck aluminium frame, with plywood deck and hatch with phenolic resin coating	1.90 x 0.60	13.1	1241.190								•
15	Stairway access deck aluminium frame, with plywood deck and hatch with phenolic resin coating.	1.80 x 0.68	12.2	1243.180							•	
16	Access deck aluminium frame, with plywood deck and hatch with phenolic resin coating	1.80 x 0.68 2.85 x 0.68	15.0 21.6	1242.180 1242.285		•	•	•	•	•		
17	SoloTower access deck aluminium frame, with plywood deck and hatch with phenolic resin coating	0.75 x 1.13	11.4	1242.113 🕮	•							
18	Bridging deck Only for use in double structures of Uni Standard towers	2.85 x 0.66	19.8	1343.285 🕒				•				
19	Intermediate deck, aluminium for console bracket structures	2.85 x 0.23	10.5	1339.285 🖷				•	•			



Pos.	Description	Dimensions L/H x W [m]	Weight approx. [kg]	Ref. No.	SoloTower	Zifa	Uni Light	Uni Compact	Uni Standard	Uni Wide	Uni Comfort	Staro
1	Toe board , wood for twin towers and bridging deck	0.60 x 0.15	3.5	1340.058 🕒					•			
2	Toe board with claw, wood	1.80 x 0.15 1.95 x 0.15 2.85 x 0.15	4.2 4.2 5.6	1439.180 1439.195 1439.285		•	•	•	•	•	•	•
3	End toe board, wood	0.75 x 0.15 1.44 x 0.15 1.90 x 0.15	1.6 2.9 3.9	1438.075 1438.144 1438.190		•	•	•	•	•	•	•
4	SoloTower toe board unit, aluminium		5.6	1240.113 🛎	•							
5	Landing stairway, aluminium		15.5	1212.180							•	
6	Stairway guardrail, aluminium for use for landing-type stairway Ref. No. 1212.180	3.07	3.8	1213.180							•	
7	Strut for outrigger, aluminium locks the outrigger Ref. No. 1216.000	3.75	5.4	1217.375 🛎							•	
8	Outrigger, aluminium for widening the bases of higher structures. Locking with horizontal diagonal brace Ref. No. 1209.285	1.50	8.2	1216.000							•	
9	Stairway guardrail, aluminium	1.20	1.8	1327.120 🛎							•	
10	Guardrail, aluminium for twin towers and bridging	0.58 x 0.50	4.7	1342.058 🕒					•			
11	Rotation preventer, aluminium	0.5	2.8	1248.261	•	•	•	•	•	•		
12	Stabilizer, aluminium	1.80	4.2	1248.180 ^(b)		•	•	•	•	•		
13	Stabilizer, extendable, aluminium	2.60 - 3.40	8.5	1248.260		•	•	•	•	•		
14	Stabilizer, aluminium	5.00	14.9	1248.500					•	•		
15	SoloTower stabilizer, aluminium	1.2-2.1	5.2	1248.000 🛎	•							
16	Ladder for Staro rolling tower, aluminium 6 double rungs		7.8	1246.006								•
17	Suspended step ladder, aluminium 8 steps, with snap-on hook and castors at the ladder base	2.20	6.8	1314.108 🛎					•	•		
18	Ladder support set for suspended ladder Ref. No. 1314.108		2.0	1314.109 🛎					•	•		
19	Uni distance tube, aluminium tube, with hook and rubber foot	1.10	1.4	1275.110 🛎	۲	•	۲		۲			
		1.80	2.1	1275.180 🛎	•			•		•	•	
20	Swivel coupler steel, galvanized	WS 19	1.5	4/02.019								
0.1		WS 22	1.5	4/02.022								
21	steel, galvanized	WS 19	1.3	4700.019								
		VV5 ZZ	1.3	4700.022				•		•	•	

Components





Pos.	Description	Dimensions L/H x W [m]	Weight approx. [kg]	Ref. No.	SoloTower	Zifa	Uni Light	Uni Compact	Uni Standard	Uni Wide	Uni Comfort	Alu bridg. beam 600
1	Hand wheel with bush		0.1	6491.422 🛎	•							
2	Uni assembly hook, pair		1.2	1300.010								
3	SoloTower assembly hook, 4 pieces		1.2	1300.002 🛎	►							
4	Console bracket, aluminium for widening of the work platform on one or two sides	0.75 x 0.90	5.4	1341.075 🖷					•	•		
5	Double guardrail with toe board, aluminium	2.00 x 1.10	9.7	1332.200								•
	folds together for transport	3.00 x 1.10	12.9	1332.300								•
6	Guardrail fixture, aluminium for fastening the double guardrail to the Alu bridging beam for Ref. No. 1332.xxx	0.50	0.9	1330.000								•
7	Guardrail locking pin, steel for securing the double guardrail with the guardrail fixture for Ref. No. 1330.xxx		0.1	1333.000								•
8	Guardrail mounting standard, aluminium for connecting the three-part brick guard made from scaffolding tubes, guardrail clamps and toe board	1.20	2.4	1334.000								•
9	Clamp, steel for connecting the Alu bridging beams Ref. No.1348.xxx		0.4	1331.000								•
10	Tube pallet 125 steel, hot-dip galvanized, length of pallet posts: 0.86 m, load 1,500 kg.	1.37 x 0.97	32.0	5105.125		•	•	•	•	•	• 1	•
11	SoloTower assembly bag		0.2	1300.003 🖴	►	•						• •
12	Identification sign Block à 50 pcs.		0.5	6344.400 🛎	•	•	•	•	•	•		•
13	See-through pocket for Ref. No. 6344.400, 10 pcs. ⊞ with integrated prohibition sign		0.4	6344.011		•					•	•

Spare parts

Pos.	Description	Dimensions L/H x W [m]	Weight approx. [kg]	PU	Ref. No.
14	Wheel including axle for Ref. No. 1308.150 / 1302.150 / 1301.150 / 1312.150	d=0.15	0.6		6496.921 🛎
15	Wheel including axle for Ref. No. 1309.150 / 1303.150	d=0.15	0.6		6491.501 🕒
16	Wheel including axle for Ref. No. 1259.200 / 1259.201 / 1359.200	d=0.20	0.9		6496.922 🛎
17	Finger 42 mm pair, blue complete with springs and rivets		0.4	2 🎟	6491.416 🖷
18	Finger 42 mm pair, grey complete with springs and rivets		0.4	2 🎟	6491.417 🖷
19	Finger 42 mm pair, orange complete with springs and rivets		0.4	2 🎟	6496.923 🖷
20	Finger 48 mm pair, orange complete with springs and rivets		0.4	2 🎟	6496.924 🖷



Layher is your dependable partner with more than 75 years of experience. "Made by Layher" always means "Made in Germany" too – and that goes for the entire product range. Superb quality – and all from one source.



Proximity to the customer is a central factor behind Layher's success – geographically speaking too. Wherever our customers need us, we will be there – with our advice, assistance and solutions.



Wilhelm Layher GmbH & Co KG Scaffolding Grandstands Ladders



More Possibilities. The Scaffolding System.

Ochsenbacher Strasse 56 74363 Gueglingen-Eibensbach Germany Post Box 40 74361 Gueglingen-Eibensbach Germany Telephone +49 (0) 71 35 70-0 Telefax +49 (0) 71 35 70-2 65 E-mail export@layher.com www.layher.com

